

SEMI FLUID GREASE

Premium Lithium Grease

Issue: July 2017

PRODUCT CODE	PACK SIZE	CTN / QTY
SEMI00045	450gm	6
SEMI0005	500ml	6
SEMI020	20 KG	





Description

Penrite Semi Fluid Grease is an extreme pressure, NLGI 00, lithium soap thickened grease, blended using extreme pressure additives, anti-wear, rust and oxidation inhibitors.

Application

Penrite Semi Fluid Grease may be used in the following applications:

- Trailer bearing hubs where heavy oils are specified and leakage is a problem
- Chain cases
- Slow speed industrial gear boxes where AGMA 7EP (ISO 460 and above) or heavier oils are specified
- Leaky gear boxes
- Reduction gear boxes in slasher mowers
- Track rollers in earthmoving equipment.
- Centralised lubrication systems that require fluid (or "liquid") type greases
- Burman motorcycle gear boxes

Normal operating temperature range is from -20° C to 130° C.

Product Benefits

- Extends bearing and gear life by minimising wear and shock loads
- Does not splash so maximises lubrication efficiency
- Resists leakage even under heavily loaded conditions
- Resists squeeze out
- Good low and high temperature fluidity
- Protects against rust and corrosion
- Good water resistance
- Lead and Chlorine free

Typical Data

Soap Type	Lithium
NLGI	00
Drop Point, °C	170
Four Ball Weld Load, kg	250
Timken OK Load, kg	18
Copper Corrosion	1a
Colour	Light Brown



Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. A MSDS is available on request.



PENRITE OIL COMPANY PTY LTD

88 Lewis Road, Wantirna South Victoria AUSTRALIA 3152, ABN 25 005 001 525 Enquiries: Phone 1300-PENRITE (1300 736 7483 Fax: 1800-PENRITE (1800 736 7483) International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977 New Zealand Ph: 0800 533 698, Fax: 0508 736 748 PROUDLY AUSTRALIAN FAMILY OWNED SINCE 1926