



PENRITE



85% REDUCTION IN LANDFILL WASTE

SEMI SYNTHETIC 15W-40 (Semi Syn.)

Last updated: 08/11/2017 5:29 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
ED15W40001	1L	6
ED15W40004	4L (NZ)	4
ED15W40005	5L	4
ED15W40020	20L	

PRODUCT BENEFITS

Semi Synthetic 15W-40 is a premium quality, semi synthetic, SAE 15W-40, friction modified engine oil. It is formulated using the latest engine oil technology and high performance additives including a FULL ZINC anti-wear package for complete engine protection. **Licensed** by the API (American Petroleum Institute) to meet SN specifications ensuring quality and satisfaction. It also meets European ACEA A3/B4 specifications.



APPROVALS AND LICENSES

- [Click Here](#) for API License

APPLICATION

Semi Synthetic 15W-40 is designed for use in modern 4, 6 & 8+ cylinder, multi-cam, multi-valve (including VVT), naturally aspirated, supercharged & turbocharged engines. It is not recommended for Rotary engines.

Semi Synthetic 15W-40 is designed for modern petrol and light duty diesel engines where the use of SAE 15W-40 or 20W-40 oil is specified in the owner's handbook. It meets the requirements of API SN/CF and the European Standards ACEA A3/B4, as well as many manufacturers' specifications, providing increased wear protection, better resistance to sludge formation and lower piston deposits than previous and lower grade oils. It can also be used where previous API specifications SM (2004-10), SL (2001-04) and SJ were recommended.

Semi Synthetic 15W-40 is suitable for use in passenger cars, 4WDs & light commercial vehicles and is compatible with Petrol/LPG (Dual Fuel), E10, Diesel (without DPF) and most other other conventional fuels. If using with E85 fuel, Penrite recommend more frequent oil change periods.

NOTE: when changing oil, Penrite recommend using **Penrite Engine Flush**, a fast acting, solvent free, engine cleaning formulation that removes engine deposits, sludge and contaminants with the oil service drain. It contains added zinc for engine wear protection and its fast acting formulation works in 10 minutes.

PRODUCT BENEFITS

- **COMPLETE** engine protection
- **API** tested and registered for quality guarantee assurance
- **LATEST** oil specification technology meeting API SN and ACEA A3/B4 for maximum wear protection, minimum sludge formation & reduced piston deposits
- **FULL ZINC** anti-wear additive package for complete engine wear protection
- **SHEAR STABLE** VI Improvers help maintain oil viscosity
- **CATALYST** and oxygen sensor friendly
- **PETROL & DIESEL** compatible engine oil

MANUFACTURER'S (OEM) APPROVALS & INDUSTRY LICENSES

- API LICENSED

INDUSTRY & MANUFACTURER'S SPECIFICATIONS

- ACEA A3/B4
- API SJ/CF
- API SL/CF
- API SM/CF
- API SN/CF
- MB 229.1.
- VW 501 01
- VW 502 00



PENRITE



**85% REDUCTION
IN LANDFILL
WASTE**

TYPICAL DATA

Density at 15°C, kg/L	0.868
Viscosity, Kinematic, cSt at 40°C	114
Viscosity, Kinematic, cSt at 100°C	15.3
Viscosity Index	140
Cold Cranking Viscosity, cP at -20°C	5036
Zinc, Mass %	0.109
Phosphorus, Mass %	0.100
Sulphated Ash, mass %	1.29
Base Number	10.1