



SMALL ENGINE FOUR STROKE Multigrade 10W-30

Semi Synthetic Engine Oil

Issue: April 2017



| PRODUCT CODE | PACK SIZE | CTN QTY |
|--------------|-----------|---------|
| SEFS1030001 | 1 Litre | 6 |
| SEFS10300025 | 2.5 Litre | 4 |
| SEFS1030005 | 5 Litre | 4 |
| SEFS1030020 | 20 Litre | 1 |
| SEFS1030205 | 205 Litre | 1 |

Description

Small Engine Four Stroke 10W-30 is non-friction modified, semi synthetic engine oil, formulated with modern additives for use in small four stroke engines. It provides complete protection against wear & corrosion and is designed to meet the lubrication needs of small four stroke engines.

Application

Small Engine Four Stroke 10W-30 is suitable for use in lawnmowers, generator sets and pumps, four stroke outboards / inboards, four stroke brushcutters and in other gardening equipment that specify this viscosity grade.

Small Engine Four Stroke 10W-30 is suitable for many 4 stroke motorcycles including those with wet clutches. It can also be used in motor cycles with a separate gear box and clutch assembly as a gear oil where the manufacturer recommends a 10W-30 engine oil for this application.

Air Cooled Engines

| | | | |
|---------------------------------------|---------------------------------------|-------------|--------|
| Cummins | Graden | Greenfield | Honda |
| Husqvarna | John Deere | Kawasaki | Kubota |
| Robin | Simplicity | Subaru | Toro |
| Yamaha | Briggs and Stratton (selected models) | | |
| Kohler (Aegis, Command, Triad series) | | & Many More | |

4 Stroke Outboards/Marine Stern Drives*

| | | | |
|----------|--------|----------|---------|
| Evinrude | Honda | Johnson | Tohatsu |
| Yamaha | Yanmar | And more | |

* May also use Marine Outboard Four Stroke Engine Oil 10W-40

Product Benefits

- Excellent engine cleanliness
- Ultimate wear protection.
- Protect against rust and corrosion.

Industry Specifications

| | | |
|-----------|------------|------------------------------|
| API SL/CF | ACEA A3/B3 | CHINA NATIONAL GB 11121-2006 |
|-----------|------------|------------------------------|

Typical Data

| | |
|-----------------------------------|-------|
| Colour | Amber |
| Density at 15°C, kg/L | 0.869 |
| Viscosity, Kinematic, cSt | |
| at 40°C | 85 |
| at 100°C | 12.0 |
| Viscosity Index | 135 |
| Viscosity, Cold Cranking @ -25 °C | 4865 |
| Sulphated Ash, mass % | 1.34 |
| Phosphorus, mass % | 0.110 |
| Zinc, mass% | 0.122 |
| Base Number | 10.7 |

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
 Victoria AUSTRALIA 3152, ABN 25 005 001 525
 Enquiries: Phone 1300-PENRITE (1300 736 748)
 Fax: 1800-PENRITE (1800 736 748)
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748
 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
 FAMILY OWNED
 SINCE 1926**

