



PENRITE



85% REDUCTION
IN LANDFILL
WASTE

STEAM CYLINDER OIL

Last updated: 24/04/2019 1:25 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
CYL900205	205L	

PRODUCT BENEFITS

Penrite Cyl Oil Mineral 900 is a heavy straight run mineral oil manufactured via a hydro-treating process that **DOES NOT** contain any compounding additives.

APPLICATION

Penrite Cyl Oil Mineral 900 may be used for the lubrication of steam cylinders as well as valve lubrication and is suitable for heavily loaded slow moving bearings and gears, where a demulsifiable oil is required.

Penrite Cyl Oil Mineral 900 can also be used in old gearboxes where a 250 style oil is required and no extreme pressure additives are needed.

PRODUCT BENEFITS

- Extended oil life due to inherent oxidation stability.
- Good demulsibility characteristics of the pure mineral oil allows for outstanding lubrication.

INDUSTRY & MANUFACTURER'S SPECIFICATIONS

TYPICAL DATA

Colour	Amber
Density at 15°C, kg/L	0.911
Viscosity, Kinematic, cSt at 40°C	930
Viscosity, Kinematic, cSt at 100°C	41.9
Viscosity Index	74
Pour Point, °C	+2.0

