



100 Celebrating
YEARS

**AUSTRALIAN OWNED AND
TRUSTED SINCE 1926** 

SUPER DOT 4 BRAKE FLUID

Last updated: 22/11/2017 4:34 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
BF0005	500mL	6
BF004	4L	4
BF020	20L	

PRODUCT BENEFITS

SUPER DOT 4 BRAKE FLUID is a premium quality, non-silicone, non-mineral/petroleum based, fully synthetic brake fluid designed for use in a wide range of brake and clutch applications

APPLICATION

SUPER DOT 4 BRAKE FLUID is recommended for re-fill or top-up of brake and clutch systems in passenger cars, 4WD's, motorcycles, light and heavy duty commercial vehicles, mining, construction and agricultural equipment that require a non petroleum based DOT 3, DOT 4 or Super DOT 4 brake & clutch hydraulic fluid.

SUPER DOT 4 BRAKE FLUID is suitable for use where the vehicle manufacturer specifies DOT 3 or DOT 4 brake fluid.

SUPER DOT 4 BRAKE FLUID should be changed according to the manufacturers service specifications.

SUPER DOT 4 BRAKE FLUID can be used for first fill or refilling a brake or clutch system. For best results, the system should always be flushed with Penrite Brake Fluid SUPER DOT 4 prior to first fill or before refilling the system.

PLEASE NOTE

- Do not mix this product with SILICONE DOT 5 or MINERAL type brake fluids.
- For vehicles that require mineral based products i.e. Citroen, **Penrite LHM Plus** should be used.
- Not mixable with Silicone type assembly compounds
- Avoid contact with skin, varnish & paint. If skin contact occurs wash with water.

CAUTION

Brake Fluids are naturally hygroscopic and will absorb water from the air. This will lower the effectiveness of the product. After opening bottle, ensure cap is resealed tightly to avoid water contamination.

PRODUCT BENEFITS

- Excellent braking response due to high boiling point of fluid.
- High wet boiling point ensures long term retention of fluid performance.
- Better performance for life of fluid compared to DOT 3 fluids.
- Compatible with all common brake system materials
- Compatible with DOT 3 & DOT 5.1 (low temperature, non-silicone type)

PRODUCT PERFORMANCE LEVELS

- AS 1960.1-1995
- DOT 3
- DOT 4
- Ford ESZ-M6C55-A
- Holden HN 1796
- ISO 4925
- JIS K2233 (Japan)
- SAE J1703
- SAE J1704
- SUPER DOT 4
- US FMVSS No 116 Super DOT 4





100 *Celebrating*
YEARS

**AUSTRALIAN OWNED AND
TRUSTED SINCE 1926** 

TYPICAL DATA

Colour	Amber
Density at 20°C, kg/L	1.069
Viscosity, Kinematic, cSt at -40°C	1147
Viscosity, Kinematic, cSt at 100°C	2.23
Equilibrium Reflux Boiling Point (wet), (typical)	183°C (361°F)
Equilibrium Reflux Boiling Point (dry), (typical)	275°C (525°F)