



PENRITE

VANTAGE SEMI SYNTHETIC 15W-40

Semi Synthetic Engine Oil

Issue: November 2016

Product Code	Pack Size	Ctn / Qty
VANSEMI15W40001	1 Litre	6
VANSEMI15W40004	4 Litre	4
VANSEMI15W40006	6 Litre	3
VANSEMI15W40010	10 Litre	1
VANSEMI15W40020	20 Litre	1



Description

Vantage Semi Synthetic 15W-40 is a premium quality, semi synthetic, SAE 15W-40 engine oil for use in a wide range of modern motor vehicles. It features the latest engine oil technology, including a **FULL ZINC** anti-wear package for advanced engine protection.

Vantage Semi Synthetic 15W-40 is **Licensed** by the API (American Petroleum Institute) to meet **SN** specifications, ensuring quality and satisfaction.

Application

Vantage Semi Synthetic 15W-40 is designed for use in modern 4, 6 & 8+ cylinder multi-cam, multi-valve (including VVT), naturally aspirated, supercharged & turbocharged engines. It is **not suitable** for Rotary engines. It is suitable for use in passenger cars, 4WDs & light commercial vehicles and is compatible with Petrol/LPG (Dual Fuel), E10, Diesel (without DPF) and most other conventional fuels.

Vantage Semi Synthetic 15W-40 is designed for modern petrol and light duty diesel engines where the use of SAE 15W-40 or 20W-40 oil is specified in the owner's handbook. It meets the requirements of API SN/CF and the European Standards ACEA A3/B4, as well as many manufacturers' specifications providing increased wear protection, better resistance to sludge formation and lower piston deposits than previous and lower grade oils. It can also be used where previous API specifications SM (2004-10), SL (2001-04), SJ were recommended and where the earlier ILSAC GF-3 or GF-4 specifications were required.

Vantage Semi Synthetic 15W-40 is not recommended for use in four stroke motorcycles with wet clutches. The appropriate Penrite MC-4ST motorcycle oil should be used for these applications.

Product Benefits

- **LATEST** oil specification technology meeting **API SN** and **ACEA A3/B4** for maximum wear protection, minimum sludge formation & reduced piston deposits
- **FULL ZINC** anti-wear additive package for complete engine wear protection
- **SHEAR STABLE** VI Improvers help maintain oil viscosity
- **CATALYST** and oxygen sensor friendly
- **PETROL & DIESEL** compatible engine oil
- **COMPLETE** engine protection

Industry Specifications

API SN/CF	ACEA A3/B4	MB 229.1
VW 501 01 / 502.00 / 505.00	Renault RN0700 / RN0710	

Typical Data

Density at 15°C, kg/L	0.873
Viscosity, Kinematic, cSt	
at 40°C	109
at 100°C	14.8
Viscosity Index	148
Viscosity, Cold Cranking @ -20 °C	4969
Zinc, mass %	0.109
Phosphorus, mass%	0.100
CA, mass%	0.331
Sulphated Ash, mass %	1.29
Base Number	10.1

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
 Victoria AUSTRALIA 3152, ABN 25 005 001 525
 Enquiries: Phone 1300-PENRITE (1300 736 748)
 Fax: 1800-PENRITE (1800 736 748)
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748
United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
 FAMILY OWNED
 SINCE 1926**

