



COOLANTS





WHAT MAKES PENRITE COOLANT DIFFERENT?

- **FULLY COMPATIBLE** with the OEM products
- **MEETS MANUFACTURERS'** service intervals
- **TESTED AND APPROVED** for warranty and non-warranty service
- **PREMIX CONCENTRATION 50%** as per all manufacturer requirements
- **MIXES** with all coolant types
- **INITIAL FACTORY FILL** as used by OEM's





RED OEM COOLANT

8 YEAR/500,000KM

ANTI-FREEZE ANTI-BOIL Coolant

Si-OAT Technology

OEM LICENSED and Approved

SUITABLE for approx. 8.8 Million vehicles in Australia & NZ

SUITABLE for VW, Audi, Holden, Toyota and Mercedes

PREMIX concentration 50% as per OEM requirements

COMPATIBLE with OEM products - G12++

OEM APPROVALS & INDUSTRY LICENSES:

Audi TL 774-G
Bentley TL 774-G
Bugatti TL 774-G
Cummins CES 14603
Deutsche Bundeswehr TL 6850-0038/6
Deutz DQC CC-14
Deutz Fahr Harvesters (from 04/2017)
Ducati (approved)
Irizar (from 09/2016)
Lamborghini TL 774-G
Liebherr Minimum LH-01-COL3A
MAN 324 Type Si-OAT
MB-Approval 325.5/325.6/326.6
MTU MTL 5048
Porsche (From 2010)
Seat TL 774-G
Setra MB-Approval 325.5
Skoda TL 774-G
Smart MB-Approval 325.6 (from 05/2014)
VW TL 774-G

RED OEM COOLANT CONCENTRATE

1L	COOLRED001
2.5L	COOLRED0025
5L	COOLRED005
20L	COOLRED020
20L BOX	COOLRED020BOX
60L	COOLRED060
205L	COOLRED205

RED OEM COOLANT PREMIX

1L	COOLREDPMX001
5L	COOLREDPMX005
20L	COOLREDPMX020
205L	COOLREDPMX205



GREEN OEM COOLANT

8 YEAR/500,000KM

ANTI-FREEZE ANTI-BOIL Coolant

HOAT Technology (Hybrid)

OEM LICENSED and Approved

SUITABLE for approx. 5.5 Million vehicles in Australia & NZ

SUITABLE for BMW, Ford, Mini and Mazda

PREMIX concentration 50% as per OEM requirements

COMPATIBLE with OEM products - G11

GREEN OEM COOLANT CONCENTRATE

1L	COOLGREEN001
2.5L	COOLGREEN0025
5L	COOLGREEN005
20L	COOLGREEN020
20L BOX	COOLGREEN020BOX
60L	COOLGREEN060
205L	COOLGREEN205

GREEN OEM COOLANT PREMIX

1L	COOLGREENPMX001
5L	COOLGREENPMX005
20L	COOLGREENPMX020
205L	COOLGREENPMX205

OEM APPROVALS & INDUSTRY LICENSES:

Audi TL 774-C
BMW GS 94000
Deutz DQC CA-14
Eicher TMTL Part No. 93183798
Fendt
Ferrari (1979-2005)
Huerlimann (to 03/2017)
Jenbacher TA-Nr. 1000-021
Lamborghini Tractors (to 03/2017)
Liebherr LH-00-COL3A
MAN 324 NF
MAN Diesel & Turbo Liste 3.3.7
Maybach MB-Approval 325.0
MB-Approval 325.0
Mini BMW GS 94000
Mitsubishi Colt (2004-2007)
MTU MTL 5048
MWM 0199-99-2091-9 DE
Opel / Vauxhall (Until 2000) B 040 0240
Porsche (Until 1995)
Rolls Royce (From 1998) BMW GS 94000
Saab 690 1599
Same (to 03/2017)
Seat TL-774-C
Setra MB-Approval 325.0
Skoda TL 774-C
Smart MB-Approval 325.0
Tesla (From 2013)
Van Hool
Volvo Truck (From 2005)
VW TL 774-C



BLUE OEM COOLANT

8 YEAR/500,000KM

ANTI-FREEZE ANTI-BOIL Coolant

OAT Technology

SILICATE FREE

OEM Licensed and Approved

SUITABLE for approx. 4.0 Million vehicles in Australia & NZ

SUITABLE for Nissan, Subaru, Mitsubishi and Hyundai

SUITABLE concentration 50% as per OEM requirements

SUITABLE with OEM products - G12+ & G12

OEM APPROVALS & INDUSTRY LICENSES:

Audi TL 774-D/F
Bentley TL 774-D/F
DAF MAT 74002
Deutz DQC CB-14
Ferrari (from 2005)
Lamborghini TL 774-D/F
MAN 324 SNF
MB-Approval 325.3
Mini Diesel (2007-2011)
MTU MTL 5048
Porsche (1996-2009)
Seat TL 774-D/F
Siemens (approved)
Skoda TL 774-D/F
VW TL 774-D/F

BLUE OEM COOLANT CONCENTRATE

1L	COOLBLUE001
5L	COOLBLUE005
20L	COOLBLUE020

BLUE OEM COOLANT PREMIX

1L	COOLBLUEPMX001
5L	COOLBLUEPMX005



350,000 KM GREEN COOLANT

350,000KM drain intervals if used and maintained between 33% & 50%

MEETS with many manufacturer specifications

COMPATIBLE with all plastics, rubbers and seals

PROTECTS all internal surfaces from corrosion, including aluminium

PHOSPHATE FREE formulation allows use with hard water

SILICATE AND AMINE FREE

PERFORMANCE LEVEL:

AS/NZS 2108-2004 Type A
ASTM D-3306
BS 6580:1992
Chrysler MS-9769
Cummins CES 14603
Ford ESE M97B44-A
Ford WSS M97B51-A1
Holden HN 1825M
Holden HN 1899
Holden HN 2043
JCB STD00088
Leyland BLS.22.AF.01
MAN Liste 3.3.7
MTU MTL 5048
SAE J1034

350,000 KM GREEN COOLANT CONCENTRATE

1L	COOL3500001
2.5L	COOL3500025
5L	COOL350005
20L	COOL350020
20L BOX	COOL350020BOX
60L	COOL350060
205L	COOL350205

350,000 KM GREEN COOLANT PREMIX

1L	COOL350PMX001
5L	COOL350PMX005

MIXES WITH ALL COOLANT TYPES

UNIVERSAL TOP UP COOLANT PREMIX

COMPATIBLE with all coolant types

WILL NOT DISCOLOUR original coolant

COMPATIBLE with plastics, rubbers and seals

PROTECTS all internal surfaces from corrosion, including aluminium

LONG LIFE coolant & inhibitor pack

PHOSPHATE FREE formulation

READY TO USE - no mixing

PERFORMANCE LEVEL:

AS2108-2004 Type A
BS 6580
SAE J1034
ASTM D3306/4985
Ford M97-B44A/B44D/51A
Mitsubishi ES-X64217
Chrysler MS-9769
Nissan NES M5059
Toyota Long Life TSK2601G
GM 6277M/1825M/1899M
Holden HN2217/HN2043
& many more

UNIVERSAL COOLANT TOP UP PREMIX

1L	AFABPMXYELLOW001
----	------------------





PGXL COOLANT (PROPYLENE GLYCOL)

PROVIDES long Life protection for all metals

PROVIDES anti freeze anti boil protection

EXCELLENT protection for aluminium & heavy diesel wet sleeve liners

LOW TOXICITY compared to Mono Ethylene Glycol based coolants

CONTAINS nitrite and molybdate for cylinder liner protection.

COMPATIBLE with both OAT and conventional coolants

REQUIRES no dosing with supplemental cooling additive

PERFORMANCE LEVEL:

ASTM D-6211
ASTM D-6257
TMC RP 330



PGXL COOLANT CONCENTRATE

205L	PGXL205
------	---------

PGXL COOLANT PREMIX

20L	PGXLPMX020
205L	PGXLPMX205

HD LONGLIFE ECO1 AFAB

8 YEAR Heavy Duty drain intervals if used and maintained at 50%

15,000 HOUR drain intervals in off highway engines

PROTECTS all internal surfaces from corrosion, including aluminium

PHOSPHATE FREE formulation allows use with hard waters

SILICATE AND AMINE FREE

HEAVY DUTY PERFORMANCE

DOES NOT NEED SCA (Supplementary Coolant Additives)* but is Compatible with them

REDUCED operation costs due to less downtime required to service equipment

PERFORMANCE LEVEL:

AS2108-2004 Type A
ASTM D3306/4985/6210
SAE J1034/J1941
Caterpillar EC-1
MAN 324
Mack O14 GS 17009
Volvo VCS
Isuzu (GM6277M)
MTU MTL 5048
Freightliner 48-2288D,
Kenworth R026-170-97
Detroit 7SE-298

HD LONG LIFE ECO1 AFAB CONCENTRATE

20L	AFABECO1020
205L	AFABECO1205

HD LONG LIFE ECO1 AFAB PREMIX

20L	AFABECO1PMX020
205L	AFABECO1PMX205



APPROVED BY



TAKE IT TO TEN



10 TENTHS RACE COOLANT INHIBITOR

LOWERS engine operating temperatures preventing damage

LEAVES NO slippery residue if dropped on a race track

CONTAINS a conventional Hybrid inhibitor

REMOVES cavitation for better heat dissipation

COMPATIBLE with seals, pipes & hoses

PROTECTS all metal types from corrosion

PROTECTS water pumps and seals

BIODEGRADABLE and environmentally friendly

LASTS 3 TO 5 YEARS or 150,000km when used and maintained at correct concentration

PERFORMANCE LEVEL:

AS 2108-2004 Type B

10 TENTHS RACE COOLANT INHIBITOR CONCENTRATE

1L	RCI001
----	--------

10 TENTHS RACE COOLANT INHIBITOR PREMIX

5L	RCIPMX005
----	-----------

► **JACK SIMPSON**
450 CLASS WINNER
FINKE 2019

10 TENTHS PERFORMANCE



NEW POWER SPORTS COOLANT PREMIX IS READY TO USE.

Low toxic, propylene glycol based, Anti-Freeze
Anti-Boil coolant premix.

10 TENTHS POWER SPORTS COOLANT

MUCH SAFER for the environment

ANTI-FREEZE ANTI-BOIL protection

EXCELLENT protection for off road and marine power
sports equipment

LOW TOXICITY compared to Mono Ethylene Glycol
based coolants

COMPATIBLE with most coolant types

PREMIXED at 50/50 ratio so no mixing required

LASTS for 3 Years or 500 hours

PROVIDES long life protection for all metals, plastics,
rubbers and seals



PERFORMANCE LEVEL:

ASTM D-6211
ASTM D-6257
TMC RP 330

10 TENTHS POWER SPORTS COOLANT PREMIX

1L	COOLPOWERPMX001
5L	COOLPOWERPMX005



GREEN 100,000KM RADIATOR CORROSION INHIBITOR

TYPE B - Inhibitor only

PROTECTS all internal surfaces from corrosion

1L MAKE UP TO 20L

PERFORMANCE LEVEL:

AS/NZS 2108.1-1997 Type B
Deutz-MWM 0199-209
Ford ESD-M99B166C
MAN 248/B&W D36 5600
Sulzer Diesel ZBS0503
Wartsila 32-9011

GREEN RADIATOR CORROSION INHIBITOR CONCENTRATE

500mL	COOL10005
1L	COOL1001
20L	COOL1020

RED 100,000KM RADIATOR CORROSION INHIBITOR

TYPE B - Inhibitor only

ANTI FOAM AGENT to help protect against cavitation.

HELPS prevent wet liner erosion

1L MAKE UP TO 20L

PERFORMANCE LEVEL:

AS/NZS 2108.1-1997 Type B
Deutz-MWM 0199-209
Ford ESD-M99B166C
MAN 248/B&W D36 5600
Sulzer Diesel ZBS0503
Wartsila 32-9011

RED RADIATOR CORROSION INHIBITOR CONCENTRATE

1L	COOL100RED001
----	---------------



CLASSIC CAR COOLANT

SUITABLE for use in both hard and soft water

BIO-DEGRADABLE and non-toxic

WILL NOT STAIN engine castings or radiators surrounds

OVERDOSING will not cause corrosion or deposition

CAN LOWER running temperatures by 8-10° C cooler than glycol treatments

PERFORMANCE LEVEL:

AS 2108-2004 Type B

CLASSIC CAR COOLANT

1L	VC1001
----	--------

RADIATOR FLUSH



WHEN IN DOUBT, FLUSH IT OUT

SUITABLE for use for all cooling systems

1 x 375mL bottle treats up to 15 Litres

FAST ACTING, cleans in 7 minutes

REMOVES internal rust & corrosion

IMPROVES cooling system circulation

COMPATIBLE with all types of coolants

RADIATOR FLUSH

375mL	ADRF375
-------	---------

20L	ADRF020
-----	---------



RADIATOR STOP LEAK

SUITABLE for use in all cooling systems

1 x 375mL bottle treats up to 12 Litres

COMPATIBLE with all metal types including aluminium

COMPATIBLE with Anti-Freeze/ Anti-Boil solutions

STOPS coolant leaks in system

SAFE for rubber hoses and seals

RADIATOR FLUSH

375mL	ADRF375
-------	---------

20L	ADRF020
-----	---------

DEMINERALISED WATER

MAXIMISES Life of engine coolants and lead acid batteries

CAN BE MIXED with all types of engine coolants

SUITABLE as an engine coolant top up

MULTIPLE applications in varied industries

OEM quality product

DEMINERALISED WATER

1L	DEWATER001
----	------------

2L	DEWATER002
----	------------

5L	DEWATER005
----	------------

20L	DEWATER020
-----	------------



COOLANT TEST STRIPS

QUICK and effective coolant tests

ALL IN ONE product

PREVENT costly repairs from poor coolant

WORKS on all types of coolants

COOLANT TEST STRIPS

70 STRIPS	TSTRIPS
-----------	---------





A Better Class of Oil

110-116 Greens Rd,
Dandenong South, Victoria 3175
Australia

Ph: 1300 736 748

www.penriteoil.com.au



**100%
AUSTRALIAN
OWNED**