Page 1 of 12 Product: DOT 3 Brake Fluid Issue Date: 29th July 2016

Revision: 0.1

SAFETY DATA SHEET

SECTION 1 – IDENTIFICATION: PRODUCT IDENTIFIER/CHEMICAL IDENTITY

1.1 PRODUCT IDENTIFIER: DOT 3 Brake Fluid

1.2 PRODUCT CODE: DOT3

1.3 RELEVANT IDENTIFIED USES OF THE MIXTURE AND USES ADVISED AGAINST:

RELEVANT IDENTIFIED USES: Brake fluid. RESTRICTIONS ON USE: None known.

1.4 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:

SUPPLIER NAME: PENRITE OIL Company Pty Ltd (ABN: 25005 001 525),
ADDRESS (Australia): 110-116 Greens Road, Dandenong South VIC, Australia, 3175
TELEPHONE NUMBER (Australia): 1300 736 748; +61 3 9801 0877 (Int); Fax: 1800 736 748

ADDRESS (New Zealand): 75 Lady Ruby Drive, East Tamaki, Auckland, New Zealand, 2013

TELEPHONE NUMBER (New Zealand):0800 533 698; Fax: 0800 533 698 **E-MAIL:** tech@penriteoil.com (Aust and NZ)

1.5 EMERGENCY TEL. NUMBER: Australia: 1300 736 748; New Zealand: 0800 533 698

(Poisons Information Centre (Aust 131 126; NZ 0800 764 766)

1.6 HSNO DETAILS:

HSNO APPROVAL NUMBER: HSR002606.

HSNO GROUP TITLE: Lubricants, Lubricant Additives, Coolants and Anti-Freeze Agents

(Subsidiary Hazard) Group Standard, 2006.

SECTION 2 – HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE HAZARDOUS CHEMICAL:

GHS CLASSIFICATION HAZARD

CLASS & CATEGORY: Under the Model Work Health and Safety Regulations the product would be

rated as hazardous:

Serious Eye Damage/Irritation - Category 2A

Specific Target Organ Toxicity (Repeated Exposure) - Category 2

2.2 LABEL ELEMENTS INCLUDING PRECAUTIONARY STATEMENTS:

SIGNAL WORD: Warning

PICTOGRAMS:



HAZARD STATEMENTS: H319 - Causes serious eye irritation.

H373 - May cause damage to kidneys through prolonged or repeated exposure

if swallowed.

PRECAUTIONARY STATEMENTS:

PREVENTION: P102 - Keep out of reach of children.

P103 - Read label before use.

P260 - Do not breathe mist/vapour/spray. P264 - Wash hands thoroughly after handling. P280 - Wear eye protection/face protection.

RESPONSE: P101 - If medical advice is needed, have product container or label at hand.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 - Get medical advice/attention if you feel unwell.

P337+P313 - If eye irritation persists: Get medical advice/attention.

STORAGE: Not Applicable.

DISPOSAL: P501 - Dispose of contents/container in accordance with local regulations.

Page 2 of 12 Product: DOT 3 Brake Fluid

SAFETY DATA SHEET

SECTION 2 – HAZARD(S) IDENTIFICATION Continued

2.3 OTHER HAZARDS:

This is a Schedule 5 Poison. Excessive exposure may result in mild irritation to the skin, eye or respiratory system. Prolonged or repeated contact may cause defatting of the skin which may lead to dermatitis. People with pre-existing skin conditions, such as eczema or dermatitis, should take precautions so as not to exacerbate the condition. As for all chemical products, persons should not expose open wounds, cuts, abrasions or irritated skin to this material.

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENTS	CAS NUMBER	Concentration % W/W	GHS Classification*
Ethanol, 2-[2-(2-butoxyethoxy)ethoxy]- (Triethylene glycol monobutyl ether)			
(Butyl triglycol)	143-22-6	20% - < 30%	Eye Dam 1 - H318
Ethanol, 2,2'-oxybis- (Diethylene glycol)	111-46-6	10% - < 25%	Acut Tox 4 - H302
			STOT RE 2 - H373
Ethanol, 2-(2-methoxyethoxy)- (Diethylene glycol monomethyl ether)			
(Methyl diglycol)	111-77-3	< 2.5%	Toxic Repro 2 - H361d
Ethanol, 2-(2-butoxyethoxy)- (Diethylene glycol monobutyl ether)			
(Butyl diglycol)	112-34-5	< 2.5%	Eye Irrit 2A - H319
Denatonium Benzoate	3734-33-6	10mg/kg	Not Applic
Other non-hazardous ingredients	-	To 100%	Not Applic

Not Applic = Not Applicable *Please see Section 15 of this SDS for full text description of the Label Elements

SECTION 4 – FIRST AID MEASURES

4.1 DESCRIPTION OF NECESSARY FIRST AID MEASURES:

INGESTION:

For advice, contact a Poisons Information Centre (Phone Australia 131 126; New Zealand 0800 764 766) or a doctor. Rinse mouth out and give a glass of water. Never give fluid to a person exhibiting decreased awareness. Do NOT induce vomiting except under medical supervision. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. As the product contains glycol ethers if ingested seek medical assistance.

EYE:

If in eyes, hold eyelids apart and flush the eye immediately with large amounts of running water. Continue flushing for at least 15 minutes or until advised to stop by a doctor. Check for contact lenses. If there are contact lenses, these should be removed after several minutes of rinsing by the exposed person or medical personnel if it can be done easily. As the product is an eye irritant, after flushing, if irritation develops or persists, seek medical assistance.

SKIN CONTACT:

If skin or hair contact has occurred remove any contaminated clothing and footwear, wash skin or hair thoroughly with soap and water. If irritation develops or persists, consult a Doctor.

INHALATION:

If affected, remove the patient from further exposure into fresh air, if safe to do so. If providing assistance, avoid exposure to yourself - only enter contaminated environments with adequate respiratory equipment. Once removed, lay patient down in a well-ventilated area and reassure them whilst waiting for medical assistance. If not breathing, provide artificial respiration and seek immediate medical assistance. If unconscious, place in a recovery position and seek immediate medical assistance. If irritation develops or persists, consult a Doctor.

Page 3 of 12 Product: DOT 3 Brake Fluid

SAFETY DATA SHEET

SECTION 4 – FIRST AID MEASURES Continued

PROTECTION FOR FIRST

AIDERS:

No personnel shall place themselves in a situation that is potentially hazardous to themselves. Assess the scenario for PPE requirements before entering. Assess environment for vapours before entering. Do not enter contaminated area without a respirator. As the product contains Glycols, if the person has ingested the product, do not use direct mouth-to-mouth resuscitation techniques. Always ensure that you are wearing gloves when dealing with first aid procedures involving chemicals and/or blood.

FIRST AID FACILITIES: Eye wash fountain and safety showers are recommended in the area where the

product is used.

4.2 MOST IMPORTANT SYMPTOMS & EFFECTS, BOTH ACUTE & DELAYED, CAUSED BY EXPOSURE:

ACUTE:

Ingestion or inhalation of vapours may lead to irritation of the mouth and respiratory tract. Symptoms may include a burning sensation in the nose and throat, coughing or difficulty breathing. Ingestion may lead to nausea and diarrhoea. Eye contact may lead to localised burning, redness and tearing.

Skin contact may lead to redness or itching.

CHRONIC: Skin contact may aggravate/exacerbate existing skin conditions, such as

dermatitis. Prolonged or repeated contact may result in damage in kidneys.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NECESSARY:

ADVICE TO DOCTOR: Treat symptomatically.

SECTION 5 – FIRE FIGHTING MEASURES

5.1 EXTINGUISHING MEDIA:

SUITABLE MEDIA: Use extinguishing media appropriate for surrounding fire. Use carbon dioxide,

alcohol resistant foam, dry chemical or water spray. Spray down fumes

resulting from fire.

UNSUITABLE MEDIA: Avoid using full water jet directed at residual material that may be burning.

Water may cause splattering on hot residue.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

COMBUSTION HAZARDS: Combustion may produce oxides of carbon, as well as smoke and irritating

vapours.

5.3 ADVICE FOR FIREFIGHTERS:

FIRE: The product is not flammable under conditions of use. This is a glycol-based

liquid that will burn if preheated - Typical Flash Point >93°C. Keep storage

tanks, pipelines, fire exposed surfaces, etc. cool with water spray.

HAZCHEM CODE: Not applicable.

EXPLOSION: No information to indicate that the product is an explosion hazard. Extinguish all

sources of flame or spark. Closed containers may explode when exposed to

extreme heat.

PROTECTIVE

EQUIPMENT: In the event of a fire, wear full protective clothing and self-contained breathing

equipment with full-face piece operated in the pressure demand or other

positive pressure mode.

Page 4 of 12 Product: DOT 3 Brake Fluid

SAFETY DATA SHEET

SECTION 6 – ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

PERSONAL PROTECTION:

For small spills, wear Natural rubber, Butyl rubber, Nitrile or PVC gloves, glasses/goggles, boots and full-length clothing. During routine operation a respirator is not required. However, if mists or vapours are generated, an approved organic vapour/particulate respirator is required. For large spills, or in confined spaces, a full chemically resistant body-suit is recommended and the atmosphere must be evaluated for oxygen deficiency. If in doubt about potential oxygen deficiency wear self-contained breathing apparatus.

CONTROL MEASURES:

Ventilate area and extinguish and/or remove all sources of ignition. Stop the leak if safe to do so. CAUTION: The spilled product will be slippery. Avoid contact with the spilled material.

EMERGENCY PROCEDURES: In the event of a spill or accidental release, notify the relevant authorities in accordance with all applicable regulations.

6.2 ENVIRONMENTAL PRECAUTIONS:

SPILL ADVICE:

Do not allow product to enter drains, surface water, sewers or watercourses - inform local authorities if this occurs.

6.3 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:

CONTAINMENT:

Contain the spill and absorb with a proprietary absorbent material, sand or earth. For large spills prepare a bund/barrier/dyke ahead of the spill to confine the spill and allow later recovery. If there is the possibility of spills to enter drains, surface water, sewers or watercourses ensure bunding, or that drains are covered, to minimise the potential for this to occur.

CLEANING PROCEDURES:

Having contained the spill, as mentioned above, collect all material quickly and place used absorbent in suitable containers. Follow local regulations for the disposal of waste. For large spills that have been bunded, the material can be pumped into vessels and returned for reprocessing or destruction. Personnel must wear gloves, goggles or glasses, boots and full-length clothing during cleaning procedures. Wash contaminated area and objects with detergent and water after spill has been cleared. Rinse the cleaned area with water. Do not allow wash water or rinsings to enter drains, surface water, sewers or water courses.

SECTION 7 - HANDLING AND STORAGE, INCLUDING HOW THE CHEMICAL MAY BE SAFELY USED

7.1 PRECAUTIONS FOR SAFE HANDLING:

SAFE HANDLING:

Avoid contact with the product by using appropriate protective equipment such as gloves, glasses or goggles and full-length clothing. Prevent small spills and leakage to avoid slip hazards. Properly dispose of any contaminated rags or cleaning materials in order to prevent fire hazards. Eating, drinking and smoking should be prohibited in the area where this material is handled, stored and processed. Workers should follow good personal hygiene practices, such as washing hands before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Keep containers tightly closed when not in use. Prevent product from entering waterways, drains or sewers.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATABILITIES:

SAFE STORAGE:

Store in a dry, well ventilated area away from direct sunlight, ignition sources, oxidising agents, foodstuffs, animal feed and clothing. Keep containers closed when not in use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store only in original containers. Keep out of reach of children.

INCOMPATIBILITIES:

Mineral oils and strong oxidizing substances including strong acids, as well as isocyanates.

Page 5 of 12 Product: DOT 3 Brake Fluid

SAFETY DATA SHEET

SECTION 8 – EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1 EXPOSURE CONTROL MEASURES:

EXPOSURE LIMIT VALUES: Exposure standards for the product have not been established. However, in the operation of certain equipment or at elevated temperatures, if glycol vapours or mists are generated, the following Exposure Standard must be observed:

Ethanol, 2,2'-oxybis- (Diethylene glycol)

23 ppm 100 mg/m³ TWA:

Ethanol, 2-(2-methoxyethoxy)- (Methyl Diglycol) (HSE - EH40/2005)

TWA: 10 ppm 50 mg/m³

Ethanol, 2-(2-butoxyethoxy)- (Butyl Diglycol) (HSE - EH40/2005) TWA: 10 ppm 67.5 mg/m³ STEL: 15 ppm 101.2 mg/m³

8.2 BIOLOGICAL

MONITORING: No data available.

8.3 CONTROL BANDING: No data available.

8.4 ENGINEERING CONTROLS:

ENGINEERING CONTROLS:

Special ventilation is not normally required when using this product in normal use scenarios. However, in the operation of certain equipment, at elevated temperatures, or in confined spaces mists or vapour may be generated and local exhaust ventilation should be provided to maintain airborne concentration levels below the nominated exposure standard and at an acceptable level that does not cause irritation.

8.5 INDIVIDUAL PROTECTION MEASURES:

EYE & FACE PROTECTION:

Wear safety glasses/goggles to avoid eye contact when handling. If there is a risk of splashing during use, a full face shield is recommended. Use eye protection in accordance with AS 1336 and AS 1337.

SKIN (HAND) PROTECTION: If there is the chance of contact with the material wear gloves to provide hand protection. Natural rubber. Butvl rubber. Nitrile or PVC gloves are recommended.

SKIN (CLOTHING)

PROTECTION:

During normal operating procedures, long sleeved clothing is recommended to avoid skin contact. Soiled clothing should be washed with detergent prior to re-

use.

RESPIRATORY PROTECTION: During routine operation a respirator is not required. However, if mists or

vapours are generated, an approved half face organic vapour/particulate respirator is required. Use respirators in accordance with AS 1715 and AS 1716.

THERMAL PROTECTION: Not applicable.

Page 6 of 12 Product: DOT 3 Brake Fluid

SAFETY DATA SHEET

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

9.1 PHYSICAL AND CHEMICAL PROPERTIES:
APPEARANCE: Amber liquid.
ODOUR: Minor odour.
ODOUR THRESHOLD: No data available.
pH: Typically 7.0 to 11.5.

MELTING/FREEZING POINT: < -50°C.

INITIAL BOILING POINT: Typically > 205°C. No data available. **BOILING RANGE (°C):** Typically > 93°C FLASHPOINT (°C): **EVAPORATION RATE:** No data available. FLAMMABILITY LIMITS (%): No data available. VAPOUR PRESSURE: < 2 millibars. VAPOUR DENSITY: No data available DENSITY (kg/L @ 20°C): Typically 1.01 - 1.06. SOLUBILITY IN WATER(q/L): Completely miscible.

PARTITION COEFFICIENT: < 2.0 (all main components).

AUTO-IGNITION TEMP (°C): > 300°C.

DECOMPOSITION TEMP (°C): > 300°C.

VISCOSITY (cSt @ 100°C): Typically 2.2.

VISCOSITY (cSt @ -40°C): Typically 1270.

SECTION 10 – STABILITY AND REACTIVITY

10.1 REACTIVITY: The product does not pose any further reactivity hazards other than those listed

in the following sub-sections.

10.2 CHEMICAL STABILITY: Stable under recommended storage and handling conditions (see section 7).

The product will decompose at temperatures > 300°C.

10.3 POSSIBILITY OF

HAZARDOUS REACTIONS: Keep away from mineral oils, isocyanates and strong oxidising agents.

Hazardous polymerisation does not occur. Glycol ethers can form peroxides on storage. They can also react with light metals with the evolution of hydrogen.

10.4 CONDITIONS TO AVOID: Observe the usual precautionary measures for handling chemicals. Do not heat

the container, leave it in direct sunlight or leave the container open when not in use. As there is the potential for peroxide formation with glycol ethers, never

distil this product to dryness without testing for peroxide formation.

10.5 INCOMPATIBLE

MATERIALS: Strong oxidising agents including concentrated acids, isocyanates and mineral

oils. As a general precaution never mix brake fluids with other materials.

10.6 HAZARDOUS DECOMPOSITION

PRODUCTS: Hazardous decomposition products are not expected to form during normal

storage requirements. Extended storage may lead to the formation of peroxides in Glycol ethers as mentioned previously. See Section 5.2 for Hazardous

Combustion products.

SECTION 11 – TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:

The product is a mixture and the manufacturer has nominated the following for the product:

Oral - LD₅₀ (Rat): >5000 mg/kg Dermal - LD₅₀ (Rabbit): >3000 mg/kg

Ethanol, 2-[2-(2-butoxyethoxy)ethoxy]- (Butyl Triglycol)

Oral - LD₅₀ (Rat): >2000 mg/kg bw Dermal - LD₅₀ (Rat): >2000 mg/kg bw

Page 7 of 12 Product: DOT 3 Brake Fluid

SAFETY DATA SHEET

SECTION 11 – TOXICOLOGICAL INFORMATION Continued

Ethanol, 2,2'-oxybis- (Diethylene glycol)

Oral - LD₅₀ (Rat): 15600 mg/kg bw Dermal - LD₅₀ (Rabbit): 12500 mg/kg bw

Inhalation - LC₅₀ (Rat, aerosol, 4 hours): >4600 mg/m³

Inhalation - LC₅₀ (Mice, 2 hours): >130 mg/m³

Ethanol, 2-(2-butoxyethoxy)- (Butyl Diglycol)

Oral - LD₅₀ (Rat): >2000 mg/kg bw Dermal - LD₅₀ (Rat): >2000 mg/kg bw

Ethanol, 2-(2-methoxyethoxy)- (Methyl Diglycol)

Oral - LD₅₀ (Rat): >5500 mg/kg bw Dermal - LD₅₀ (Rabbit): >6540 mg/kg bw

Inhalation - LC₅₀ (Rat, vapour, 1 hour): >200 mg/L

Ethanol, 2,2'-oxybis- (Diethylene glycol)

The NICNAS IMAP Report for Diethylene glycol nominates that incidents have been reported following human exposure. Typical features of acute toxicity include neurological impairment, metabolic acidosis and acute renal failure. Early mortality and morbidity are high, with most deaths occurring within the first two weeks following Diethylene glycol exposure. Humans appear to be 10 times more susceptible to acute oral toxic effects of Diethylene glycol compared with experimental animals. The median lethal dose for humans is reported as 1,490 mg/kg bw in the IMAP Report.

Ethanol, 2-[2-(2-butoxyethoxy)ethoxy]- (Butyl Triglycol)

The NICNAS IMAP Report for Butyl triglycol nominates that observed sublethal dose effects include lethargy, ataxia, blood in the urogenital area and piloerection.

Ethanol, 2-(2-butoxyethoxy)- (Butyl Diglycol)

The NICNAS IMAP Report for Butyl diglycol nominates that observed sublethal dose effects include laboured breathing, rapid respiration, anorexia, slight to moderate weakness, tremors and prostration. According to the NICNAS IMAP Report, it has been estimated that a single lethal dose of Butyl diglycol for humans is approximately 1mL/kg. Cyanosis, tachypnoea and slight uraemia have also been reported in humans.

11.2 SWALLOWED:

The Ethanol, 2-(2-methoxyethoxy)- and the Ethanol, 2,2'-oxybis- with 10mg/kg of denatonium benzoate mean that this is a Schedule 5 Poison. The manufacturer states that if any significant amount of this product is ingested, there is a risk of renal damage which in extreme cases could lead to kidney failure, coma or death. Other symptoms of overexposure include Central Nervous System effects, abdominal discomfort, metabolic acidosis, headache and nausea. During normal usage ingestion should not be a means of exposure.

11.3 SKIN CORROSION/ IRRITATION:

This product is not expected to exhibit Dermal Corrosivity/Irritation according to OECD Test 404, based on the available data and the known hazards of the components. May be mildly irritating to the skin. The manufacturer states that extended contact with damaged skin could result in the absorption of harmful amounts. Prolonged or repeated contact may cause defatting of the skin which may lead to dermatitis. Correct handling procedures incorporating appropriate protective clothing and gloves should minimise the risk of skin irritation. People with pre-existing skin conditions, such as dermatitis, should take extreme care so as not to exacerbate the condition.

11.4 SERIOUS EYE DAMAGE/ IRRITATION:

The product is rated as Causes serious eye irritation. Symptoms may include localised burning, redness and tearing. Correct handling procedures incorporating appropriate eye protection should minimise the risk of eye irritation.

Page 8 of 12 Product: DOT 3 Brake Fluid

SAFETY DATA SHEET

SECTION 11 - TOXICOLOGICAL INFORMATION Continued

11.5 RESPIRATORY OR

SKIN SENSITISATION: This product is not expected to be a skin sensitiser according to OECD Test

406, based on the available data and the known hazards of the components. This product is not expected to be a respiratory tract sensitiser, based on the

available data and the known hazards of the components.

11.6 GERM CELL **MUTAGENICITY:**

This product is not expected to be mutagenic according to tests such as OECD

Tests 471, 475, 476, 478 and 479, based on the available data and the known

hazards of the components.

11.7 CARCINOGENICITY: This product is not expected to be a carcinogen according to OECD Test 451,

based on the available data and the known hazards of the components.

11.8 REPRODUCTIVE TOXICITY:

This product is not expected to be a reproductive hazard according to tests such as OECD Tests 414 and 421, based on the available data and the known hazards of the components. The product contains Methyl Diglycol that is rated

as Suspected of damaging the unborn child, however this is present at amounts below the Concentration cut-off levels where it would be considered to be a

Reproductive Toxin.

11.9 SPECIFIC TARGET ORGAN TOXICITY (STOT) -

SINGLE EXPOSURE: This product is not expected to cause organ damage from a single exposure,

based on the available data and the known hazards of the components. This product is not expected to pose an irritation hazard at ambient temperature or under normal handling conditions. Not classified as a respiratory irritant, however inhalation of vapours or mist (generated at elevated temperatures or by mechanical action) may cause irritation to the nose, throat and respiratory

system.

11.10 SPECIFIC TARGET ORGAN TOXICITY (STOT) -

REPEATED EXPOSURE: The Diethylene glycol component means that this product is rated as May cause

damage to kidneys through prolonged or repeated exposure if swallowed.

11.11 ASPIRATION HAZARD: This product is not expected to be an aspiration hazard, based on the available

data and the known hazards of the components.

11.12 OTHER INFORMATION: No additional information is available.

SECTION 12 – ECOLOGICAL INFORMATION

12.1 ECOTOXICITY: The product is of low acute ecotoxicity. The manufacturer nominated the

following for the product:

LC₅₀ (Oncorhynchus Mykiss, 96hr): > 100 mg/L.

12.2 PERSISTENCE & **DEGRADABILITY:**

Based on the available data and the known hazards of the components and similar products the product is expected to be inherently biodegradable. Major

constituents are expected to be readily biodegradable. According to Test OECD

302B (Zahn Wellans/EMPA) the result is 100% elimination at 21 days.

12.3 BIOACCUMULATIVE POTENTIAL:

Based on the available data and the known hazards of the components the

manufacturer states that the product is not expected to bioaccumulate. Log Pow

for all main components is < 2.0.

12.4 MOBILITY IN SOIL: The product is soluble in water and will partition into the aqueous phase. The

product will be mobile in soil until degraded.

12.5 OTHER ADVERSE

EFFECTS: There is no data available for the product as a whole.

Page 9 of 12 Product: DOT 3 Brake Fluid

SAFETY DATA SHEET

SECTION 13 - DISPOSAL CONSIDERATIONS

13.1 DISPOSAL METHODS:

PRODUCT:

The product should not be released to the environment, so any unused material should be recycled wherever possible or be disposed of as hazardous waste at an appropriate collection depot. The product is also suitable for incineration at very high temperatures to prevent formation of undesirable combustion products. Spilled product that cannot be recovered should be absorbed and then shovelled into a suitable waste container, such as a plastic drum and then be treated as a solid waste. Follow Government regulations for disposal of such waste. Do not mix new or used brake fluid with solvents, lubricating oils or coolants when disposing. All unused, waste or spilled product must be taken for recycling or disposal by suitably licensed contractors in accordance with Government regulations.

CONTAINERS:

Empty containers may contain residual product. They should be completely drained and then stored until reconditioned or disposed of. Empty drums should be taken for recycling or disposal through suitably licensed contractors in accordance with Government regulations. Where the containers are of metal construction they should not be pressurised, cut by a grinder, welded, brazed, soldered, drilled or exposed to heat, flames or other sources of ignition. Closed metal containers when exposed to such conditions/treatment may explode causing serious injury or death.

SECTION 14 – TRANSPORT INFORMATION

This product is not regulated for land, sea or air transportation. (HS Code: 3819.00.00)

14.1 LAND (ADG Code):

UN NUMBER: Not applicable

UN PROPER SHIPPING

NAME: Not applicable

TRANSPORT HAZARD

CLASS(ES): Not applicable PACKAGING GROUP: Not applicable

ENVIRONMENTAL

HAZARDS: Not applicable

SPECIAL PRECAUTIONS

FOR USER: Not applicable HAZCHEM CODE: Not applicable

14.2 SEA (IMDG):

UN NUMBER: Not applicable

UN PROPER SHIPPING

NAME: Not applicable

TRANSPORT HAZARD

CLASS(ES): Not applicable PACKAGING GROUP: Not applicable

ENVIRONMENTAL

HAZARDS: Not applicable

SPECIAL PRECAUTIONS

FOR USER: Not applicable

Page 10 of 12 Product: DOT 3 Brake Fluid

SAFETY DATA SHEET

SECTION 14 – TRANSPORT INFORMATION Continued

14.3 AIR (IATA):

UN NUMBER: Not applicable

UN PROPER SHIPPING

NAME: Not applicable

TRANSPORT HAZARD

CLASS(ES): Not applicable PACKAGING GROUP: Not applicable

ENVIRONMENTAL

HAZARDS: Not applicable

SPECIAL PRECAUTIONS

FOR USER: Not applicable

SECTION 15 – REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS:

APPLICABLE REGULATIONS:

SUSMP: Schedule 5 Poison (S5).

AICS:
MONTREAL PROTOCOL:
STOCKHOLM CONVENTION:
ROTTERDAM CONVENTION:
BASEL CONVENTION:
All ingredients are on the AICS List.
Not applicable to this product.
Not applicable to this product.
Not applicable to this product.

INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM

SHIPS (MARPOL): Not determined.

OTHER REGULATORY INFORMATION:

GHS CLASSIFICATION HAZARD CLASS & CATEGORY

AND HAZARD STATEMENT: Acute Toxicity - Oral Category 4; H302 - Harmful if swallowed.

Serious Eye Damage/Irritation Category 1; H318 - Causes serious eye damage. Serious Eye Damage/Irritation Category 2A; H319 - Causes serious eye

irritation.

Toxic to Reproduction Category 2: H361d - Suspected of damaging the unborn

child.

Specific Target Organ Toxicity (Repeated Exposure) Category 2; H373 - May

cause damage to organs through prolonged or repeated exposure.

HSNO APPROVAL NUMBER: HSR002606.

HSNO GROUP TITLE: Lubricants, Lubricant Additives, Coolants and Anti-Freeze Agents (Subsidiary

Hazard) Group Standard 2006.

Page 11 of 12 Product: DOT 3 Brake Fluid

SAFETY DATA SHEET

SECTION 16 – ANY OTHER RELEVANT INFORMATION

SDS INFORMATION:

Date of SDS Preparation: 29th July 2016 Revision: 0.1

REVISION CHANGES: Changes to supplier information and addition of HSNO number in Section 1.

ACRONYMS:

SUSMP Standard for the Uniform Scheduling of Medicines and Poisons

CAS Number Chemical Abstracts Service Registry Number

EINECS European Inventory of Existing Commercial Chemical Substances

UN Number United Nations Number

OSHA Occupational Safety and Health Administration

ACGIH American Conference of Governmental Industrial Hygienists
HSE-WEL Health and Safety Executive - Workplace Exposure Limit

IMDG International Maritime Dangerous Goods
IATA International Air Transport Association

IUCLID International Uniform Chemical Information Database RTECS Registry of Toxic Effects of Chemical Substances

%W/W Percent weight for weight

OECD Organisation for Economic Co-Operation and Development

ADG Code Australian Code for the Transport of Dangerous Goods by Road and Rail

HAZCHEM Code Emergency action code of numbers and letters which gives information to emergency services

NOHSC National Occupational Health and Safety Commission

NICNAS National Industrial Chemicals Notification & Assessment Scheme

IMAP Inventory Multi-Tiered Assessment and Prioritisation

AICS Australian Inventory of Chemical Substances

TWA Time-Weighted Average STEL Short term Exposure Limit

HSNO Hazardous Substances and New Organisms Act 1996

GHS Globally Harmonised System of Classification and Labelling of Chemicals

WHS Work Health and Safety
PPE Personal Protective Equipment.

EH40 EH40/2005 Workplace Exposure Limits

LITERATURE REFERENCES AND SOURCES OF DATA:

OECD Guidelines for Testing of Chemicals

Annex I: OECD Test Guidelines for Studies Included in SIDS

Manual for the Assessment of Chemicals Chapter 2 Data Gathering

International Toxicity Testing Guidelines

Hazardous Substance Information System - Guidance Material for Hazard Classifications

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.

Model Work Health and Safety Regulations.

Model Work Health and Safety Regulations - Transitional Principles

Workplace Exposure Standards for Airborne Contaminants

Australian Dangerous Goods Code 7th Edition

Approved Criteria for Classifying Hazardous Substances [NOHSC:1008 (2004)] Guidance on the Classification of Hazardous Chemicals under the WHS Regulations

Assigning a Hazardous Substance to a Group Standard User Guide to the HSNO Thresholds and Classifications

Summary User Guide to the HSNO Thresholds and Classifications of Hazardous Substances

Correlation between GHS and New Zealand HSNO Hazard Classes and Categories

HSNO Control Regulations

Record of Group Standard Assignment

Labelling of Hazardous Substances Hazard and Precautionary Information

Thresholds and Classifications Under the Hazardous Substances and New Organisms Act 1996

Workplace Exposure Standards and Biological Exposure Indices

NICNAS IMAP Human Health Tier II Assessment for Ethanol, 2,2'-oxybis- CAS Number: 111-46-6

NICNAS IMAP Human Health Tier II Assessment for Ethanol, 2-(2-methoxyethoxy)- CAS Number: 111-77-3 NICNAS IMAP Human Health Tier II Assessment for Ethanol, 2-(2-butoxyethoxy)- CAS Number: 112-34-5 NICNAS IMAP Human Health Tier II Assessment for Ethanol, 2-[2-(2-butoxyethoxy)ethoxy]- CAS Number: 143-

22-6

Page 12 of 12 Product: DOT 3 Brake Fluid

SAFETY DATA SHEET

SECTION 16 – ANY OTHER RELEVANT INFORMATION Continued

All information contained in this Safety Data Sheet and the health, safety and environmental information are considered to be accurate to the best of our knowledge as of the issue date specified above. However, no warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this data sheet.

Health and safety precautions and environmental advice noted in this data sheet may not be accurate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The Company accepts no responsibility for any injury, loss or damage, resulting from abnormal use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material.