

# Safety Data Sheet

## Hazardous, Dangerous Goods

### 1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: Chain Cleaner (Aerosol)

#### Synonyms

Chain Cleaner (Aerosol)  
HS Code: 3402.20.90.90

#### Product Code

MCACC0004  
-

Recommended use: MC chain cleaner.

**Supplier:** Penrite Oil Company Pty Ltd  
**ABN:** 25 005 001 525  
**Street Address:** Australia:  
110-116 Greens Road  
Dandenong South VIC 3175

New Zealand:  
75 Lady Ruby Drive  
East Tamaki Auckland 2013

**Telephone:** Australia: 1300 736 748; New Zealand: 0800 533 698  
**Facsimile:** Australia: 1800 736 748; New Zealand: 0800 533 698

**Emergency Telephone number:** Australia: 1300 736 748; New Zealand: 0800 533 698

### 2. HAZARDS IDENTIFICATION

#### Classification

This material is hazardous according to criteria of Safe Work Australia.

#### Hazard Classifications

Aerosols - Category 1  
Aspiration Hazard - Category 1  
Skin Corrosion/Irritation - Category 2  
Specific Target Organ Toxicity (Single Exposure) - Category 3 Narcotic Effects  
Chronic Hazard to the Aquatic Environment - Category 2

#### Label Elements

#### Hazard Pictogram(s)



#### Signal Word

Danger

#### Hazard Statements

H222 Extremely flammable aerosol.  
H229 Pressurized container: may burst if heated.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

# Safety Data Sheet

## Prevention Precautionary Statements

P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P211	Do not spray on an open flame or other ignition sources.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing fume, gas, mist, vapours or spray.
P264	Wash hands, face and all exposed skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing including eye/face protection and suitable respirator.

## Response Precautionary Statements

P101	If medical advice is needed, have product container or label at hand.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P331	Do NOT induce vomiting.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse
P391	Collect spillage.

## Storage Precautionary Statements

P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C.

## Disposal Precautionary Statement

P501	Dispose of contents/container in accordance with local, regional, national and international regulations.
------	---

**Poison Schedule:** Not Applicable

**Child-resistant fastening:** Not Applicable

**Tactile warning:** Not Applicable

## DANGEROUS GOOD CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

**Dangerous Goods Class:** 2.1

## 3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
Kerosine, petroleum, hydrodesulfurized	64742-81-0	>60 %
Butane	106-97-8	10 - 30 %
Propane	74-98-6	10 - 30 %
Ingredients determined to be Non-Hazardous	-	Balance
		100%

## 4. FIRST AID MEASURES

**Product Name:** Chain Cleaner (Aerosol)

**Reference No:** PEN0010501

**Issued:** 2021-07-09

**Version:** 3.0

**Page 2 of 8**

# Safety Data Sheet

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

**Inhalation:** Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

**Skin Contact:** If skin or hair contact occurs, immediately remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a Doctor; or for 15 minutes and transport to Doctor or Hospital. For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

**Eye contact:** If in eyes wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

**Ingestion:** Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Immediately call Poisons Centre or Doctor.

**PPE for First Aiders:** Wear safety shoes, overalls, gloves, safety glasses, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

**Notes to physician:** Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

**Hazchem Code:** None allocated

**Suitable extinguishing media:** If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).

**Specific hazards:** Extremely flammable aerosol. May form flammable vapour mixtures with air. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Electrical requirements for work area should be assessed according to AS3000. Vapour may travel a considerable distance to source of ignition and flash back. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke.

**Fire fighting further advice:** Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire. Keep containers cool with water spray. On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

## 6. ACCIDENTAL RELEASE MEASURES

### SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of gas. If safe to do so, isolate the leak. Increase ventilation to assist with dispersion.

### LARGE SPILLS

If safe to do so, shut off all possible sources of ignition. Clear area of all unprotected personnel. Use a spark-free shovel. If safe to do so, isolate the leak. Increase ventilation to assist with dispersion. If contamination of crops,

# Safety Data Sheet

sewers or waterways has occurred advise local emergency services.

**Dangerous Goods - Initial Emergency Response Guide No: 49**

## 7. HANDLING AND STORAGE

**Handling:** Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols.

**Storage:** Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Store locked up. Do not expose to temperatures exceeding 50°C. Keep containers closed when not in use - check regularly for leaks.

This material is classified as a Division 2.1 Flammable Gas as per the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and/or the "New Zealand NZS5433: Transport of Dangerous Goods on Land" and must be stored in accordance with the relevant regulations.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**National occupational exposure limits:**

	TWA		STEL		NOTICES
	ppm	mg/m3	ppm	mg/m3	
Butane	800	1900	-	-	-
Oil mist, refined mineral	-	5	-	-	-
Propane	-	-	-	-	Asphyxiant

As published by Safe Work Australia.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

Asphyxiant - gases which can lead to reduction of oxygen concentration by displacement or dilution. The minimum oxygen content in air should be 18% by volume under normal atmospheric pressure.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

**Biological Limit Values:** As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

**Engineering Measures:** Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Use with local exhaust ventilation or while wearing appropriate respirator. Vapour heavier than air - prevent concentration in hollows or sumps. Do NOT enter confined spaces where vapour may have collected. An asphyxiant gas which can lead to the reduction of oxygen concentration by displacement or dilution. The minimum oxygen content in air should be 18% by volume under normal atmospheric pressure.

**Personal Protection Equipment:** SAFETY SHOES, OVERALLS, GLOVES, SAFETY GLASSES,

# Safety Data Sheet

RESPIRATOR.

Personal protective equipment (PPE) must be suitable for the nature of the work and any hazard associated with the work as identified by the risk assessment conducted.

Wear safety shoes, overalls, gloves, safety glasses, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

**Hygiene measures:** Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Form:</b>	Aerosol
<b>Colour:</b>	Clear
<b>Odour:</b>	Solvent-like
<b>Solubility:</b>	Emulsifies in water
<b>Specific Gravity:</b>	0.58
<b>Relative Vapour Density (air=1):</b>	>1
<b>Vapour Pressure (20 °C):</b>	N Av
<b>Flash Point (°C):</b>	-60 to -104
<b>Flammability Limits (%):</b>	1.5 - 9.6
<b>Autoignition Temperature (°C):</b>	494 - 600
<b>Melting Point/Range (°C):</b>	N Av
<b>Boiling Point/Range (°C):</b>	-42 to 0
<b>pH:</b>	N App
<b>Viscosity:</b>	N Av
<b>Total VOC (g/Litre):</b>	N Av

(Typical values only - consult specification sheet)

N Av = Not available, N App = Not applicable

## 10. STABILITY AND REACTIVITY

**Chemical stability:** This material is thermally stable when stored and used as directed.

**Conditions to avoid:** Elevated temperatures and sources of ignition.

**Incompatible materials:** Oxidising agents.

**Hazardous decomposition products:** Oxides of carbon and nitrogen, smoke and other toxic fumes.

**Hazardous reactions:** No known hazardous reactions.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

**Acute Effects**

# Safety Data Sheet

**Inhalation:** Material may be an irritant to mucous membranes and respiratory tract. Inhalation of vapour can result in headaches, dizziness and possible nausea. Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness. An asphyxiant; exposure to high concentrations can cause suffocation.

**Skin contact:** Contact with skin will result in irritation.

**Ingestion:** Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract. May cause lung damage if swallowed. Small amounts of liquid aspirated into the respiratory system during ingestion or vomiting may cause bronchopneumonia or pulmonary oedema.

**Eye contact:** May be an eye irritant.

## Acute toxicity

**Inhalation:** This material has been classified as not hazardous for acute inhalation exposure. Acute toxicity estimate (based on ingredients):  $LC_{50} > 20,000$  ppm for gases

**Skin contact:** This material has been classified as not hazardous for acute dermal exposure. Acute toxicity estimate (based on ingredients):  $LD_{50} > 2,000$  mg/Kg bw

**Ingestion:** This material has been classified as not hazardous for acute ingestion exposure. Acute toxicity estimate (based on ingredients):  $LD_{50} > 2,000$  mg/Kg bw

**Corrosion/Irritancy:** Eye: this material has been classified as not corrosive or irritating to eyes. Skin: this material has been classified as a Category 2 Hazard (reversible effects to skin).

**Sensitisation:** Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as not a skin sensitiser.

**Aspiration hazard:** This material has been classified as Aspiration Hazard - Category 1

**Specific target organ toxicity (single exposure):** This material has been classified as a Category 3 Hazard. Exposure via inhalation may result in depression of the central nervous system.

## Chronic Toxicity

**Mutagenicity:** This material has been classified as not a mutagen.

**Carcinogenicity:** This material has been classified as not a carcinogen.

**Reproductive toxicity (including via lactation):** This material has been classified as not a reproductive toxicant.

**Specific target organ toxicity (repeat exposure):** This material has been classified as not a specific hazard to target organs by repeat exposure.

## 12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

**Acute aquatic hazard:** This material has been classified as not hazardous for acute aquatic exposure. Acute toxicity estimate (based on ingredients):  $> 100$  mg/L

**Long-term aquatic hazard:** This material has been classified as a Category Chronic 2 Hazard. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): 1 - 10 mg/L, where the substance is not rapidly degradable and/or  $BCF \geq 500$  and/or  $\log K_{ow} \geq 4$ .

**Ecotoxicity:** No information available.

# Safety Data Sheet

**Persistence and degradability:** No information available.

**Bioaccumulative potential:** No information available.

**Mobility:** No information available.

## 13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

## 14. TRANSPORT INFORMATION

### ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".



**UN No:** 1950  
**Dangerous Goods Class:** 2.1  
**Packing Group:** None  
**Hazchem Code:** None  
**Emergency Response Guide No:** 49

**Proper Shipping Name:** AEROSOLS

**Segregation Dangerous Goods:** Not to be loaded with explosives (Class 1), flammable liquids (Class 3), if both are in bulk, flammable solids (Class 4.1), spontaneously combustible substances (Class 4.2), dangerous when wet substances (Class 4.3), oxidising agents (Class 5.1), organic peroxides (Class 5.2) or radioactive substances (Class 7). Exemptions may apply.

### MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. This material is classified as a Marine Pollutant (P) according to the International Maritime Dangerous Goods Code.



**UN No:** 1950  
**Dangerous Goods Class:** 2.1  
**Packing Group:** None

**Proper Shipping Name:** AEROSOLS

### AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous

# Safety Data Sheet

Goods Regulations for transport by air.



**UN No:** 1950  
**Dangerous Goods Class:** 2.1  
**Packing Group:** None

**Proper Shipping Name:** AEROSOLS, FLAMMABLE

## 15. REGULATORY INFORMATION

**This material is not subject to the following international agreements:**

Montreal Protocol (Ozone depleting substances)  
The Stockholm Convention (Persistent Organic Pollutants)  
The Rotterdam Convention (Prior Informed Consent)

**This material is subject to the following international agreements:**

Basel Convention (Hazardous Waste)

- Waste mineral oils unfit for their originally intended use

International Convention for the Prevention of Pollution from Ships (MARPOL)

- Annex I - Oil
- Annex III - Harmful Substances carried in Packaged Form

**This material/constituent(s) is covered by the following requirements:**

AICC Status: Formulations where all components AICC listed.

All components of this product are listed on or exempt from the New Zealand Inventory of Chemical (NZIoC).

**HSNO Group Standard:** HSR002515 - Aerosols (Flammable) Group Standard 2020

## 16. OTHER INFORMATION

Reason for issue: Revised. Updated to GHS 7.

This Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd on behalf of its client.

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.