

# SAFETY DATA SHEET

## SECTION 1 – IDENTIFICATION: PRODUCT IDENTIFIER/CHEMICAL IDENTITY

**1.1 PRODUCT IDENTIFIER:** Petrol Total System Cleaner

**1.2 PRODUCT CODE:** ADPTSC

**1.3 RELEVANT IDENTIFIED USES OF THE MIXTURE AND USES ADVISED AGAINST:**

**RELEVANT IDENTIFIED USES:** Multipurpose Fuel Additive for Petrol/Gasoline

**RESTRICTIONS ON USE:** None known.

**1.4 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:**

**SUPPLIER NAME:** PENRITE OIL Company Pty Ltd (ABN: 25005 001 525),  
**ADDRESS (Australia):** 110-116 Greens Road, Dandenong South VIC, Australia, 3175  
**TELEPHONE NUMBER (Australia):** 1300 736 748; +61 3 8710 6600 (Int); Fax: 1800 736 748

**ADDRESS (New Zealand):** 75 Lady Ruby Drive, East Tamaki, Auckland, New Zealand, 2013

**TELEPHONE NUMBER (New Zealand):** 0800 533 698; Fax: 0800 533 698

**E-MAIL:** [tech@penriteoil.com](mailto:tech@penriteoil.com) (Aust and NZ)

**1.5 EMERGENCY TEL. NUMBER:** Australia: 1300 736 748; New Zealand: 0800 533 698  
(Poisons Information Centre (Aust 131 126; NZ 0800 764 766))

**1.6 HSNO DETAILS:**

**HSNO APPROVAL NUMBER:** HSR002587.

**HSNO GROUP TITLE:** Fuel Additives (Combustible, Toxic [6.7]) Group Standard 2017

## SECTION 2 – HAZARD(S) IDENTIFICATION

**2.1 CLASSIFICATION OF THE HAZARDOUS CHEMICAL:**

**GHS CLASSIFICATION HAZARD**

**CLASS & CATEGORY:** Under the Model Work Health and Safety Regulations the product would be rated as Hazardous:

Flammable Liquid - Category 4  
Aspiration Hazard - Category 1  
Skin Corrosion/Irritation - Category 2  
Serious Eye Damage/Irritation - Category 2A  
Carcinogenicity - Category 1B  
Chronic Aquatic Toxicity - Category 3

**2.2 LABEL ELEMENTS INCLUDING PRECAUTIONARY STATEMENTS:**

**SIGNAL WORD:** Danger

**PICTOGRAMS:**



**HAZARD STATEMENTS:**

H227 - Combustible liquid.  
H304 - May be fatal if swallowed and enters airways.  
H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H350i - May cause cancer by inhalation.  
H412 - Harmful to aquatic life with long lasting effects.

**PRECAUTIONARY STATEMENTS:**

**PREVENTION:**

P102 - Keep out of reach of children.  
P103 - Read label before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from flames and hot surfaces - No smoking.  
P264 - Wash hands thoroughly after handling.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

# SAFETY DATA SHEET

## SECTION 2 – HAZARD(S) IDENTIFICATION Continued

**RESPONSE:** P101 - If medical advice is needed, have product container or label at hand.  
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTRE (phone Australia 131 126; New Zealand 0800 764 766) or doctor/physician.  
P302+P352 - IF ON SKIN: Wash with plenty of soap and water.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313-If exposed or concerned: Get medical advice/attention.  
P331 - Do NOT induce vomiting.  
P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: get medical advice/attention.  
P362 - Take off contaminated clothing and wash before reuse.  
P370+P378 - In case of fire: Use carbon dioxide, alcohol-resistant foam, dry chemical or water spray.

**STORAGE:** P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.

**DISPOSAL:** P501 - Dispose of contents/container in accordance with local regulations.

**2.3 OTHER HAZARDS:** This is a Schedule 5 Poison. Due to the presence of solvents there is a possibility of organ system damage. The presence of the solvent component suggests that the product may be irritating to the respiratory system and may cause drowsiness or dizziness. The product is a combustible liquid and will potentially form flammable/explosive mixtures in air. There may be static discharge issues with the product in large scale operations that could lead to a fire. People with pre-existing skin conditions, such as eczema or dermatitis, should take precautions so as not to exacerbate the condition. As for all chemical products, persons should not expose open wounds, cuts, abrasions or irritated skin to this material.

## SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENTS	CAS NUMBER	Concentration % W/W	GHS Classification*
Distillates, petroleum, hydrotreated light	64742-47-8	60% - 70%	Flamm Liq 4 - H227 Asp Haz 1 - H304
Solvent naphtha, petroleum, light aromatic	64742-95-6	10% - 20%	Flamm Liq 3 - H226 Asp Haz 1 - H304 Aquat Chron 2 - H411
Polyolefin alkyl phenol alkyl amine 1,2,4-Trimethylbenzene**	Proprietary 95-63-6	8% - 10% 5% - < 6.5%	Skin Irrit 2 - H315 Flam Liq 3 - H226 Skin Irrit 2 - H315 Eye Irrit 2A - H319 Acute Tox 4 - H332 STOT SE 3 - H335
1,3,5-Trimethylbenzene**	108-67-8	2% - < 3.5%	Chron Aq Tox 2 - H411 Flam Liq 3 - H226 STOT SE 3 - H335
N-Propylbenzene**	103-65-1	< 1.6%	Chron Aq Tox 2 - H411 Flam Liq 3 - H226 Asp Haz 1 - H304 STOT SE 3 - H335 Aquat Chron 2 - H411

# SAFETY DATA SHEET

## SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS Cont'd

INGREDIENTS	CAS NUMBER	Concentration % W/W	GHS Classification*
Benzene, dimethyl- (Xylene)**	1330-20-7	< 1.6%	Flam Liq 3 - H226 Asp Haz 1 - H304 Acute Tox 4 - H312 Skin Irrit 2 - H315 Acute Tox 4 - H332 STOT SE 3 - H335
1-Hexanol, 2-ethyl-	104-76-7	< 1.6%	Skin Corr 1 - H314 Acute Tox 4 - H332 Tox Rep 2 - H361d
Cumene (Isopropylbenzene)	98-82-8	< 1.6%	Flam Liq 3 - H226 Asp Haz 1 - H304 STOT SE 3 - H335 Carc 1B - H350i
1,2,3-Trimethylbenzene**	526-73-8	< 1.6%	Aquat Chron 2 - H411 Flam Liq 3 - H226 Skin Irrit 2 - H315 Eye Irrit 2A - H319 Chron Aq Tox 2 - H411
Complex mixture of additives	Not Applic	To 100%	Not Applic

Not Applic = Not Applicable

\* Please see Section 15 of this SDS for the full text description of the Label Elements.

\*\*These ingredients are components of the Solvent naphtha, petroleum, light aromatic and not additional ingredients in the final mixture.

## SECTION 4 – FIRST AID MEASURES

### 4.1 DESCRIPTION OF NECESSARY FIRST AID MEASURES:

**INGESTION:**

Rinse mouth out with water. If swallowed, do NOT induce vomiting. For advice, contact the Poisons Information Centre (phone Australia 131 126; New Zealand 0800 764 766) or a Doctor at once. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Within 6 hours of ingestion, if delayed symptoms, such as a fever greater than 38.3°C, shortness of breath, chest congestion or continued coughing/wheezing occurs transport immediately to a medical facility. As the product is hydrocarbon based and of low viscosity (~6.5cSt @ 40°C), if ingested seek urgent medical assistance.

**EYE:**

If in eyes, hold eyelids apart and flush the eye immediately with large amounts of running water. Continue flushing for at least 15 minutes or until advised to stop by a Doctor. Check for contact lenses. If there are contact lenses, these should be removed after several minutes of rinsing by the exposed person or medical personnel if it can be done easily. As the product is rated as Causes serious eye irritation, after flushing, if eye irritation persists seek medical attention.

**SKIN CONTACT:**

If skin or hair contact has occurred remove any contaminated clothing and footwear, wash skin or hair thoroughly with soap and water. As the product is rated as Causes skin irritation, after washing if skin irritation develops or persists, consult a Doctor.

# SAFETY DATA SHEET

## SECTION 4 – FIRST AID MEASURES Continued

**INHALATION:** If affected, remove the patient from further exposure into fresh air, if safe to do so. If providing assistance, avoid exposure to yourself - only enter contaminated environments with adequate respiratory equipment, once environment has been assessed for flammable vapours. Once removed, lay patient down in a well-ventilated area and reassure them whilst waiting for medical assistance. If the person feels unwell and symptoms, such as dizziness or uncoordination occur, contact the Poisons Information Centre (phone Australia 131 126; New Zealand 0800 764 766) whilst waiting for medical assistance. If not breathing, provide artificial respiration and seek immediate medical assistance. If unconscious, place in a recovery position and seek immediate medical assistance.

**PROTECTION FOR FIRST AIDERS:** No personnel shall place themselves in a situation that is potentially hazardous to themselves. Assess the scenario for PPE requirements before entering. Assess environment for flammable vapours before entering. Never enter an environment with a flammable atmosphere. Do not enter contaminated area without a respirator or Self Contained Breathing Apparatus once you have assessed the atmosphere. As the product is hydrocarbon based and of low viscosity, if the person has ingested the product, do not use direct mouth-to-mouth resuscitation techniques. Always ensure that you are wearing gloves when dealing with first aid procedures involving chemicals and/or blood.

**FIRST AID FACILITIES:** Eye wash fountain and safety showers are recommended in the area where the product is used.

**4.2 MOST IMPORTANT SYMPTOMS & EFFECTS, BOTH ACUTE & DELAYED, CAUSED BY EXPOSURE:**  
**ACUTE:** Ingestion may lead to nausea and diarrhoea. Ingestion or inhalation of vapours may lead to irritation of the mouth and respiratory tract. Symptoms may include a burning sensation in the nose and throat, coughing or difficulty breathing. The product is rated as an aspiration hazard; if material is aspirated into the lungs it may exhibit as coughing, wheezing, congestion or fever. Vapours may cause drowsiness or dizziness. Inhalation of high vapour concentrations may cause central nervous system depression resulting in dizziness, headache, nausea and possible loss of coordination. The product is rated as an eye irritant. Eye contact may lead to localised burning, redness, pain, swelling and tearing. Skin contact may lead to redness or itching.

**CHRONIC:** Repeated or prolonged skin contact may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. Repeated or prolonged skin contact may also aggravate/exacerbate existing skin conditions, such as dermatitis.

**4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NECESSARY:**  
**ADVICE TO DOCTOR:** Treat symptomatically. As the product is hydrocarbon based and of low viscosity, if vomiting has occurred after ingestion, the patient should be monitored for adverse effects to ensure that the product has not aspirated into the lungs. Small amounts of this product aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary oedema. The product contains 2-Ethylhexanol which is suspected of damaging the unborn child. Inhalation of high vapour concentrations may cause central nervous system depression.

## SECTION 5 – FIRE FIGHTING MEASURES

**5.1 EXTINGUISHING MEDIA:**  
**SUITABLE MEDIA:** Use extinguishing media appropriate for surrounding fire. Use carbon dioxide, alcohol-resistant foam, dry chemical or water spray. Spray down fumes resulting from fire.

**UNSUITABLE MEDIA:** Avoid using full water jet directed at residual material that may be burning. Water may cause splattering on hot residues. Product will float on water.

# SAFETY DATA SHEET

## SECTION 5 – FIRE FIGHTING MEASURES Continued

### 5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

**COMBUSTION HAZARDS:** Combustion may produce oxides of carbon and nitrogen, as well as smoke and irritating vapours.

### 5.3 ADVICE FOR FIREFIGHTERS:

**FIRE:** This product is combustible with a typical flash point of 65°C. The vapour is heavier than air and will spread along the ground and may accumulate in low points or depressions. Therefore, ignition may occur well away from the point of release of the material. Keep storage tanks, pipelines, fire exposed surfaces, etc. cool with water spray.

**HAZCHEM CODE:** Not Applicable.

**EXPLOSION:** No information to indicate that the product is an explosion hazard; though the volatile solvent component may form an explosive mixture with air. Note: Under the WHS legislation, this product is rated as Flammable Liquid - Category 4, with a typical Flash point of 65°C. Extinguish all sources of flame or spark. Closed containers may explode when exposed to extreme heat.

### PROTECTIVE

**EQUIPMENT:** In the event of a fire, wear full protective clothing and self-contained breathing equipment with full-face piece operated in the pressure demand or other positive pressure mode.

## SECTION 6 – ACCIDENTAL RELEASE MEASURES

### 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

**PERSONAL PROTECTION:** For small spills, wear Nitrile gloves, glasses/goggles, boots and full-length clothing. During routine operation for a small spill in the open a respirator is not required. However, if mists or vapours are generated, an approved organic vapour/particulate respirator is required. For large spills, or in confined spaces, a full chemically resistant body-suit is recommended and the atmosphere must be evaluated for oxygen deficiency and whether the atmosphere is flammable. If in doubt about potential oxygen deficiency, wear self-contained breathing apparatus. Never enter an environment with a flammable atmosphere.

**CONTROL MEASURES:** Ventilate area and extinguish and/or remove all sources of ignition. CAUTION: Vapour may form an explosive mixture with air. Never enter a spill area unless you know the vapours have dissipated to make the area safe. Stop the leak if safe to do so. CAUTION: The spilled product will be slippery. Avoid contact with the spilled material.

**EMERGENCY PROCEDURES:** In the event of a spill or accidental release, notify the relevant authorities in accordance with all applicable regulations.

### 6.2 ENVIRONMENTAL PRECAUTIONS:

**SPILL ADVICE:** Do not allow product to enter drains, surface water, sewers or watercourses - inform local authorities if this occurs. Take precautions against static discharge. Ensure all equipment is grounded and use non-sparking tools during clean up operations.

### 6.3 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:

**CONTAINMENT:** Personnel must wear the appropriate clothing as required in Section 6.1 during containment procedures; after the environment has been evaluated. Contain the spill and absorb with a proprietary absorbent material, sand or earth. CAUTION: The spilled product will be slippery. Be careful of static discharges and/or sparking during clean up. For large spills prepare a bund/barrier/dyke ahead of the spill to confine the spill and allow later recovery. If there is the possibility of spills to enter drains, surface water, sewers or watercourses ensure bunding, or that drains are covered, to minimise the potential for this to occur.

# SAFETY DATA SHEET

## SECTION 6 – ACCIDENTAL RELEASE MEASURES Continued

**CLEANING PROCEDURES:** Having contained the spill, as mentioned above, collect all material quickly and place used absorbent in suitable containers. Be careful of static discharges and/or sparking during clean up. Use only non-sparking tools during cleaning operations. **CAUTION:** The spilled product will be slippery. Follow local regulations for the disposal of waste. For large spills that have been banded, the material can be pumped, using flammable liquid equipment, into vessels and returned for reprocessing or destruction. Personnel must wear the appropriate clothing as required in Section 6.1 during cleaning procedures; after the environment has been evaluated. Wash contaminated area and objects with detergent and water after spill has been cleared. Rinse the cleaned area with water. Do not allow wash water or rinsings to enter drains, surface water, sewers or water courses.

## SECTION 7 – HANDLING AND STORAGE, INCLUDING HOW THE CHEMICAL MAY BE SAFELY USED

### 7.1 PRECAUTIONS FOR SAFE HANDLING:

#### SAFE HANDLING:

Avoid contact with the product by using appropriate protective equipment such as gloves, glasses or goggles and full-length clothing. Extinguish any potential sources of ignition before using as flammable vapours will be generated during application. Do not leave containers in direct sunlight. Due to the possibility of pressure build up in the container, open the container with care. Avoid breathing mists or vapours. Do not smoke when handling the material. Prevent small spills and leakage to avoid slip hazards. Properly dispose of any contaminated rags or cleaning materials in order to prevent fire hazards. Eating, drinking, and smoking should be prohibited in the area where this material is handled, stored and processed. Workers should follow good personal hygiene practices, such as washing hands before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Keep containers tightly closed when not in use. Please note that flammable mixtures may be formed when residual material remains in empty containers. Prevent product from entering waterways, drains or sewers. There is the potential for electrostatic accumulation in the product. As a precaution, containers should always be earthed before dispensing commences.

### 7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:

#### SAFE STORAGE:

Classified as a Combustible Liquid (Typical Flash Point = 65°C). Store in a cool, dry, well ventilated area away from direct sunlight, ignition sources, oxidising agents, foodstuffs and clothing. Keep containers closed when not in use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store only in original containers. It is recommended that the product is stored below 25°C.

#### INCOMPATIBILITIES:

Strong oxidising substances including strong acids.

## SECTION 8 – EXPOSURE CONTROLS & PERSONAL PROTECTION

### 8.1 EXPOSURE CONTROL MEASURES:

**EXPOSURE LIMIT VALUES:** Exposure standards for the product have not been established. The following values are applicable for the individual components:

**Distillates, petroleum, hydrotreated light** (Manufacturer recommendation):

TWA: 165 ppm 1200 mg/m<sup>3</sup>

**1,2,3-Trimethyl Benzene** (Manufacturer recommendation):

TWA: 25 ppm (ACGIH)

**1,2,4-Trimethyl Benzene** (Manufacturer recommendation):

TWA: 25 ppm (ACGIH)

# SAFETY DATA SHEET

## SECTION 8 – EXPOSURE CONTROLS & PERSONAL PROTECTION Cont'd

### EXPOSURE LIMIT VALUES (Continued):

**1,3,5-Trimethyl Benzene** (Manufacturer recommendation):

TWA: 25 ppm (ACGIH)

**Xylene** (Manufacturer recommendation):

TWA: 100 ppm (ACGIH/OSHA) STEL: 150 ppm (ACGIH)

**Cumene:**

TWA: 25 ppm 125 mg/m<sup>3</sup> STEL: 75 ppm 375 mg/m<sup>3</sup>

### 8.2 BIOLOGICAL

**MONITORING:** No data available.

**8.3 CONTROL BANDING:** No data available.

### 8.4 ENGINEERING CONTROLS:

**ENGINEERING CONTROLS:** Special ventilation is not normally required when using this product in normal use scenarios. However, in the operation of certain equipment, at elevated temperatures, or in confined spaces mists or vapour may be generated and local exhaust ventilation should be provided to maintain airborne concentration levels below the nominated exposure standard and at an acceptable level that does not cause irritation. PLEASE NOTE: Due to the flammable nature of the product, if there is a necessity to use ventilation equipment it should not be a potential source of ignition for any vapours generated.

### 8.5 INDIVIDUAL PROTECTION MEASURES:

**EYE & FACE PROTECTION:** Wear safety glasses/goggles to avoid eye contact when handling. If there is a risk of splashing during use, a full face shield is recommended. Use eye protection in accordance with AS 1336 and AS 1337.

**SKIN (HAND) PROTECTION:** If there is the chance of contact with the material wear gloves to provide hand protection. Nitrile rubber gloves are recommended.

### SKIN (CLOTHING) PROTECTION:

During normal operating procedures, long sleeved clothing is recommended to avoid skin contact. Soiled clothing should be washed with detergent prior to re-use.

**RESPIRATORY PROTECTION:** During routine operation a respirator is not required. However, if mists or vapours are generated, an approved half face organic vapour/particulate respirator is required. Use respirators in accordance with AS 1715 and AS 1716.

**THERMAL PROTECTION:** Not applicable.

# SAFETY DATA SHEET

## SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 PHYSICAL AND CHEMICAL PROPERTIES:

<b>APPEARANCE:</b>	Straw liquid.
<b>ODOUR:</b>	Characteristic hydrocarbon solvent odour.
<b>ODOUR THRESHOLD:</b>	No data available.
<b>pH:</b>	Not applicable.
<b>MELTING/FREEZING POINT:</b>	No data available.
<b>INITIAL BOILING POINT:</b>	No data available.
<b>BOILING RANGE (°C):</b>	No data available.
<b>FLASHPOINT (°C):</b>	Typically 65°C.
<b>EVAPORATION RATE:</b>	No data available.
<b>FLAMMABILITY LIMITS (%):</b>	No data available.
<b>VAPOUR PRESSURE (kPa):</b>	No data available.
<b>VAPOUR DENSITY:</b>	No data available.
<b>DENSITY (g/mL @ 15°C):</b>	Typically 0.878.
<b>SOLUBILITY IN WATER(g/L):</b>	Insoluble in water.
<b>PARTITION COEFFICIENT:</b>	No data available for n-octanol/water.
<b>AUTO-IGNITION TEMP (°C):</b>	No data available.

**DECOMPOSITION TEMP (°C):** No data available.

**VISCOSITY (cSt @ 100°C):** Typically 2.3.

**VISCOSITY(cSt @ 40°C):** Typically 6.5.

## SECTION 10 – STABILITY AND REACTIVITY

**10.1 REACTIVITY:** The product does not pose any further reactivity hazards other than those listed in the following sub-sections.

**10.2 CHEMICAL STABILITY:** Stable under recommended storage and handling conditions (see section 7).

### 10.3 POSSIBILITY OF

**HAZARDOUS REACTIONS:** Keep away from strong oxidising agents, such as strong acids, chlorates, nitrates and peroxides. Hazardous polymerisation does not occur.

**10.4 CONDITIONS TO AVOID:** The product has a relatively low flash point of 65°C. Avoid ignition sources including heat and sparks. Observe the usual precautionary measures for handling chemicals. Do not heat the container or leave the container open when not in use.

### 10.5 INCOMPATIBLE

**MATERIALS:** Strong oxidising agents including strong acids.

### 10.6 HAZARDOUS DECOMPOSITION

**PRODUCTS:** Hazardous decomposition products are not expected to form during normal storage requirements. See Section 5.2 for Hazardous Combustion products.

## SECTION 11 – TOXICOLOGICAL INFORMATION

### 11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:

The product is a mixture and test data is not available for the product as a whole.

#### **Distillates, petroleum, hydrotreated light (IUCLID)**

Oral - LD<sub>50</sub> (Rat): > 5000 mg/kg

Dermal - LD<sub>50</sub> (Rabbit): > 2000 mg/kg

#### **Solvent naphtha, petroleum, heavy aromatic**

Oral - LD<sub>50</sub> (Rat): > 2900 mg/kg

#### **1,2,4-Trimethylbenzene**

Oral - LD<sub>50</sub> (Rat): 5000 mg/kg

Dermal - LD<sub>50</sub> (Rabbit): 3160 mg/kg

Inhalation - LC<sub>50</sub> (Rat, vapour, 4 hours): 18000 mg/m<sup>3</sup>

#### **N-Propylbenzene**

Oral - LD<sub>50</sub> (Rat): 6040 mg/kg



# SAFETY DATA SHEET

## SECTION 11 – TOXICOLOGICAL INFORMATION Continued

### **1,3,5-Trimethylbenzene**

Oral - LD<sub>50</sub> (Rat): >5000 mg/kg

Inhalation - LC<sub>50</sub> (Rat, vapour, 4 hours): 24000 mg/m<sup>3</sup>

### **Xylene**

Oral - LD<sub>50</sub> (Rat): >3523 mg/kg

Dermal - LD<sub>50</sub> (Rabbit): >14100 mg/kg

Inhalation - LC<sub>50</sub> (Rat, vapour, 4 hours): 5000-8500 ppm

### **1-Hexanol, 2-ethyl-**

Oral - LD<sub>50</sub> (Rat): 2040 mg/kg

Dermal - LD<sub>50</sub> (Rat): >3000 mg/kg

Dermal - LD<sub>50</sub> (Rabbit): 1970 mg/kg

Inhalation - LC<sub>50</sub> (Rat, vapour, 4 hours): 0.89 - 5.3 mg/l

### **Cumene**

Oral - LD<sub>50</sub> (Rat): 1400 mg/kg

Oral - LD<sub>50</sub> (Mouse): 12750 mg/kg

Dermal - LD<sub>50</sub> (Rabbit): 10578 mg/kg

Inhalation - LC<sub>50</sub> (Rat, vapour, 4 hours): 8000 ppm

### **11.2 SWALLOWED:**

The hydrocarbon component means this is a Schedule 5 Poison. As the product is hydrocarbon based and the viscosity is low (~6.5 cSt@40°C), caution should be taken in respect to aspiration into the lungs. Small amounts of this product aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary oedema. Ingestion of large amounts may lead to nausea and vomiting. During normal usage ingestion should not be a means of exposure.

### **11.3 SKIN CORROSION/ IRRITATION:**

This product is rated as Causes skin irritation. Symptoms may include redness or itching. Prolonged or repeated contact may cause defatting of the skin which may lead to dermatitis. Correct handling procedures incorporating appropriate protective clothing and gloves should minimise the risk. People with pre-existing skin conditions, such as dermatitis, should take extreme care so as not to exacerbate the condition.

### **11.4 SERIOUS EYE DAMAGE/ IRRITATION:**

The product is rated as Causes serious eye irritation. Symptoms may include localised burning, redness and tearing. Correct handling procedures incorporating appropriate eye protection should minimise the risk of eye damage/irritation.

### **11.5 RESPIRATORY OR SKIN SENSITISATION:**

This product is not expected to be a skin sensitiser, based on the available data and the known hazards of the components. This product is not expected to be a respiratory tract sensitiser, based on the available data and the known hazards of the components.

### **11.6 GERM CELL MUTAGENICITY:**

This product is not expected to be mutagenic, based on the available data and the known hazards of the components.

### **11.7 CARCINOGENICITY:**

This product is rated as May cause cancer. The product contains low levels of Cumene, as a component of the solvent naphtha, petroleum, light aromatic ingredient, which is rated as Carcinogenic Category 1B: H350i - May cause cancer by inhalation.

### **11.8 REPRODUCTIVE TOXICITY:**

This product is not expected to be a reproductive hazard based on the available data and the known hazards of the components. The product contains 2-Ethyl hexanol as a component, which is rated as Suspected of damaging the unborn child according to the NICNAS IMAP Report, however this is present at amounts well below the Concentration cut-off levels.

# SAFETY DATA SHEET

## SECTION 11 – TOXICOLOGICAL INFORMATION Continued

### 11.9 SPECIFIC TARGET ORGAN TOXICITY (STOT) -

#### SINGLE EXPOSURE:

This product is not expected to cause organ damage from a single exposure, based on the available data and the known hazards of the components. It contains components that are rated as May cause respiratory irritation and hydrocarbon solvents that may cause drowsiness and dizziness, however these are present at amounts well below the Concentration cut-off levels. The product is not expected to pose an irritation hazard at ambient temperature or under normal handling conditions. It contains hydrocarbon components, hence inhalation of vapours or mist (generated at elevated temperatures or by mechanical action) may cause irritation to the nose and throat. Inhalation of high concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea. Exposure to high levels of hydrocarbon solvent vapours may impact on the liver and kidneys.

### 11.10 SPECIFIC TARGET ORGAN TOXICITY (STOT) -

#### REPEATED EXPOSURE:

This product is not expected to cause organ damage from prolonged or repeated exposure based on the available data and the known hazards of the components. However, as the product is hydrocarbon based care should be taken in respect to repeated or prolonged exposure.

### 11.11 ASPIRATION HAZARD:

This product is rated as an aspiration hazard - May be fatal if swallowed and enters airways. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary oedema. This can be fatal. As the product is hydrocarbon based, if the product has been ingested or vomiting has occurred after ingestion, the patient must seek urgent medical attention and should be monitored for adverse effects.

11.12 OTHER INFORMATION: There is no additional information available.

## SECTION 12 – ECOLOGICAL INFORMATION

### 12.1 ECOTOXICITY:

The manufacturer nominates the following Ecotoxicity data:

#### **1,2,4-Trimethylbenzene**

EC<sub>50</sub> (Daphnia, 48hr): 6.14 mg/L

#### **Xylene**

LC<sub>50</sub> (Fish, 24hr): 13.4 ppm

LC<sub>50</sub> (Fish, 96hr): 13.5 mg/L

LC<sub>50</sub> (Fish, 96hr): 27 to 42 mg/L

There is no data available for the product as a whole. However, some of the components have been rated as Toxic to aquatic life with long lasting effects. Based upon these nominated values and the ratings supplied by the additive package manufacturer, by calculation the product is expected to be Harmful to aquatic life with long lasting effects.

### 12.2 PERSISTENCE & DEGRADABILITY:

Based on the available data and the known hazards of the components, the solvent constituents are expected to be inherently biodegradable, however the product contains components that may persist in the environment.

### 12.3 BIOACCUMULATIVE POTENTIAL:

There is no data available for the product as a whole.

### 12.4 MOBILITY IN SOIL:

There is no data available for the product as a whole..

### 12.5 OTHER ADVERSE EFFECTS:

There is no data available for the product as a whole. The product will float on water and the solvent component will evaporate rapidly into the air.

# SAFETY DATA SHEET

## SECTION 13 – DISPOSAL CONSIDERATIONS

### 13.1 DISPOSAL METHODS:

**PRODUCT:**

The product should not be released to the environment, so any unused material should be recycled wherever possible or be disposed of as hazardous waste at an appropriate collection depot. The product is also suitable for incineration at very high temperatures to prevent formation of undesirable combustion products. Spilled product that cannot be recovered should be absorbed and then shovelled into a suitable waste container, such as a plastic drum and then be treated as a solid waste. Follow Government regulations for disposal of such waste. All unused, waste or spilled product must be taken for recycling or disposal by suitably licensed contractors in accordance with Government regulations. Note: Waste product must be handled as a Combustible liquid.

**CONTAINERS:**

Empty containers may contain residual product. CAUTION: Residues are combustible and will ignite with a source of ignition. Containers should be completely drained in a well ventilated area where vapours cannot accumulate and then stored until reconditioned or disposed of. Empty containers should be taken for recycling or disposal through suitably licensed contractors in accordance with Government regulations. As containers may contain combustible residues, they should not be pressurised, cut by a grinder, drilled or exposed to heat, flames or other sources of ignition. Closed containers when exposed to such conditions/treatment may explode causing serious injury.

## SECTION 14 – TRANSPORT INFORMATION

This product is not regulated for land, sea or air transportation. (HS Code: 3911.90)

### 14.1 LAND (ADG Code):

**UN NUMBER:** Not applicable

**UN PROPER SHIPPING NAME:** Not applicable

**TRANSPORT HAZARD CLASS(ES):** Not applicable

**PACKAGING GROUP:** Not applicable

**ENVIRONMENTAL HAZARDS:** Not applicable

**SPECIAL PRECAUTIONS FOR USER:** Not applicable

**HAZCHEM CODE:** Not applicable

### 14.2 SEA (IMDG):

**UN NUMBER:** Not applicable

**UN PROPER SHIPPING NAME:** Not applicable

**TRANSPORT HAZARD CLASS(ES):** Not applicable

**PACKAGING GROUP:** Not applicable

**ENVIRONMENTAL HAZARDS:** Not applicable

**SPECIAL PRECAUTIONS FOR USER:** Not applicable

### 14.3 AIR (IATA):

**UN NUMBER:** Not applicable

**UN PROPER SHIPPING NAME:** Not applicable

**TRANSPORT HAZARD CLASS(ES):** Not applicable

**PACKAGING GROUP:** Not applicable

**ENVIRONMENTAL HAZARDS:** Not applicable

**SPECIAL PRECAUTIONS FOR USER:** Not applicable

# SAFETY DATA SHEET

## SECTION 15 – REGULATORY INFORMATION

### 15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS:

#### APPLICABLE REGULATIONS:

<b>SUSMP:</b>	Schedule 5 (S5).
<b>AICS:</b>	All ingredients are on the AICS List.
<b>MONTREAL PROTOCOL:</b>	Not determined.
<b>STOCKHOLM CONVENTION:</b>	Not applicable.
<b>ROTTERDAM CONVENTION:</b>	Not applicable.
<b>BASEL CONVENTION:</b>	Not determined.
<b>INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS (MARPOL):</b>	Not determined.

#### OTHER REGULATORY INFORMATION:

#### GHS CLASSIFICATION HAZARD CLASS & CATEGORY

**AND HAZARD STATEMENT:** Flammable Liquids Category 3; H226 - Flammable liquid and vapour.  
Flammable Liquids Category 4; H227 - Combustible liquid.  
Aspiration Hazard Category 1; H304 - May be fatal if swallowed and enters airway.  
Acute Toxicity Category 4; H312 - Harmful in contact with skin.  
Skin Corrosion/Irritation Category 1C; H314 - Causes severe skin burns and eye damage.  
Skin Irritation Category 2; H315 - Causes skin irritation.  
Serious Eye Damage/Irritation Category 2A; H319 - Causes serious eye irritation.  
Acute Toxicity Category 4; H332 - Harmful if inhaled.  
Specific Target Organ Toxicity (Single Exposure) Category 3; H335 - May cause respiratory irritation.  
Carcinogenicity Category 1B; H350i - May cause cancer by inhalation.  
Toxic to Reproduction Category 2; H361d - Suspected of damaging the unborn child.  
Chronic Aquatic Toxicity Category 2; H411 - Toxic to aquatic life with long lasting effects.  
Chronic Aquatic Toxicity Category 3; H412 - Harmful to aquatic life with long lasting effects.

**HSNO APPROVAL NUMBER:** HSR002587

**HSNO GROUP TITLE:** Fuel Additives (Combustible, Toxic [6.7]) Group Standard 2017

## SECTION 16 – ANY OTHER RELEVANT INFORMATION

#### SDS INFORMATION:

**Date of SDS Preparation:** 16<sup>th</sup> August 2018

**Revision:** 1.0

**REVISION CHANGES:** Changes to product formulation. Changes to Sections 2, 3, 5, 9, 11, 15 and 16.

#### ACRONYMS:

SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
CAS Number	Chemical Abstracts Service Registry Number
EINECS	European Inventory of Existing Commercial Chemical Substances
UN Number	United Nations Number
OSHA	Occupational Safety and Health Administration
ACGIH	American Conference of Governmental Industrial Hygienists
HSE-WEL	Health and Safety Executive - Workplace Exposure Limit
EH40	EH40/2005 Workplace Exposure Limits
IMDG	International Maritime Dangerous Goods
IATA	International Air Transport Association
IUCLID	International Uniform Chemical Information Database
RTECS	Registry of Toxic Effects of Chemical Substances
%W/W	Percent weight for weight
OECD	Organisation for Economic Co-Operation and Development

# SAFETY DATA SHEET

## SECTION 16 – ANY OTHER RELEVANT INFORMATION Continued

### ACRONYMS (Continued):

ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail
HAZCHEM Code	Emergency action code of numbers and letters which gives information to emergency services
NOHSC	National Occupational Health and Safety Commission
NICNAS	National Industrial Chemicals Notification & Assessment Scheme
IMAP	Inventory Multi-Tiered Assessment and Prioritisation
AICS	Australian Inventory of Chemical Substances
TWA	Time-Weighted Average
STEL	Short Term Exposure Limit
HSNO	Hazardous Substances and New Organisms Act 1996
GHS	Globally Harmonised System of Classification and Labelling of Chemicals
WHS	Work Health and Safety PPE Personal Protective Equipment.
LD <sub>50</sub>	Median Lethal Dose
LC <sub>50</sub>	Median Lethal Concentration
EC <sub>50</sub>	Effective Concentration of a substance that causes 50% of the maximum response after exposure for a nominated time
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
ECHA	European Chemicals Agency
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
HCIS	Hazardous Chemical Information System

### LITERATURE REFERENCES AND SOURCES OF DATA:

OECD Guidelines for Testing of Chemicals  
Annex I: OECD Test Guidelines for Studies Included in SIDS  
Manual for the Assessment of Chemicals Chapter 2 Data Gathering  
International Toxicity Testing Guidelines  
Hazardous Chemical Information System (HCIS) - Guidance Material for Hazard Classifications  
Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.  
Model Work Health and Safety Regulations.  
Model Work Health and Safety Regulations - Transitional Principles  
Workplace Exposure Standards for Airborne Contaminants  
Australian Dangerous Goods Code 7<sup>th</sup> Edition  
Approved Criteria for Classifying Hazardous Substances [NOHSC:1008 (2004)]  
Guidance on the Classification of Hazardous Chemicals under the WHS Regulations  
Assigning a Hazardous Substance to a Group Standard  
User Guide to the HSNO Thresholds and Classifications  
Summary User Guide to the HSNO Thresholds and Classifications of Hazardous Substances  
Correlation between GHS and New Zealand HSNO Hazard Classes and Categories  
HSNO Control Regulations  
Record of Group Standard Assignment  
Labelling of Hazardous Substances Hazard and Precautionary Information  
Thresholds and Classifications Under the Hazardous Substances and New Organisms Act 1996  
Workplace Exposure Standards and Biological Exposure Indices  
NICNAS IMAP Human Health Tier II Assessment for Distillates, petroleum, hydrotreated light, CAS Number: 64742-47-8  
NICNAS IMAP Human Health Tier II Assessment for Low Boiling Point Petroleum Naphthas including CAS Number: 64742-95-6  
NICNAS IMAP Human Health Tier II Assessment for 1-Hexanol, 2-ethyl-, CAS Number: 104-76-7  
NICNAS IMAP Human Health Tier II Assessment for Xylene, CAS Number: 1330-20-7  
NICNAS IMAP Human Health Tier II Assessment for Cumene, CAS Number: 98-82-6.

All information contained in this Safety Data Sheet and the health, safety and environmental information are considered to be accurate to the best of our knowledge as of the issue date specified above. However, no warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this data sheet.

Health and safety precautions and environmental advice noted in this data sheet may not be accurate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The Company accepts no responsibility for any injury, loss or damage, resulting from abnormal use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material.