



**100** Celebrating  
**YEARS**

**AUSTRALIAN OWNED AND TRUSTED SINCE 1926** 

# 10 TENTHS PREMIUM 5W-50 (Full Synthetic)

Last updated: 15/06/2026 3:22 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
FS5W50005	5L	4
FS5W50020	20L	

## PRODUCT BENEFITS

10 TENTHS Premium 5W-50 is a premium full synthetic SAE 5W-50, non-friction modified, modern engine oil. Contains advanced additive technology providing ULTIMATE PERFORMANCE and protection.

It may be used where API SP (American Petroleum Institute) is specified as well as for many manufacturers' requirements.

Use in modern 4, 6 & 8+ cylinder, multi cam, multi-valve including VVT, naturally aspirated, supercharged & turbocharged engines. It can be used in standard and high performance engines for both competition and normal on/off road use in a wide range of vehicles.

May be used in vehicles where SAE 5W-40 engine oils were originally recommended by the manufacturer. It can be used where ACEA A3/B3 is recommended in model years prior to 2017 and where ACEA A3/B4 is recommended in model years prior to 2008. It can also be used where API SN or previous API SM, SL, SJ or earlier specifications are recommended.

It is suitable for vehicles such as the Ford Mustang 2.3 Litre Turbo that requires a SAE 5W-50 oil, Subaru WRX, Nissan GT-R, and a wide range of other vehicles.

Suitable for use in passenger car, light commercial, competition vehicles and motorcycles and it can be used with petrol, LPG, E10, E85 (Racing & Competition only), diesel (without DPF), avgas, nitro, methanol & other conventional fuels. It is also suitable for use in four stroke motorcycles with wet clutches and meets JASO MA requirements.

## PRODUCT BENEFITS

- **FULL ZINC** anti-wear additive package for ultimate engine wear protection
- **Maximum** wear protection, minimum sludge formation & reduced piston deposits
- Competition proven and trusted for performance engines
- Longer engine life by reducing formation of high temperature engine deposits
- Blended using premium full synthetic base oils for excellent cold flow performance, thermal stability and maximum heat resistance
- Non-friction modified so can be used in motorcycles with wet clutches
- Formulated to meet Ford WSS-M2C-931-C specification for use in high performance vehicles

## PRODUCT PERFORMANCE LEVELS

- API SN
- API SP

## SUITABLE FOR USE WHERE SPECIFICATIONS BELOW ARE REQUIRED (FOR OUT OF WARRANTY SERVICE)

- ACEA A3/B3 (PRIOR TO 2017)
- ACEA A3/B4 (PRIOR TO 2008)
- API SL
- API SL/CF
- API SM
- API SM/CF





**100** *Celebrating*  
**YEARS**

**AUSTRALIAN OWNED AND  
TRUSTED SINCE 1926** 

**TYPICAL DATA**

Density at 15°C, kg/L	NA
Viscosity, Kinematic, cSt at 40°C	113
Viscosity, Kinematic, cSt at 100°C	18.5
Viscosity Index	184
Cold Cranking Viscosity, cP at -30°C	5382
Ca content, Mass %	0.296
Zinc, Mass %	0.124
Boron, Mass %	0.063
Total Base Number (TBN)	9.8