# BTS ULTRA 5W-40 (Full Synthetic)

Last updated: 06/08/2025 4:49 pm

PRODUCT CODE PACK SIZE CARTON QTY

#### **PRODUCT BENEFITS**

**BTS ULTRA 5W-40** is a premium full synthetic, SAE 5W-40 engine oil developed for use in modern petrol and diesel engines exclusively for professional workshops and service centres. It meets a broad range of specifications required by modern vehicle fleets to reduce workshop inventory whilst providing outstanding performance, protection and fuel economy. It is manufactured using advanced mid SAPS (Sulphated Ash, Phosphorus and Sulphur)\* additive technology for improved wear protection, fuel economy and reduced emissions.

For use where API SN/CF and ACEA C3 specifications are required

## **Application**

**BTS ULTRA 5W-40** is designed for use in modern 4, 6 & 8+ cylinder multi-cam, multi-valve (including VVT), naturally aspirated, supercharged & turbocharged low emission engines. It can be used in passenger cars, 4WD's & light duty commercial vehicles and is compatible with Petrol, LPG, E10, Hybrid, diesel, including those fitted with/without DPF's (Diesel Particulate Filters), biodiesel and most other conventional fuels.

BTS ULTRA 5W-40 may be used where SAE 5W-30, SAE 10W-30, SAE 0W-40 and SAE 5W-40 grade oils are specified by the manufacturer. It can be used where API SN and previous API specifications SM (2004-10), SL (2001-04), SJ (1998-2001) are recommended and where ACEA A3/B3 and A3/B4 is recommended in model years prior to 2010. It can be used in modern petrol and light duty diesel engines where ACEA C3 or ACEA C2 is specified by the manufacturer and in LPG and diesel engines where API CF or earlier is required. It may also be used as a replacement for ILSAC GF-3, GF-4 and GF-5 grade oils and where ACEA A1/B1 (Obsolete) and ACEA A5/B5 fuel economy oils are required.

BTS ULTRA 5W-40 is suitable for use in a wide range of petrol and light duty diesel vehicles including those fitted with a Diesel Particulate Filter (DPF). It is approved for warranty service by Mercedes Benz to MB-Approval 229.51 and can be used in GM vehicles requiring GMW 16177 (dexos™ 2), Volkswagen vehicles where VW 502 00 / 505 00 / 505 01 is specified. It can also be used in Porsche vehicles where Porsche A40 is needed and in BMW where BMW Longlife-04 is required as well as in many other makes and models including -

BMW	CHRYSLER	DODGE	HOLDEN/GM	HYUNDAI
JEEP	KIA	MERCEDES- BENZ	MITSUBISHI	NISSAN
SSANGYONG	SUBARU	ТОУОТА	AND MANY OTHER MAKES OF VEHICLES	

### **PRODUCT BENEFITS**

- Full Ssyntehtic high performance base oil and latest advanced additive packs
- MAXIMUM wear protection, minimum sludge formation & reduced piston deposits
- Current European ACEA C3
- EXCEEDS many manufacturer product vehicle requirements
- LONG LIFE extended engine oil drain intervals
- IMPROVED fuel economy
- Protection for emission control devices such as DPF's & catalytic converters
- · Superior cold engine start up performance, minimising friction and wear at start-up

## **PRODUCT PERFORMANCE LEVELS**

**TYPICAL DATA** 

PENRITE ULTRA PULSTATHER PERFOL EDISES.

5W-40

Website: www.penriteoil.com.au Email: penrite@penriteoil.com.au