



PENRITE



85% REDUCTION
IN LANDFILL
WASTE

CLASSIC V-DUB

Last updated: 27/05/2021 1:58 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
CLASV005	5L	4

PRODUCT BENEFITS

Classic V-Dub is a premium mineral, multi-grade SAE 20W-60 engine oil, designed to provide outstanding protection for both horizontally opposed, flat four/six (Boxer) and in line, air or water cooled petrol and diesel engines. It features a double layer of engine wear protection with a **HIGH ZINC** anti-wear formulation and increased operating temperature viscosity over standard SAE grade oils.

APPLICATIONS

Classic V-Dub is designed for use in Volkswagen Beetles (Type 1), Super Beetle (Type 131), Kombi/Transporter Vans (Type 2), Karmann Ghia, Fastback and Squareback (Type 3), 411/412 (Type 4), Kubelwagen (Type 82), Trekker (Type 181) and VW/Porsche 914 vehicles, manufactured from 1940 to 2003. It is also suitable for Formula Vee race cars and dune buggies fitted with Volkswagen air and water cooled engines as well as in other makes and models such as air cooled Porsche 911/356 models, Citroen 2CV, Fiat 500, NSU Prinz, Tatra and in BMC & Leyland Minis as a combined engine and transmission oil. It may also be used in early water cooled engines in Golf, Passat and Caravelle/Transporter vans including inline diesel engine T3 vans as well as for rotary engine vehicles where this viscosity and specification is required.

Classic V-Dub can be used where SAE 30, 20W-40 or 20W-50 engine oils were originally specified. It features a standard multigrade cold temperature SAE viscosity grade with an increased operating temperature range that provides an added layer of protection for the engine especially under increased load and temperature conditions. It can also be used in other petrol and diesel engines that require this grade and specification of oil.

Classic V-Dub meets API SJ/CG-4 and contains a high zinc additive pack for added anti-wear protection for older engines. It contains a special additive pack that has been specifically selected to provide better protection for Volkswagen air and water cooled engines. It is compatible with the original grades that were specified and exceeds their specification requirements, hence offering a greater level of engine protection compared to the original oils.

Classic V-Dub contains a Tacky Additive so that when vehicles are laid up, the engine oil doesn't run off the internal surfaces. This, combined with an increased level of rust inhibitor, provides protection against corrosion and deterioration when the engine is not used or in storage.

PRODUCT BENEFITS

- **INCREASED** operating temperature protection compared to SAE 30 monograde and SAE 20W-40 & 20W-50 multigrade engine oils
- **HIGH ZINC** anti-wear additive package for ultimate engine wear protection
- Reduces oil consumption and maintains oil pressure
- Contains optimum quantities of modern additives for better engine protection
- Exceeds the originally required oil quality and performance levels
- Provides protection against rust and corrosion when vehicle is not used for long periods

PRODUCT PERFORMANCE LEVELS

- ACEA E2
- API SJ/CG-4
- CCMC D4
- CCMC G1
- CCMC PD1

SUITABLE FOR USE WHERE SPECIFICATIONS BELOW ARE REQUIRED

(FOR OUT OF WARRANTY SERVICE)

- API SG
- API SH





PENRITE



**85% REDUCTION
IN LANDFILL
WASTE**

TYPICAL DATA

Density at 15°C, kg/L	0.879
Viscosity, Kinematic, cSt at 40°C	211
Viscosity, Kinematic, cSt at 100°C	23.4
Viscosity Index	136
Ca content, Mass %	0.337
Zinc, Mass %	0.148
Phosphorus, Mass %	0.142