



100 Celebrating
YEARS

AUSTRALIAN OWNED AND TRUSTED SINCE 1926 

CONVOY FLEET GEAR 75W-90 (Synthetic)

Last updated: 15/12/2025 3:58 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
HDTD75W90020	20L	
HDTD75W90205	205L	

PRODUCT BENEFITS

Convoy Fleet Gear 75W-90 is a premium quality, heavy duty, full synthetic total driveline fluid designed to meet the requirements of modern heavy duty commercial differentials and transmissions operating under the harshest of conditions. with high loads and high temperatures.

APPLICATION

Convoy Fleet Gear 75W-90 is recommended for use in drivetrains of modern heavy duty trucks, buses and other commercial vehicles requiring a full synthetic SAE 75W-90 gear oil. It is recommended for use in both transmissions and differentials and can be used as a total driveline fluid where it meets the requirements of many commercial vehicle manufacturers.

It is ideal for use in Scania trucks where Scania STO 2:A is required and in Volvo trucks where synthetic axle fluid 97312 is specified. It may also be used in MAN trucks and buses where MAN 341 Type GA2 is required and where an API GL-5 or GL-4 fluid is required for Non-Synchronised gearboxes as well as in many other heavy duty applications.



PRODUCT BENEFITS

- Excellent wear protection
- Smooth gear operation for longer
- Outstanding performance under high temperatures and load conditions
- Full Synthetic base oils for long life and heat resistance
- Minimises inventory with one oil for the total driveline
- High Viscosity Index allows excellent lubrication at high and low temperatures

PRODUCT PERFORMANCE LEVELS

- | | |
|-----------------------|----------------|
| • API GL-4 | • ZF TE-ML 02B |
| • API GL-5 | • ZF TE-ML 05A |
| • API MT-1 | • ZF TE-ML 07A |
| • Mack GO-J | • ZF TE-ML 08 |
| • MAN 341 Z2 | • ZF TE-ML 12B |
| • MAN 342 S1 | • ZF TE-ML 12L |
| • MIL-PRF 2105E | • ZF TE-ML 12N |
| • SAE J2360 | • ZF TE-ML 16B |
| • SCANIA STO 1:0 | • ZF TE-ML 16F |
| • SCANIA STO 1:1G | • ZF TE-ML 17B |
| • Scania STO 2:0 A FS | • ZF TE-ML 19C |
| • Volvo 97312 | • ZF TE-ML 21A |

TYPICAL DATA

Colour	Amber
Density at 15°C, kg/L	0.875
Viscosity, Kinematic, cSt at 40°C	94
Viscosity, Kinematic, cSt at 100°C	15.5
Viscosity Index	175