



100 Celebrating
YEARS

**AUSTRALIAN OWNED AND
TRUSTED SINCE 1926** 

CONVOY MULTI-FLEET DIESEL 10W-40 (Synthetic)

Last updated: 26/08/2025 9:36 am

PRODUCT CODE	PACK SIZE	CARTON QTY
DLD020	20L	
DLD205	205L	

PRODUCT BENEFITS

Convoy Multi-Fleet Diesel 10W-40 is a SAE 10W-40 synthetic performance engine oil for heavy-duty applications. It is formulated with premium quality base oils and additives to provide optimum performance and protection for OEM long-drain applications.

APPLICATION

Convoy Multi-Fleet Diesel 10W-40 is suitable for naturally aspirated and turbo charged light and heavy-duty diesel engines where a SAE 10W-40 engine oil is specified by the manufacturer and in applications where oils meeting API CI-4 or ACEA E4 or ACEA E7 are recommended.

It is developed for use in Scania trucks and buses to provide the best total operating economy for Scania Euro V engines and is also suitable for Scania Euro VI engines with after treatment systems. This includes KN-PGRT Euro 5 engines, All V8s including LPGRS and KN-PGRT Euro 6 engines (Note: using LDF-3 in Euro VI engines can reduce DPF service life). It allows for extended drain intervals and is compatible with high sulphur fuels.

VEHICLES & FUEL TYPES

Convoy Multi-Fleet Diesel 10W-40 is suitable for light & heavy duty commercial vehicles, construction, mining and agricultural equipment. It is suitable for use with Diesel and LPG fuels.

Please note: Some trucks and heavy vehicles fitted with DPFs may need to use **Convoy Ultra HD 10W-40** or **Convoy Ultra HD 5W-30** oils. Please check Penrite Lube Recommendation Guide for the correct lubricant.

PRODUCT BENEFITS

- Suitable for OEM Long Drain and extended performance requirements
- EGR and SCR compatible
- Controls oil consumption
- Provides ideal wear, bore polish and deposit protection
- Effective dispersant additives keep soot in suspension, reducing wear

PRODUCT PERFORMANCE LEVELS

- ACEA E4
- ACEA E7
- API CI-4
- Cummins CES 20077
- Cummins CES 20078
- Deutz DQC IV-18
- Mack EO-N
- MAN M3277
- MB 228.5
- MTU Type 3
- Renault RLD-2
- Scania LDF-3
- Volvo VDS-3





100 *Celebrating*
YEARS

**AUSTRALIAN OWNED AND
TRUSTED SINCE 1926** 

TYPICAL DATA

Colour	Amber
Density at 15°C, kg/L	0.86
Viscosity, Kinematic, cSt at 40°C	98
Viscosity, Kinematic, cSt at 100°C	14.4
Viscosity Index	152
Ca content, Mass %	0.42
Zinc, Mass %	0.12
Phosphorus, Mass %	0.11
Sulphated Ash, Mass %	1.6
Total Base Number (TBN)	15.3