



100 Celebrating
YEARS

AUSTRALIAN OWNED AND TRUSTED SINCE 1926 

ENVIRO+ EU 5W-40 (FULL SYN.)

Last updated: 10/11/2025 12:17 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
EPLUSEU5W40007	7L	

PRODUCT BENEFITS

ENVIRO+ EU 5W-40 is a premium **full synthetic**, **SAE 5W-40** engine oil. It meets the performance requirements of many manufacturers such as Audi, BMW, Hyundai, Kia, Mercedes-Benz, Mitsubishi, Nissan, Subaru & VW. It is manufactured using advanced mid **SAPS** (Sulphated Ash, Phosphorus and Sulphur)* **additive** technology.

ENVIRO+ EU 5W-40 meets **API SN** and **ACEA C3** specifications.

*Low and mid **SAPS** oils may sometimes be referred to as "**Low Ash**" oils

APPLICATION

ENVIRO+ EU 5W-40 is designed for use in **modern** 4, 6 & 8+ cylinder multi-cam, multi-valve (including VVT), naturally aspirated, **supercharged** & turbocharged engines. It is not suitable for **Rotary** engines.

ENVIRO+ EU 5W-40 is suitable for use in passenger cars, 4WDs & **light duty** commercial vehicles and is **compatible** with Petrol, **LPG**, **E10**, light duty **diesel** engines including those fitted **with/without DPF's** (Diesel Particulate Filters) and most other **conventional** fuels.

ENVIRO+ EU 5W-40 is suitable for use in VAG (Volkswagen Automotive Group) vehicles where VW 504 00/507 00 specifications are required for **non-warranty** service. (For **VW warranty service** we recommend **fully approved ENVIRO+ 5W-30**). It is also suitable for use where MB 229.31/229.51 and BMW Longlife'04 are required in vehicles such as Mercedes-Benz, BMW, Jeep, Chrysler, Dodge & SsangYong. It may also be used for specific Kia, Mini, Mitsubishi, Nissan, Hyundai, Saab, Subaru and Suzuki vehicles **equipped** with a DPF.

ENVIRO+ EU 5W-40 is not recommended for use in **four stroke** motorcycles with wet clutches. The appropriate Penrite **MC-4ST** motorcycle oil should be used for these applications.

Please Note: A 58mm cap with pouring **tap** is available to fit 7, 10 & 20 litre packs. <https://penriteoil.com.au/products/58mm-plastic-tap>

PRODUCT BENEFITS

- **FULL SYNTHETIC** high performance **base oil** and latest advanced **additive** packs
- **EXCEEDS** many manufacturer product vehicle **specifications**
- **LONG LIFE** extended engine oil drain intervals
- **MAINTAINS** OE performance outside of **warranty** period
- Protection for emission control devices such as **DPFs** & catalytic converters
- Maximum **wear** protection, minimum **sludge** formation & reduced **piston deposits**
- Superior cold engine start up performance, minimising friction and wear at start-up

PRODUCT PERFORMANCE LEVELS

- ACEA C3
- API SN
- VW 504 00 / 507 00

TYPICAL DATA

Density at 15°C, kg/L	0.850
Viscosity, Kinematic, cSt at 40°C	94.8
Viscosity, Kinematic, cSt at 100°C	14.4
Viscosity Index	202
Cold Cranking Viscosity, cP at -30°C	5484
Ca content, Mass %	0.183
Zinc, Mass %	0.089
Phosphorus, Mass %	0.080

