



PENRITE



85% REDUCTION
IN LANDFILL
WASTE

ENVIRO+ 5W-30 (FULL SYN.)

Last updated: 01/02/2024 11:12 am

PRODUCT CODE	PACK SIZE	CARTON QTY
EPLUS5W30001	1L	6
EPLUS5W30005	5L	4
EPLUS5W30007	7L	
EPLUS5W30010	10L	
EPLUS5W30020	20L	
EPLUS5W30020BOX	20L	
EPLUS5W30060	60L	
EPLUS5W30205	205L	



PRODUCT BENEFITS

ENVIRO+ 5W-30 is a premium full synthetic, SAE 5W-30 **Original Equipment Manufacturer (OEM), Fully Licensed and Warranty Approved** engine oil. It is fully approved for warranty service for VAG (Volkswagen Automotive Group) vehicles such as Volkswagen / Audi / Skoda / Seat engines using the latest advances in mid SAPS (Sulphated Ash, Phosphorus and Sulphur)* additive technology.

Enviro+ 5W-30 is VW 504 00/507 00 **APPROVED** and exceeds ACEA C3 specifications.

APPROVALS AND LICENSES

- [Click Here](#) for VW Approval 504 00 / 507 00

APPLICATION

ENVIRO+ 5W-30 is designed for use in modern 4, 6 & 8+ cylinder multi-cam, multi-valve (including VVT), naturally aspirated, supercharged & turbocharged engines. It is suitable for use in direct injection (FSI/TSI) petrol and light duty diesel (TDI) engines including those fitted with/without DPFs (Diesel Particulate Filters).

ENVIRO+ 5W-30 may be used where SAE 0W-30, 5W-30 and 10W-30 grade oils are specified by the manufacturer. It can be used where ACEA C3 oils are specified by the manufacturer. It can also be used for vehicle models prior to 2008 model year where fuel economy specifications ACEA A1/B1 (Obsolete) and ACEA A5/B5 are required or where ACEA A3/B4 was specified. It may also be used where ACEA C2 is required.

ENVIRO+ 5W-30 is suitable for warranty service in Audi, Volkswagen and Skoda vehicles where VW 504 00 / 507 00 specifications are required. It is also suitable for use where MB 229.31/229.51, BMW Longlife-04, Porsche C30, Chrysler MS-11106 oils are required in vehicles such as Mercedes Benz, BMW, Porsche, Chrysler/Jeep & SsangYong as well as other vehicles requiring these specifications.

VEHICLE & FUEL TYPES

ENVIRO+ 5W-30 is suitable for use in passenger cars, 4WDs & light commercial vehicles and can be used with Petrol, LPG, E10, diesel (With & Without DPFs) & other conventional fuels. It is not recommended for use in motorcycles.

IMPORTANT MAINTENANCE INFORMATION

For vehicles fitted with a Diesel Particulate Filter, we recommend the use of Penrite **ENVIRO+DPF CLEANER** to clean & prevent DPF blockages, maximise catalyst life and improve engine efficiency, power & fuel economy.

NOTE: when changing oil, Penrite recommend using **Penrite Engine Flush**, a fast acting, solvent free, engine cleaning formulation that removes engine deposits, sludge and contaminants with the oil service drain. It contains added zinc for engine wear protection and its fast acting formulation works in 10 minutes.

Please Note: A 58mm cap with pouring tap is available to fit 7, 10 & 20 litre packs. <https://penriteoil.com.au/products/58mm-plastic-tap>

* Low SAPS oils may sometimes be referred to as "Low Ash" oils



PENRITE



**85% REDUCTION
IN LANDFILL
WASTE**

PRODUCT BENEFITS

- **Manufacturer Approved** product to maintain vehicle warranty & specifications
- **Long** engine oil drain intervals
- **Maintains** fuel economy
- **Excellent** protection for emission control devices such as DPFs & Catalytic converters
- **Maximum wear protection**, minimum sludge formation & reduced piston deposits
- **Excellent** resistance to viscosity and thermal breakdown even in extreme service
- **Superior** cold engine start up performance, minimising friction and wear at start-up

MANUFACTURER'S (OEM) APPROVALS & INDUSTRY LICENSES

- VW Standard 504 00
- VW Standard 507 00

PRODUCT PERFORMANCE LEVELS

- ACEA C3
- API SP
- BMW LL-04
- BMW Longlife-04
- Chrysler MS-11106
- Fiat 9.55535-S3
- MB 229.31
- MB 229.51
- MB 229.52
- Porsche C30
- VW 504 00
- VW 504 00 / 507 00
- VW 507 00

SUITABLE FOR USE WHERE SPECIFICATIONS BELOW ARE REQUIRED

(FOR OUT OF WARRANTY SERVICE)

- A5/B5 (PRIOR TO 2008)
- ACEA A1/B1 (Obsolete)
- ACEA A3/B4 (PRIOR TO 2008)
- ACEA C2

TYPICAL DATA

Density at 15°C, kg/L	0.852
Viscosity, Kinematic, cSt at 40°C	68.3
Viscosity, Kinematic, cSt at 100°C	11.7
Viscosity Index	169
Cold Cranking Viscosity, cP at -30°C	5906
Ca content, Mass %	0.162
Zinc, Mass %	0.085
Phosphorus, Mass %	0.075
Sulphated Ash, Mass %	0.70
Total Base Number (TBN)	6.62