



PENRITE



85% REDUCTION
IN LANDFILL
WASTE

EXTREME PRESSURE GREASE

Last updated: 25/03/2022 4:06 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
EPGR00045	450g	6
EPGR0005	500g	6
EPGR0025	2.5Kg	6
EPGR020	20Kg	
EPGR180	180Kg	

PRODUCT BENEFITS

Extreme Pressure Grease is an NLGI No 2, red coloured, general purpose grease manufactured from high quality base oils and uses a lithium soap base.

APPLICATION

Extreme Pressure Grease is suitable for use in all general grease applications in automotive and industrial service. This includes plain bearings, slow speed wheel and anti-friction bearings, chassis grease, general plant lubrication and agricultural and construction equipment lubrication.

NOTE: For high speed, high temperature applications, including wheel bearings of vehicles fitted with disc brakes, [Penrite High Temperature Wheel Bearing Grease](#) should be used.

PRODUCT BENEFITS

- Extreme pressure performance for protection against shock loadings
- Resists water wash out.
- Protects against rust and corrosion.
- Long service life.
- Tackiness additive helps grease stay in place.

PRODUCT PERFORMANCE LEVELS

- DIN 51502: KP2K-30
- ISO 6743: ISO-L-XCDHB 2
- NLGI 2

TYPICAL DATA

Colour	Red
NLGI Grade	2
Soap Type	Lithium
Density at 15°C, kg/L	0.9
Base Oil Viscosity, ISO	320
Operating Temperature Range °C	-20° to +130°
Appearance	Smooth Tacky
Timkin OK Load, kg	18
Drop Point, °C	190
4-ball Weld Load, kg	400
Water Washout, 1hr/80°C, %	4

