



100 Celebrating
YEARS

AUSTRALIAN OWNED AND TRUSTED SINCE 1926 

FARMRITE STOU

Last updated: 14/01/2026 2:10 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
UFO020	20L	
UFO205	205L	

PRODUCT BENEFITS

FARMRITE STOU (Universal Farm Oil) is a premium mineral Super Tractor Oil Universal (STOU) manufactured from highly refined base oils and advanced multi-functional additives. It is a multi purpose product for use in a wide range of machines and covers multiple applications.

Formerly - UNIVERSAL FARM OIL

APPLICATION

It is designed for use in 4 stroke naturally aspirated & turbo charged diesel and petrol engines, transmissions, front & rear axles, differentials, wet brakes, hydraulics, Power Take Off (PTO) clutches and some final drives of farm tractors and construction equipment. It can be used where 15W-40, 20W-40 and 15W-30 grade oils are specified or where SAE 80W or SAE 90 grade gear oils are specified.

FARMRITE STOU reduces inventory holding as one oil can be used for most applications, also lessening the chance of mis-application. It can reduce wet brake squawk in rear axles where normal tractor transmission oils have been used previously and can be used in many diesel engines (up to API CG-4 performance)

Please Note: A 58mm cap with pouring tap is available to fit 20 litre packs. <https://penriteoil.com.au/products/58mm-plastic-tap>



PRODUCT BENEFITS

- One oil for both hydraulic and engine applications
- Saves on Inventory costs
- Reduces the chances of mis-matching products
- Can be used in both Petrol & Diesel applications

PRODUCT PERFORMANCE LEVELS

- ACEA E3
- Allison C-3
- Allison C-4
- API CG-4/SF
- API GL-4
- Caterpillar TO-2
- Ford M2C159-B
- Ford M2C159-C
- Ford M2C86-A
- JDM J27
- John Deere JD20A
- John Deere JD20C
- MAN 271
- Massey Ferguson MF M1135
- Massey Ferguson MF M1139
- Massey Ferguson MF M1141
- Massey Ferguson MF M1143
- Massey Ferguson MF M1144
- Massey Ferguson MF M1145
- MB 227.1.
- MIL-L-2104D
- New Holland 420A
- New Holland 82009201
- New Holland 82009202
- New Holland 82009203
- Sperry Vickers Eaton I-280-S
- Sunstrand JDQ84
- Vickers 104c Pump
- Volvo BM
- ZF TE ML 06
- ZF TE ML 07

SUITABLE FOR USE WHERE SPECIFICATIONS BELOW ARE REQUIRED (FOR OUT OF WARRANTY SERVICE)

- API CG-4/SF
- API GL-4



100 *Celebrating*
YEARS

**AUSTRALIAN OWNED AND
TRUSTED SINCE 1926** 

TYPICAL DATA

Density at 15°C, kg/L	0.871
Viscosity, Kinematic, cSt at 40°C	100
Viscosity, Kinematic, cSt at 100°C	14
Viscosity Index	142
Cold Cranking Viscosity, cP at -20°C	4767
Zinc, Mass %	0.139