



100 Celebrating
YEARS

AUSTRALIAN OWNED AND TRUSTED SINCE 1926 

FARMRITE UTTO

Last updated: 11/03/2026 5:18 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
TTH020	20L	
TTH205	205L	
TTH1000LTR	1000L	

PRODUCT BENEFITS

FARMRITE UTTO (Tractor Transmission & Hydraulic Oil) is a multipurpose, 10W-30 / 75W-80 UTTO (Universal Tractor & Transmission Oil) tractor transmission & hydraulic fluid manufactured using highly refined base oils and the latest technology additive package.

Formerly - TRACTOR TRANSMISSION & HYDRAULIC OIL

APPLICATION

It is designed for use in a wide range of transmissions, hydraulics, PTOs, hydraulic bearings and some final drives of farm tractors and construction equipment, especially those utilising wet brake systems. Can be used as a hydraulic oil where ISO 68 grades are specified.

It meets the requirements of Case New Holland MAT 3540 and API GL-4 as well as many other specifications. It may be used where JD20A/B/C Hy-Gard is specified and is also suitable for use in the power steering systems of post EF Ford Falcon and its derivatives where a M2C134-D fluid is specified.

FARMRITE UTTO contains anti wear agents that provide wear protection as well as corrosion protection. It also quietens wet brake chatter without affecting braking performance.

Please Note: A 58mm cap with pouring tap is available to fit 20 litre packs. <https://penriteoil.com.au/products/58mm-plastic-tap>

PRODUCT BENEFITS

- Reduces inventory holding
- Lessens the chance of mis-application
- Reduces squawk and chatter from wet brake systems
- Effective anti-wear additives
- Protects against rust and corrosion.
- Long service through good thermal stability.
- Latest technology for maximum protection.

PRODUCT PERFORMANCE LEVELS

- Allison C-4
- API GL-4
- Case New Holland MAT 3526
- Case New Holland MAT 3540
- Ford ESN-M2C134-D
- Ford ESN-M2C86-B
- Ford ESN-M2C86-C
- JL Case MS-1204
- JL Case MS-1206 (Powergard PFT)
- JL Case MS-1207 (Hytran Plus)
- JL Case MS-1209 (Hytran Ultra or Multi))
- John Deere JD20C
- Kubota UDT Fluid
- Massey Ferguson M1135 Permatran III
- Massey Ferguson M1141
- Massey Ferguson M1143
- Massey Ferguson M1145
- Volvo VME WB101
- ZF TE-ML 03E
- ZF TE-ML 05F
- ZF TE-ML 06E
- ZF TE-ML 06F
- ZF TE-ML 06K
- ZF TE-ML 06M
- ZF TE-ML 06N
- ZF TE-ML 17E





100 *Celebrating*
YEARS

**AUSTRALIAN OWNED AND
TRUSTED SINCE 1926** 

TYPICAL DATA

Colour	Amber
SAE Grade	10W-30/75W-80
Density at 15°C, kg/L	0.867
Viscosity, Kinematic, cSt at 40°C	59
Viscosity, Kinematic, cSt at 100°C	9.6
Viscosity Index	146
Ca content, Mass %	0.075
Phosphorus, Mass %	0.030