GRAPHITE GREASE

Last updated: 29/08/2022 2:46 pm

PRODUCT CODE | PACK SIZE | CARTON QTY

PRODUCT BENEFITS

Penrite Graphite Grease is a grey/black coloured, NLGI 3, graphite impregnated calcium based grease

APPLICATION

Penrite Graphite Grease is designed for the lubrication of spring leaves, handbrake cables, flexible drives and exposed chains.

Penrite Graphite Grease is suitable for use in slow speed plain bearings and slides where a heavy grease with solid lubricants is required.

Penrite Graphite Grease can also be used in industrial, mining and construction equipment including bulldozers, scrapers, loading shovels and dump trucks where graphite grease is recommended and high temperature capability is not required.

Penrite Graphite Grease can be used in plain bearing locks, latches and fasteners, cables and springs and even as a fifth wheel lubricant.

NOTE: Should not be used in wheel bearings or where temperatures are likely to exceed 60°.

PRODUCT BENEFITS

- · Good resistance to water washout
- Long service life
- · Protects against wear, rust and corrosion

PRODUCT PERFORMANCE LEVELS

NLGI 3

TYPICAL DATA

Colour Grey/Black

NLGI Grade

Soap Type Calcium (Graphite)

Graphite Content, % 15
Base Oil Viscosity, ISO 100

Operating Temperature Range °C to +60° Max.

Drop Point, °C 80



Website: www.penriteoil.com.au Email: penrite@penriteoil.com.au