



# PENRITE



85% REDUCTION  
IN LANDFILL  
WASTE

## GREEN OEM COOLANT PREMIX

Last updated: 13/07/2021 5:14 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
COOLGREENPMX001	1L	6
COOLGREENPMX005	5L	3
COOLGREENPMX020	20L	
COOLGREENPMX205	205L	

### PRODUCT BENEFITS

**Green OEM Coolant Premix** is a **GENUINE GLYSANTIN® G48®**, Original Equipment Manufacturer (OEM), fully licensed and warranty approved, type "A" ethylene glycol, anti-freeze anti-boil coolant as used in initial manufacturer factory fills. It uses a technically advanced HYBRID (HOAT - Hybrid Organic Acid Technology) based inhibitor system that is Phosphate, Amine and Nitrite free. The extended long life inhibitor formulation prevents rust, corrosion, cavitation and degradation of the cooling system for 8 years or 500,000km. It is available in both concentrate and premix formulations.



**Green OEM Coolant Premix** is mixed at a 50% concentration level as per initial manufacturer requirements.

**PLEASE NOTE:** *Green OEM Coolant Concentrate replaces 7 Year Green Coolant concentrate, 4 Year Long Drain Anti Freeze Anti Boil Coolant and Heavy Duty 50/50 premix*

### APPLICATION

**Green OEM Coolant Premix** is suitable for the cooling systems of petrol, LPG, light and heavy duty diesel and industrial engines where Hybrid (HOAT) type anti-freeze / anti-boil and anti-corrosion properties are required.

**Green OEM Coolant Premix** is suitable for passenger cars, 4WD's, motorcycles, light & heavy duty commercial vehicles, construction and agricultural equipment. It is especially suited to vehicles of European origin such as Audi / VW (G11), BMW, Mercedes, Porsche (Pre-1995), Volvo, Opel & Saab, but it may be used in all types of vehicles.

**Green OEM Coolant Premix** provides long-term protection against rust and corrosion for all materials used in the engine and in the cooling system construction. It protects cast iron, aluminium, copper and solder alloys as well as the hoses, seals and plastics used for the cooling system construction. It is effective in all cast iron aluminium engines that are under load or used in extreme hot and cold climates.

**Green OEM Coolant Premix** may be used in all types of vehicles that use green, blue or yellow coloured initial fill coolants and it is also suitable for use in out of warranty service to maintain OEM performance. It is also ideal for motorcycles.

**Green OEM Coolant Premix** is a 50% concentration formulation and is ready to use directly from the container. It is pre-mixed with **Penrite De-Mineralised Water** and can be poured directly into the cooling system. No further dilution is required. It can be used as a complete service refill, top up or is safe to mix with compatible type A coolant. Penrite recommend that a 50% concentration level should be maintained for maximum, performance and longevity of the coolant and protection of the cooling system.

### COOLANT TESTING

For measuring coolant concentration and condition, we recommend **Penrite Coolant Test Strips**. Penrite recommend flushing the cooling system prior to a complete service refill. **Penrite Radiator Flush** effectively cleans the system in 7 minutes and prepares the cooling system for new coolant.

### DOSE RATE - FREEZING POINT BOILING POINT

Mix Ratio	50%
Freezing Point	-38°C
Boiling Point	+109°C



# PENRITE



**85% REDUCTION  
IN LANDFILL  
WASTE**

## **PRODUCT BENEFITS**

- **OEM Approved** to maintain manufacturer's warranty & specifications
- **8 Year 500,000km** drain intervals if used and maintained at 50%
- Protects all internal surfaces from corrosion
- **Note: Premix coolants do not require further dilution with demineralized water**
- Phosphate free formulation allows hard water use
- Nitrite and amine free

## **MANUFACTURER'S (OEM) APPROVALS & INDUSTRY LICENSES**

- Audi TL 774-C
- BMW GS 94000
- Deutz DQC CA-14
- Eicher TMTL Part No. 93183798
- Fendt
- Ferrari (1979-2005)
- Huerlimann (to 03/2017)
- Jenbacher TA-Nr. 1000-021
- Lamborghini Tractors (to 03/2017)
- Liebherr LH-00-COL3A
- MAN 324 NF
- MAN Diesel & Turbo Liste 3.3.7
- MB-Approval 326.0
- Mini BMW GS 94000
- Mitsubishi Colt (2004-2007)
- MTU MTL 5048
- MWM 0199-99-2091-9 DE
- Opel / Vauxhall (Until 2000) B 040 0240
- Porsche (Until 1995)
- Rolls Royce (From 1998) BMW GS 94000
- Saab 690 1599
- Same (to 03/2017)
- Seat TL-774-C
- Skoda TL 774-C
- Tesla (From 2013)
- VW TL 774-C



# PENRITE



**85% REDUCTION  
IN LANDFILL  
WASTE**

## PRODUCT PERFORMANCE LEVELS

- AS 2108-2004 Type A
- ASTM D-3306
- Audi G11
- Audi TL 774-C
- Bentley G11
- Bentley TL 774-C
- BS 6580
- Chrysler MS-9769
- Cummins 85T8-2
- Cummins CES MG03
- Deutsche Bundeswehr TL 6850-0038/1
- Deutz AG 0199-99-1115
- Deutz DQC CA-14
- Federal Standard O-A-548D
- Ford M97-B44-A
- Ford M97-B51-A1
- G11
- Glystantin® G48®
- GM 1825M
- GM 1899M
- Holden HN 2043
- Holden HN 2217
- JASO M325 (Japan)
- JCB STD 0088
- Jenbacher TA-Nr. 1000-021
- JI Case JIC 501
- JIS K2234 (Japan)
- John Deere JDM H24
- KSM 2142 (Korea)
- Lamborghini G11
- Lamborghini TL 774-C
- Leyland BLS.22.AF.01
- Liebherr TLV 035, TLV 23009 A
- MAN 324 NF
- MAN BW Liste 3.3.7
- MB 326.0
- Mini BMW GS 94000
- MTU MTL 5048
- Opel / Vauxhall (Until 2000) B 040 0240
- Opel QL 13D100
- Rolls Royce (From 1998) BMW GS 94000
- Rover BLS.22.AF.01
- Saab 690 1599
- SAE J1034
- Seat TL-774-C
- Skoda G11
- Skoda TL 774-C
- Tesla (From 2013)
- Van Hool
- Volvo Truck (From 2005)
- VW G11
- VW TL 774-C
- Zastava

## TYPICAL DATA

Colour	Green
Density at 20°C, kg/L (50% Concentration / Premix)	1.073
Glycol Content, g/L (50% Concentration / Premix)	532