



**100** Celebrating  
**YEARS**

**AUSTRALIAN OWNED AND TRUSTED SINCE 1926** 

# INDGREASE SEMI EP 00

Last updated: 28/01/2026 4:35 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
IGRSEMI00175	175Kg	

## PRODUCT BENEFITS

Indgrease Semi EP 00 is an extreme pressure, NLGI 00 lithium hydroxystearate soap thickened grease, blended using extreme pressure additives, anti wear, rust and oxidation inhibitors.

## APPLICATION

Recommended for use in centralised lubrication systems on trucks, buses, construction, agricultural, and industrial equipment where grease has to be pumped through long lines.

It may also be used in the following applications:

- Trailer bearing hubs where heavy oils are specified and leakage is a problem
- Chain cases and chain drives that require continuous lubrication without oil splash
- Slow speed industrial gearboxes where AGMA 7EP (ISO 460 and above) or heavier oils are specified.
- Worm gears and reduction drives, where slow-speed gears need good coverage and anti-wear protection.
- Lightly loaded bearings, in applications where grease circulation is needed rather than staying packed in place.
- Reduction gearboxes in slasher mowers
- Track rollers in earth moving equipment
- Burman motorcycle gearboxes

Indgrease Semi EP 00 is suitable for veteran/vintage and some classic car steering boxes. It can also be used in some classic car and motorcycle gearboxes that require high viscosity lubrication or a self-levelling grease such as Burman motorcycle gearboxes used in many older motorcycle brands such as AJS, BSA, Ariel and others.

Normal operating temperature range is from -20°C to 120°C.

## PRODUCT BENEFITS

- Extends bearing and gear life by minimising wear and shock loads
- Does not splash so maximises lubrication efficiency
- Resists leakage even under heavily loaded conditions
- Resists squeeze out
- Good low and high temperature fluidity
- Protects against rust and corrosion
- Resistant to water washout
- Suitable to use with yellow metals

## PRODUCT PERFORMANCE LEVELS

- DIN 51502: K00K-20
- ISO 6743-9: L-XBCEA00

## TYPICAL DATA

Thickener	Lithium Hydroxystearate
Colour	Dark Brown
NLGI Grade	00
Base Oil Viscosity, ISO	180
Operating Temperature Range °C	-20 to 120
Drop Point, °C	190
4-ball Weld Load, kg	200

