



PENRITE



85% REDUCTION
IN LANDFILL
WASTE

INDUS COMPRESSOR OIL 8KH ISO 68

Last updated: 23/03/2022 9:08 am

PRODUCT CODE	PACK SIZE	CARTON QTY
CO8KH68020	20L	

PRODUCT BENEFITS

Indus Compressor Oil 8KH ISO 68 (8000 HOURS) is a specialised ashless PAO and Ester based product, designed to provide extended oil drains in both oil-injected and oil-flooded rotary screw compressors. Using the latest advances in compressor additive technology, it will provide exceptional wear protection and reduced varnish build-up.

Indus Compressor Oil 8KH ISO 68 contains a special shear-stable synthetic base oil to help reduce deposit formation.

APPLICATION

Indus Compressor Oil 8KH ISO 68 is designed for use for up to 8000 hours* in the following compressor types:

- Atlas Copco Rotary Screw Compressors
- Champion Compressors
- Compair Rotary Screw Compressors
- Sullair Horizontal Screw Compressors

Indus Compressor Oil 8KH ISO 68 may also be used in the following:

- Reciprocating compressors for up to 1000 hours with air discharge temperatures of up to 150°C.
- Rotary Vane compressors for up to 2000 hours with air discharge temperatures of up to 85°C.
- Centrifugal compressors for 2-5 years with air discharge temperatures of up to 50°C.

Indus Compressor Oil 8KH ISO 68 may also be used as a steam turbine oil and for long drains in circulating systems in industrial machinery, where an ISO 68 grade is required.

PLEASE NOTE:

- This product is not recommended for breathing air unit compressors
- *That air discharge temperatures of over 85°C may result in shorter oil life

PRODUCT BENEFITS

- Up to 8000 hour oil drains
- Reduced system deposits
- Good water demulsibility
- Excellent protection against wear

PRODUCT PERFORMANCE LEVELS

- ISO 68
- SAE MS 1003-2

TYPICAL DATA

Density at 15°C, kg/L	0.853
Viscosity, Kinematic, cSt at 40°C	68
Viscosity, Kinematic, cSt at 100°C	11.0
Viscosity Index	153

