



# PENRITE



85% REDUCTION  
IN LANDFILL  
WASTE

## INDUS GEAR OIL EP 150

Last updated: 06/12/2022 12:26 pm

| PRODUCT CODE | PACK SIZE | CARTON QTY |
|--------------|-----------|------------|
| GO150020     | 20L       |            |
| GO150205     | 205L      |            |

### PRODUCT BENEFITS

**Indus Gear Oil EP** are premium mineral, extreme pressure industrial gear oils, manufactured from highly refined water white base oils and selected sulphur-phosphorus extreme pressure and anti-wear additives.

**Indus Gear Oil EP** oils meet the requirements of API GL-3.

### APPLICATION

**Indus Gear Oil EP** are designed for use in industrial gear boxes including in crushers, hoists, conveyors, winches, machine tools and lathes. They can also be used in chain drives, sprockets, plain and anti-friction bearings and slide guides.

**Indus Gear Oil EP** oils are available in 6 grades - ISO 68, ISO 150, ISO 220, ISO 320 and ISO 460



Please **Note:** A 58mm cap with pouring tap is available to fit 20 litre packs. <https://penriteoil.com.au/products/58mm-plastic-tap>

### PRODUCT BENEFITS

- Compatible with copper alloy components
- Protects against rust and corrosion
- Minimises wear by using effective extreme-pressure additives
- Good oxidation and thermal stability for long life
- Minimises foaming
- Excellent demulsibility

### PRODUCT PERFORMANCE LEVELS

- AGMA 250.04/2005-D94
- API GL-3
- Cincinnati Milacron
- Clean Panel Coker and S-200 Oxidation
- US Steel 224

### TYPICAL DATA

|                                    |       |
|------------------------------------|-------|
| Colour                             | Amber |
| ISO Grade                          | 150   |
| Density at 15°C, kg/L              | 0.889 |
| Viscosity, Kinematic, cSt at 40°C  | 156   |
| Viscosity, Kinematic, cSt at 100°C | 15.1  |
| Viscosity Index                    | 98    |
| Phosphorus, Mass %                 | 0.023 |
| AGMA Grade                         | 4EP   |
| Copper Corrosion, 3 hour at 150°C  | 1b    |