



PENRITE



**85% REDUCTION
IN LANDFILL
WASTE**

INDUS GEAR OIL EP 320

Last updated: 06/12/2022 12:31 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
GO320020	20L	

PRODUCT BENEFITS

Indus Gear Oil EP are premium mineral, extreme pressure industrial gear oils, manufactured from highly refined water white base oils and selected sulphur-phosphorus extreme pressure and anti-wear additives.

Indus Gear Oil EP oils meet the requirements of API GL-3.

APPLICATION

Indus Gear Oil EP are designed for use in industrial gear boxes including in crushers, hoists, conveyors, winches, machine tools and lathes. They can also be used in chain drives, sprockets, plain and anti-friction bearings and slide guides.

Indus Gear Oil EP oils are available in 6 grades - ISO 68, ISO 150, ISO 220, ISO 320 and ISO 460



Please **Note:** A 58mm cap with pouring tap is available to fit 20 litre packs. <https://penriteoil.com.au/products/58mm-plastic-tap>

PRODUCT BENEFITS

- Compatible with copper alloy components
- Protects against rust and corrosion
- Minimises wear by using effective extreme pressure additives
- Good oxidation and thermal stability for long life
- Minimises foaming
- Excellent demulsibility

PRODUCT PERFORMANCE LEVELS

- AGMA 250.04/2005-D94
- API GL-3
- Cincinnati Milacron
- Clean Panel Coker and S-200 Oxidation
- US Steel 224

TYPICAL DATA

Colour	Amber
ISO Grade	320
Density at 15°C, kg/L	0.906
Viscosity, Kinematic, cSt at 40°C	322
Viscosity, Kinematic, cSt at 100°C	25.1
Viscosity Index	95
Phosphorus, Mass %	0.023
AGMA Grade	6EP
Copper Corrosion, 3 hour at 150°C	1b