



100 Celebrating
YEARS

**AUSTRALIAN OWNED AND
TRUSTED SINCE 1926** 

MARINE OUTBOARD 4 STROKE 10W-30 (Semi Syn.)

Last updated: 15/10/2026 11:07 am

PRODUCT CODE	PACK SIZE	CARTON QTY
MAR10W30005	5L	4
MAR10W30020	20L	
MAR10W30205	205L	

PRODUCT BENEFITS

Marine Outboard Four Stroke 10W-30 is a semi syntehctic **NMMA** (National Marine Manufacturers Association) **FC-W®** (Catalyst Compatible) fully licensed and registered petrol engine oil. It contains advanced low ash anti-wear additives combined with specialised rust inhibitors to provide optimum engine protection in marine and salt water environments.

APPROVALS AND LICENSES

- [Click Here](#) for NMMA FC-W(CAT)® Registration Number FC-38116W

APPLICATION

Marine Outboard Four Stroke 10W-30 is designed for use in all types of petrol four stroke outboard, inboard and sterndrive engines where SAE 10W-30 is specified by the manufacturer. It can be used where API SM or earlier specification oils were recommended and where ILSAC GF-4 and ILSAC GF-3 grade oils are specified.

It can be used in personal watercraft engines as well as in inboard and sterndrive petrol engines that require this grade and viscosity.

It is also suitable for use where marine exhaust catalysts are in use.

Suitable for engines made by - :

Evinrude, Honda, Johnson, Mercury, Nissan, Parsun, Suzuki and Yamaha as well as many other manufacturers.

Please note: It is not suitable for use in diesel-fuelled engines.

Please Note: A 58mm cap with pouring tap is available to fit 20 litre packs.
<https://penriteoil.com.au/products/58mm-plastic-tap>



PRODUCT BENEFITS

- Protects against rust in salt water environments
- Registered NMMA FC-W® approved oil
- Superior high temperature wear protection
- Longer engine life
- Ensures correct catalyst operation and life

MANUFACTURER'S (OEM) APPROVALS & INDUSTRY LICENSES

- NMMA FC-W® Registration Number FC-38116W

PRODUCT PERFORMANCE LEVELS

- API SM
- NMMA FC-W®

SUITABLE FOR USE WHERE SPECIFICATIONS BELOW ARE REQUIRED (FOR OUT OF WARRANTY SERVICE)

- ILSAC GF-3
- ILSAC GF-4



100 *Celebrating*
YEARS

**AUSTRALIAN OWNED AND
TRUSTED SINCE 1926** 

TYPICAL DATA

Colour	Amber
Density at 15°C, kg/L	0.872
Viscosity, Kinematic, cSt at 40°C	82
Viscosity, Kinematic, cSt at 100°C	12.0
Viscosity Index	173
Cold Cranking Viscosity, cP at -25°C	6380
Zinc, Mass %	0.085
Phosphorus, Mass %	0.076
Sulphated Ash, Mass %	0.77
Total Base Number (TBN)	6.0