MARINE INBOARD 4 STROKE 25W-40 (Semi Syn.)

Last updated: 09/11/2026 3:43 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
MAR25W40005	5L	4
MAR25W40020	20L	
MAR25W40205	205L	



PRODUCT BENEFITS

Marine Inboard Four Stroke 25W-40 is a semi synthetic **NMMA** (National Marine Manufacturers Association) **FC-W®**, fully licensed and registered petrol engine oil. It contains advanced low ash anti-wear additives combined with specialised rust inhibitors to provide optimum engine protection in marine and salt water environments.

APPROVALS AND LICENSES

- Click Here for NMMA FC-W® License Registration Number FB-13827W

APPLICATION

Marine Inboard Four Stroke 25W-40 is designed for use in inboard/outboards and stern drive petrol engines. It can be used where SAE 25W-40 and SAE 30 oils are required and where FC-W® and FC-W (CAT)® products are specified by the manufacturer.
It is especially suitable for:

Mercruiser	Chevrolet	Chrysler	Indmar	Tohatsu
Mariner	OMC	Nissan	PCM	Volvo Penta

Marine Inboard Four Stroke 25W-40 may be used in some modern petrol engine cars that require API SL oils. Diesel-fuelled engines should use the appropriate Penrite diesel oil.

Please Note: A 58mm cap with pouring tap is available to fit 20 litre packs. https://penriteoil.com.au/products/58mm-plastic-tap

PRODUCT BENEFITS

- Specially formulated for protection for marine salt water environments
- Registered **NMMA FC-W®** approved engine oil
- Complete Anti-wear additive package for maximum wear protection
- Ensures correct catalyst operation and life

MANUFACTURER'S (OEM) APPROVALS & INDUSTRY LICENSES

- NMMA FC-W® Registration Number FB-13827W

PRODUCT PERFORMANCE LEVELS

- API SL
- China National GB 11121-2006
- NMMA FC-W®

PENRITE OIL COMPANY PTY LTD ABN 25 005 001 525
110 Greens Rd, Dandenong South, Victoria 3175 Australia
Phone: 1300-PENRITE (1300 736 748)
Fax: 1800-PENRITE (1800 736 748)

International Ph: +61 3 9801 0877, Fax: +61 (0)3 8710 6601
New Zealand Ph:0800 533 698, Fax: 0508 736 748
Website: www.penriteoil.com.au
Email: penrite@penriteoil.com.au

TYPICAL DATA

Colour	Amber
Density at 15°C, kg/L	0.889
Viscosity, Kinematic, cSt at 40°C	138
Viscosity, Kinematic, cSt at 100°C	14.9
Viscosity Index	109
Cold Cranking Viscosity, cP at -10°C	5722
Zinc, Mass %	0.085
Phosphorus, Mass %	0.077
Sulphated Ash, Mass %	0.77
Total Base Number (TBN)	7.4

PENRITE OIL COMPANY PTY LTD ABN 25 005 001 525
110 Greens Rd, Dandenong South, Victoria 3175 Australia
Phone: 1300-PENRITE (1300 736 748)
Fax: 1800-PENRITE (1800 736 748)

International Ph: +61 3 9801 0877, Fax: +61 (0)3 8710 6601
New Zealand Ph:0800 533 698, Fax: 0508 736 748
Website: www.penriteoil.com.au
Email: penrite@penriteoil.com.au