MARINE OUTBOARD 4 STROKE 10W-30 (Semi Syn.)

Last updated: 09/11/2026 3:42 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
MAR10W30005	5L	4
MAR10W30020	20L	
MAR10W30205	205L	



PRODUCT BENEFITS

Marine Outboard Four Stroke 10W-30 is a semi syntehtic **NMMA** (National Marine Manufacturers Association) **FC-W®** (Catalyst Compatible) fully licensed and registered petrol engine oil. It contains advanced low ash anti-wear additives combined with specialised rust inhibitors to provide optimum engine protection in marine and salt water environments.

APPROVALS AND LICENSES

- Click Here for NMMA FC-W(CAT)® Registration Number FC-38116W

APPLICATION

Marine Outboard Four Stroke 10W-30 is designed for use in all types of petrol four stroke outboard, inboard and sterndrive engines where SAE 10W-30 is specified by the manufacturer. It can be used where API SM or earlier specification oils were recommended and where ILSAC GF-4 and ILSAC GF-3 grade oils are specified.

It can be used in personal watercraft engines as well as in inboard and sterndrive petrol engines that require this grade and viscosity.

It is also suitable for use where marine exhaust catalysts are in use.

Suitable for engines made by - :

Evinrude, Honda, Johnson, Mercury, Nissan, Parsun, Suzuki and Yamahaas well as many other manufacturers.

Please note: It is not suitable for use in diesel-fuelled engines.

Please Note: A 58mm cap with pouring tap is available to fit 20 litre packs. https://penriteoil.com.au/products/58mm-plastic-tap

PRODUCT BENEFITS

- Protects against rust in salt water environments
- Registered NMMA FC-W® approved oil
- Superior high temperature wear protection
- Longer engine life
- Ensures correct catalyst operation and life

MANUFACTURER'S (OEM) APPROVALS & INDUSTRY LICENSES

- NMMA FC-W® Registration Number FC-38116W

PRODUCT PERFORMANCE LEVELS

- API SM
- NMMA FC-W®

SUITABLE FOR USE WHERE SPECIFICATIONS BELOW ARE REQUIRED (FOR OUT OF WARRANTY SERVICE)

- ILSAC GF-3
- ILSAC GF-4

PENRITE OIL COMPANY PTY LTD ABN 25 005 001 525
110 Greens Rd, Dandenong South, Victoria 3175 Australia
Phone: 1300-PENRITE (1300 736 748)
Fax: 1800-PENRITE (1800 736 748)

International Ph: +61 3 9801 0877, Fax: +61 (0)3 8710 6601
New Zealand Ph:0800 533 698, Fax: 0508 736 748
Website: www.penriteoil.com.au
Email: penrite@penriteoil.com.au

TYPICAL DATA

Colour	Amber
Density at 15°C, kg/L	0.872
Viscosity, Kinematic, cSt at 40°C	82
Viscosity, Kinematic, cSt at 100°C	12.0
Viscosity Index	173
Cold Cranking Viscosity, cP at -25°C	6380
Zinc, Mass %	0.085
Phosphorus, Mass %	0.076
Sulphated Ash, Mass %	0.77
Total Base Number (TBN)	6.0

PENRITE OIL COMPANY PTY LTD ABN 25 005 001 525
110 Greens Rd, Dandenong South, Victoria 3175 Australia
Phone: 1300-PENRITE (1300 736 748)
Fax: 1800-PENRITE (1800 736 748)

International Ph: +61 3 9801 0877, Fax: +61 (0)3 8710 6601
New Zealand Ph:0800 533 698, Fax: 0508 736 748
Website: www.penriteoil.com.au
Email: penrite@penriteoil.com.au