MARINE OUTBOARD 4 STROKE 10W-40 (Semi Syn.)

Last updated: 08/07/2026 10:22 am

PRODUCT CODE	PACK SIZE	CARTON QTY
MAR10W40005	5L	4
MAR10W40020	20L	
MAR10W40205	205L	



PRODUCT BENEFITS

Marine Outboard Four Stroke 10W-40 is a premium, semi synthetic **NMMA** (National Marine Manufacturers Association) **FC-W®**, fully licensed and registered petrol engine oil. It contains a **FULL ZINC** anti-wear additive package combined with specialised rust inhibitors to provide optimum engine protection in marine and salt water environments.

APPROVALS AND LICENSES

Click Here for NMMA FC-W License Registration Number FB-13811W

APPLICATION

Marine Outboard Four Stroke 10W-40 Is designed for use in all types of petrol four stroke outboard engines where SAE 10W-40 and SAE 15W-40 oils are specified including:

Honda Johnson Nissan Yamaha
Parsun Suzuki Tohatsu

Marine Outboard Four Stroke 10W-40 is also ideal for use personal water craft (PWC) / inboard & stern drive petrol engines that require this viscosity grade such as:

Honda Kawasaki Sea Doo Yamaha VM

Marine Outboard Four Stroke 10W-40 may also be used in modern petrol-engine cars that require engine oils meeting API SL or earlier specification and/or where ILSAC GF-3 is specified. It is also suitable for use in four stroke motorcycles including those with wet clutches. It is not suitable for use in diesel engines.

Please Note: A 58mm cap with pouring tap is available to fit 20 litre packs. https://penriteoil.com.au/products/58mm-plastic-tap

PRODUCT BENEFITS

- Specially Formulated for protection for marine salt water environments
- Registered NMMA FC-W® approved oil
- Fast start up oil flow with superior high temperature wear protection
- Full Zinc for maximum wear protection

MANUFACTURER'S (OEM) APPROVALS & INDUSTRY LICENSES

- NMMA FC-W® Registration Number FB-13811W

PRODUCT PERFORMANCE LEVELS

- API SL
- China National GB 11121-2006
- JASO MA
- NMMA FC-W®

PENRITE OIL COMPANY PTY LTD ABN 25 005 001 525
110 Greens Rd, Dandenong South, Victoria 3175 Australia
Phone: 1300-PENRITE (1300 736 748)
Fax: 1800-PENRITE (1800 736 748)

International Ph: +61 3 9801 0877, Fax: +61 (0)3 8710 6601
New Zealand Ph:0800 533 698, Fax: 0508 736 748
Website: www.penriteoil.com.au
Email: penrite@penriteoil.com.au

TYPICAL DATA

Colour	Amber
Density at 15°C, kg/L	0.871
Viscosity, Kinematic, cSt at 40°C	94
Viscosity, Kinematic, cSt at 100°C	13.6
Viscosity Index	147
Cold Cranking Viscosity, cP at -25°C	6472
Zinc, Mass %	0.132
Phosphorus, Mass %	0.12
Sulphated Ash, Mass %	0.91
Total Base Number (TBN)	7.4

PENRITE OIL COMPANY PTY LTD ABN 25 005 001 525
110 Greens Rd, Dandenong South, Victoria 3175 Australia
Phone: 1300-PENRITE (1300 736 748)
Fax: 1800-PENRITE (1800 736 748)

International Ph: +61 3 9801 0877, Fax: +61 (0)3 8710 6601
New Zealand Ph:0800 533 698, Fax: 0508 736 748
Website: www.penriteoil.com.au
Email: penrite@penriteoil.com.au