



100 Celebrating
YEARS

**AUSTRALIAN OWNED AND
TRUSTED SINCE 1926** 

MC-2ST FULL SYNTHETIC TWO STROKE OIL

Last updated: 26/05/2025 1:38 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
MC2FULLSYN001CP	1L	6

PRODUCT BENEFITS

MC-2 Full Synthetic Two Stroke Oil is a premium fully synthetic, ester based two-stroke engine oil for maximum power and protection in all two stroke engines. It uses a powerful, practically ashless clean burning high performance additive package for maximum lubricity and low piston deposits.

APPLICATION

MC-2 Full Synthetic Two Stroke Oil is suitable for use in all two stroke engines used in motorcycles on road or in competition, using either a premix or oil injection system. Ideal for the latest direct injection engines.

MC-2 Full Synthetic Two Stroke Oil is suitable for use in scooters, snow mobiles, go karts and Sea Doo jet skis. (other brands of jet ski should use one of the Penrite Marine Outboard Two Stroke oils).

MC-2 Full Synthetic Two Stroke Oil is also suitable for use in lawn mowers, chainsaws, and whipper snippers.

MC-2 Full Synthetic Two Stroke Oil is suitable for use with petrol / E10 and other conventional fuels. It is NOT SUITABLE for use with Methanol or E85.

Note - Not suitable for use in engines used in ultra-light aircraft.

MIXING RATIO CHART

FUEL OIL RATIO	PETROL	OIL
25:1	5 Litre	200ml
50:1	5 Litre	100ml
100:1	5 Litre	50ml

PRODUCT BENEFITS

- **Extends** engine life
- **Superior** anti-scuff properties
- **Synthetic** protection
- Low ash formulation
- Reduces exhaust port blockages
- Keeps piston rings free
- Readily mixes with petrol
- Keeps engines clean
- Exceeds OEM warranty requirements
- Environmentally Friendly - low smoke, biodegradable

PRODUCT PERFORMANCE LEVELS

- API TC
- Aprilia DiTechSR50 (Performance)
- ISO EG-D
- JASO FD
- Piaggio Hexagon (Performance)





100 *Celebrating*
YEARS

**AUSTRALIAN OWNED AND
TRUSTED SINCE 1926** 

TYPICAL DATA

Colour	Deep Red
Density at 15°C, kg/L	0.895
Viscosity, Kinematic, cSt at 40°C	39
Viscosity, Kinematic, cSt at 100°C	7.8
Viscosity Index	175
Sulphated Ash, Mass %	<0.10
Total Base Number (TBN)	2.5
Biodegradability, OECD 301B, %	64
Flash Point, °C	94