



# PENRITE



85% REDUCTION  
IN LANDFILL  
WASTE

## POWER SPORTS COOLANT PREMIX

Last updated: 21/02/2023 4:45 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
COOLPOWERPMX001	1L	6

### PRODUCT BENEFITS

**Power Sports Coolant Premix** is a Type A, low toxic, propylene glycol based, blue coloured anti-freeze anti-boil coolant. It contains low levels of silicate, is phosphate and amine free and is much safer for the environment than standard ethylene glycol based coolants. It uses a hybrid inhibitor to provide long lasting corrosion protection for the entire cooling system.

### APPLICATION

**Power Sports Coolant Premix** is designed for use wherever glycol based coolants are specified in passenger car, light & heavy commercial vehicles, 4WD's, motor cycles, UTV's, marine, mining, agricultural machinery and in industrial applications.

**Power Sports Coolant Premix** is formulated to provide excellent high temperature protection as well as long term corrosion protection for aluminium, cast iron, brass, copper, steel and solder. It has been especially formulated to provide protection for sports machinery such as off road motorcycles, UTV's, jet skis, snow mobiles, and marine engines with closed loop cooling systems.

**Power Sports Coolant Premix** is premixed at 50% concentrate and 50% de-mineralised water and does not require any further dilution. Propylene Glycol has a lower toxicity than either Mono Ethylene or Di-ethylene glycols and is therefore much safer for the environment should spillage occur, whether on land or in a marine habitat.

**Power Sports Coolant Premix** can be used to top up systems containing both OAT and conventional type coolants. We recommend that if a complete fill is required that the system be flushed prior to the introduction of the new coolant.

**Please Note** - **Power Sports Coolant Premix** is not suitable for use for on-road competition applications due to the glycol concentration level. For on road competition applications, we recommend 10 Tenths Race Coolant.

### RECOMMENDED SERVICE INTERVALS

3 Years or 500 Hours - whichever comes first.

### Freezing & Boiling Points

Freezing Point	Boiling Point
-31°C	103°C



### PRODUCT BENEFITS

- Low toxicity compared to Mono Ethylene Glycol based coolants
- Provides long life protection for all metals
- Provides anti-freeze anti-boil protection
- **Note: Premix coolants do not require further dilution with demineralized water**
- Excellent protection for aluminium & heavy diesel wet sleeve liners
- Compatible with both OAT and conventional coolants
- Premixed at 50/50 ratio so no mixing required

### PRODUCT PERFORMANCE LEVELS

- ASTM D-6211
- ASTM D-6257
- TMC RP 330



# PENRITE



**85% REDUCTION  
IN LANDFILL  
WASTE**

## **TYPICAL DATA**

Colour	Dark Blue
Density at 15°C, kg/L	1.07
Glycol Content, g/L	480
pH Range	7.5-9.0