



PENRITE



85% REDUCTION
IN LANDFILL
WASTE

PRO 20 20W-50 (Mineral) (TRADE ONLY)

Last updated: 30/11/-0001 12:00 am

PRODUCT CODE	PACK SIZE	CARTON QTY
PRO20020	20L	

PRODUCT BENEFITS

Pro 20 is a premium quality, SAE 20W-50, premium mineral engine oil developed for use in modern petrol, LPG and light duty diesel (non DPF) engines exclusively by professional workshops and vehicle service centres. It uses a combination of advanced additive technology and a low shear rate viscosity modifier, to ensure additional protection against wear, corrosion, oil oxidation, piston deposits and sludge under tough conditions.

For use where API SM/CF or earlier specification is required, as well as for many other manufacturer applications.

APPLICATION

Pro 20 is designed for use in 4, 6 & 8+ cylinder multi-cam, naturally aspirated, supercharged & turbocharged engines. It is ideal for use in most older and large capacity engines where this viscosity is recommended by the manufacturer.

Pro 20 is recommended where the manufacturer specifies a either SAE 20W-40 or 20W-50 viscosity engine oil. It can also be used where SAE 30 grade engine oil was originally recommended. It can also be used where ambient temperatures are very high or where oil consumption is becoming an issue where SAE 15W-40 was originally specified and in other older worn and larger capacity engines. It may be used where API SM/CF or earlier specifications are required.

VEHICLE & FUEL TYPES

Pro 20 is suitable for use in passenger cars, 4WDs and light duty commercial vehicles running on Petrol, LPG, E10 & Diesel. It is not suitable for use in diesel vehicles fitted with a diesel particulate filter (DPF) that require a low SAPs engine oil.

NOTE: when changing oil, Penrite recommend using **Penrite Engine Flush**, a fast acting, solvent free, engine cleaning formulation that removes engine deposits, sludge and contaminants with the oil service drain. It contains added zinc for engine wear protection and its fast acting formulation works in 10 minutes

Please Note: A 58mm cap with pouring tap is available to fit 7, 10 & 20 litre packs.
<https://penriteoil.com.au/products/58mm-plastic-tap>

PRODUCT BENEFITS

- Can be used where SJ, SL, SG or SF oils were recommended
- Superior performance to older specification engine oils
- **FULL ZINC** anti-wear additive package for ultimate engine wear protection
- Reduces oil consumption & maintains oil pressure
- Catalytic converter compatible
- Ideal for light duty diesel engines

PRODUCT PERFORMANCE LEVELS

- API SM/CF

SUITABLE FOR USE WHERE SPECIFICATIONS BELOW ARE REQUIRED (FOR OUT OF WARRANTY SERVICE)

- API SJ
- API SJ/CF
- API SL
- API SL/CF
- API SM





PENRITE



**85% REDUCTION
IN LANDFILL
WASTE**

TYPICAL DATA

Density at 15°C, kg/L	0.882
Viscosity, Kinematic, cSt at 40°C	175
Viscosity, Kinematic, cSt at 100°C	18.6
Viscosity Index	128
Cold Cranking Viscosity, cP at -15°C	8265
Zinc, Mass %	0.110
Sulphated Ash, Mass %	1.08
Total Base Number (TBN)	8.2