PRO EU 5W-30 (Full Syn) (TRADE ONLY) Last updated: 05/09/2022 3:27 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
PROEU020	20L	
PROEU060	60L	
PROEU205	205L	

PRODUCT BENEFITS

PRO EU is a premium full synthetic, SAE 5W-30 engine oil. It meets and exceeds many manufacturer specifications such as Audi, BMW, Hyundai, Kia, Mercedes-Benz, Mitsubishi, Nissan, Subaru & VW. It is manufactured using advanced mid SAPS (Sulphated Ash, Phosphorus and Sulphur)* additive technology for improved wear protection, fuel economy and reduced emissions.





PRO EU is designed for use in modern 4, 6 & 8+ cylinder multi-cam, multi-valve (including VVT), naturally aspirated, supercharged & turbocharged engines. It is not suitable for Rotary engines.

PRO EU is suitable for use in Volkswagen group vehicles where VW 504 00/507 00 specifications are required for **non-warranty** service. (For warranty service we recommend fully approved**ENVIRO+ 5W-30**). It is also suitable for use where MB 229.31/229.51 and BMW Longlife-04 oils are required in vehicles such as Mercedes-Benz, BMW, Jeep, Chrysler, Dodge & SsangYong. It is also suitable for specific Alfa Romeo, Citroen, Fiat, Kia, Mini, Mitsubishi, Peugeot, Nissan, Hyundai, Saab, Subaru and Suzuki vehicles equipped with a DPF.

VEHICLE & FUEL TYPE

PRO EU is suitable for use in passenger cars, 4WDs & light duty commercial vehicles and is compatible with Petrol, LPG, E10, light duty diesel engines including those fitted with/without DPF's (Diesel Particulate Filters) and most other conventional fuels. It is not recommended for use in four stroke motorcycles with wet clutches.

Note: When changing oil, Penrite recommend using **Penrite Engine Flush**, a fast acting, solvent free, engine cleaning formulation that removes engine deposits, sludge and contaminants with the oil service drain. It contains added Zinc for engine wear protection and its fast acting formulation works in 10 minutes.

Please Note: A 58mm cap with pouring tap is available to fit 7, 10 & 20 litre packs. https://penriteoil.com.au/products/58mm-plastic-tap

PRODUCT BENEFITS

- FULL SYNTHETIC high performance base oil and latest advanced additive packs
- EXCEEDS many manufacturer product vehicle specifications
- LONG LIFE extended engine oil drain intervals
- MAINTAINS OE performance outside of warranty period
- Protection for emission control devices such as DPFs & catalytic converters
- Maximum wear protection, minimum sludge formation & reduced piston deposits
- Superior engine cold start up performance, minimising friction and wear at start-up

PRODUCT PERFORMANCE LEVELS

• ACEA C3 • API SN

SUITABLE FOR USE WHERE SPECIFICATIONS BELOW ARE REQUIRED (FOR OUT OF WARRANTY SERVICE)

- BMW LL-04
- BMW Longlife-04
- MB 229.31
- MB 229.51
- Porsche C30
- VW 504 00
- VW 507 00

International Ph: +61 3 9801 0877, Fax: +61 (0)3 8710 6601 New Zealand Ph:0800 533 698, Fax: 0508 736 748 Website: www.penriteoil.com.au

Website: www.penriteoil.com.au Email: penrite@penriteoil.com.au



TYPICAL DATA

Density at 15°C, kg/L	0.853
Viscosity, Kinematic, cSt at 40°C	67
Viscosity, Kinematic, cSt at 100°C	11.8
Viscosity Index	174
Cold Cranking Viscosity, cP at -30°C	6030
Ca content, Mass %	0.180
Zinc, Mass %	0.088
Phosphorus, Mass %	0.079
Sulphated Ash, Mass %	0.83
Total Base Number (TBN)	8.7