



PENRITE



85% REDUCTION
IN LANDFILL
WASTE

PRO GEAR 70W-75 (100% PAO ESTER)

Last updated: 18/03/2025 2:51 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
PROG70750025	2.5L	4
PROG7075020	20L	

PRODUCT BENEFITS

Pro Gear 70W-75 is a premium full synthetic, high performance gear oil manufactured with **100% PAO & ESTER** synthetic base oils and formulated with the latest additive technology, for smooth operation, long service life and excellent load carrying capacity. It meets the performance requirements of API GL-4 Plus as well as many other manufacturers' requirements.

APPLICATION

Pro Gear 70W-75 is designed for use in manual gearboxes, transaxles and transfer cases in passenger cars, 4wd's and Light commercial vehicles. Ideal for use in manual gearboxes and transfer cases that require automatic transmission fluids and in vehicles suffering from shift quality issues using higher viscosity fluids.

It can be used in -

- BMW, Ford Falcon XR/FPV BA/BF/FG (T-56)
- Holden VY/VZ/VE 6 Speed (T-56), Jaguar S 2.7L D
- Land Rover Discovery 3/Freelander 2
- VW 6 speed gearboxes (non-DSG)
- ZF gearboxes S5-31, S5-39, S6-37 and S6-53

It can also be used where the following part numbers are specified -

- BMW 2300 1434404, BMW 2300 7533513
- Ford 52171VX00, GM1052931
- VW G052171, VW G052178, VW G052798

It can be used in dry clutch DCT and DSG gearboxes such as VW vehicles that require VW G 052 512 and in BMW vehicles requiring BMW MTF LT-3.

Please Note: A 58mm cap with pouring tap is available to fit 20 litre packs.
<https://penriteoil.com.au/products/58mm-plastic-tap>

PRODUCT BENEFITS

- **100% PAO ESTER** base oils for ultimate performance
- Smooth shift feel for the life of the oil
- Enhanced oxidation stability, reduces harmful deposits
- Improved load carrying capacity
- Contains synthetic base oils for longer life
- Will not harm brass or bronze
- Compatible with synchro materials
- Very fast flow at start up for slick gear shifts

PRODUCT PERFORMANCE LEVELS

- API GL-4
- API GL-4 Plus
- MTF BOT 338
- Tremec (T-56)
- ZF TE-ML 11 (manual)

SUITABLE FOR USE WHERE SPECIFICATIONS BELOW ARE REQUIRED (FOR OUT OF WARRANTY SERVICE)

- Ford M2C200-D2
- MB 235.7.
- VW G 052 512





PENRITE



**85% REDUCTION
IN LANDFILL
WASTE**

TYPICAL DATA

Colour	Amber
Density at 15°C, kg/L	0.874
Viscosity, Kinematic, cSt at 40°C	38
Viscosity, Kinematic, cSt at 100°C	7.5
Viscosity Index	177
Zinc, Mass %	0.131
Viscosity, Brookfield at -55°C	109,680