



PENRITE



85% REDUCTION
IN LANDFILL
WASTE

PRO GEAR GL-5 75W-85 (Full Syn)

Last updated: 25/01/2023 10:01 am

PRODUCT CODE	PACK SIZE	CARTON QTY
PROGL5001	1L	6
PROGL50025	2.5L	4
PROGL5020	20L	
PROGL5060	60L	

PRODUCT BENEFITS

Pro Gear GL-5 75W-85 is a premium full synthetic, API GL-5, SAE 75W-85, differential and transaxle gear oil manufactured with a blend of carefully selected synthetic base oils and purpose designed additives including an enhanced wear protection package to provide excellent load carrying ability and longer service life.

APPLICATION

Pro Gear GL-5 75W-85 is optimised for differentials, both hypoid and limited slip, transfer cases, manual transaxles and gearboxes in late model passenger cars, 4WD's and light commercial vehicles that specifically require the use of an API GL-5, SAE 75W-85 viscosity gear oil.

Pro Gear GL-5 75W-85 is suitable for use where MB 235.31, MB 235.62, MB 235.7, ZF TE-ML 18 is specified and where VW TL 521 45-X is required. It may be used in selected manual transmissions that require a SAE 75W-85 viscosity grade with API GL-5 specifications. It can be used to improve shift quality in colder climates where either SAE 75W-90 or SAE 80 API GL-5 oils are specified.

Pro Gear GL-5 75W-85 85 is already dosed with the correct amount of friction additive for use in limited slip differentials, no extra additive is required.

NOTE: For manual gearboxes requiring an API GL-4, SAE 75W-85 viscosity gear oil, we recommend [Penrite Pro Gear 75W-85](#). **Pro Gear GL-5 is NOT a replacement for Pro Gear 75W-85**

PRODUCT BENEFITS

- **FULL SYNTHETIC** base oils for maximum performance, protection and longer life
- **OPTIMISED** for differentials requiring low viscosity API GL-5 fluid.
- **SUITED** to many late model vehicle requirements
- **INCREASED** oxidation stability, reducing harmful deposits
- **ENHANCED** wear protection additive pack
- **SUITABLE** for use in hypoid and limited slip differentials
- **PROVIDES** fuel saving benefits over standard differential oils

PRODUCT PERFORMANCE LEVELS

- API GL-5

TYPICAL DATA

Colour	Amber
Density at 15°C, kg/L	0.880
Viscosity, Kinematic, cSt at 40°C	74
Viscosity, Kinematic, cSt at 100°C	11.4
Viscosity Index	166
Viscosity, Brookfield, cSt @ -40°	36,800
Phosphorus, Mass %	0.140

