



100 Celebrating YEARS

AUSTRALIAN OWNED AND TRUSTED SINCE 1926 

PRO ZERO 0W-20 (Full Synthetic) (TRADE ONLY)

Last updated: 17/07/2025 9:12 am

PRODUCT CODE	PACK SIZE	CARTON QTY
PROZERO020	20L	
PROZERO205	205L	

PRODUCT BENEFITS

Pro Zero is a premium, full synthetic, **SAE 0W-20** engine oil. It uses the latest advances in low to mid SAPS (Sulphated Ash, Phosphorus and Sulphur)* additive technology and features low volatility synthetic base oil that minimises oil loss as well as an enhanced corrosion protection package for ensuring compatibility with ethanol based fuels such as E85.

Pro Zero meets **SP Resource Conserving** and **ILSAC GF-6A** specifications.

Application

Pro Zero is designed for use in modern 4, 6 & 8+ cylinder multi-cam, multi-valve (including VVT), naturally aspirated, supercharged & turbocharged petrol, low emission engines including Hybrids.

Pro Zero may be used where SAE 0W-20, SAE 0W-16 and SAE 5W-20 grade oils are recommended by the manufacturer. It can be used where ILSAC GF-3, GF-4 & GF-5 and GF-6A fuel economy oils are recommended and where API SP, SN Plus or earlier API specifications SM (2004-2010), SL (2001-2004) were recommended.

Pro Zero is an **API SP Resource Conserving** and **ILSAC GF-6A** licensed product, providing improved turbocharger deposit control, oxidation, aeration, fuel economy, fuel economy retention, timing chain and idle stop wear protection and enhanced low speed pre-ignition (LSPI) protection over API SN / ILSAC GF-5 grade oils.

Vehicle and Fuel Types

Pro Zero is suitable for use in passenger cars, 4WD's & light commercial vehicles and can be used with Petrol, Hybrid, LPG, E10 and E85 fuels. It is **NOT** recommended for use in diesel engined vehicles or in motorcycles with wet clutches.

PRODUCT BENEFITS

- **API SP Resource Conserving, ILSAC GF-6A** oil specifications
- **IMPROVED** engine durability, better fuel economy, increased wear protection.
- **ENHANCED** LSPI (Low Speed Pre-Ignition) protection
- **REDUCED** Turbo Charger Deposits
- **BETTER** wear protection for "Idle Stop" engines
- **IMPROVED** oxidation and deposit control and aeration
- **MAXIMISES** fuel economy and engine life
- **CATALYST** and Oxygen sensor friendly
- **ETHANOL** fuel compatible – Safe with E85
- Suitable for **HYBRID** petrol/electric vehicles

PRODUCT PERFORMANCE LEVELS

- API SN Plus Resource Conserving
- API SP Resource Conserving
- ILSAC GF-6A





100 *Celebrating*
YEARS

**AUSTRALIAN OWNED AND
TRUSTED SINCE 1926** 

TYPICAL DATA

Density at 15°C, kg/L	0.847
Viscosity, Kinematic, cSt at 40°C	41
Viscosity, Kinematic, cSt at 100°C	7.9
Viscosity Index	168
Cold Cranking Viscosity, cP at -35°C	5723
Zinc, Mass %	0.089
Phosphorus, Mass %	0.080
Sulphated Ash, Mass %	0.85
Total Base Number (TBN)	8.5