



# PENRITE



85% REDUCTION  
IN LANDFILL  
WASTE

## PRO GEAR GL-4 75W-90 (Full Syn.)

Last updated: 28/08/2024 4:37 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
PROGL4001	1L	6
PROGL40025	2.5L	4
PROGL4020	20L	
PROGL4060	60L	

### PRODUCT BENEFITS

**Pro Gear GL-4 75W-90** is a premium full synthetic, SAE 75W-90 gear oil manufactured from a blend of selected synthetic base oils and formulated with the latest additive technology, for smooth operation, long service life and excellent load carrying capacity. It meets the performance requirements of API GL-4/GL-4 Plus as well as many manufacturers specifications.



### APPLICATION

**Pro Gear GL-4 75W-90** is recommended for manual gearboxes, transfer cases and transaxles in passenger cars, light commercials, 4WDs, trucks, construction, earthmoving and agricultural equipment that specify the use of an API GL-4, SAE 75W-90, 80W-90 or SAE90 gear oil. It is also suitable for use where an API GL-3, SAE 75W-90 gear oil is required.

It is also ideal in vehicles that are operating in highly loaded conditions such as in competition or when towing, in place of where an API GL-4, SAE 75W-85 gear oil is required.

Recommended for use in selected Ford, Holden, Hyundai, Kia, Mazda, Mitsubishi, Nissan, Suzuki and Toyota vehicles as well as many others where the manufacturer specifies the use of an API GL-4, SAE 75W-90 gear oil.

**NOTE:** Pro Gear GL-4 75W-90 is not suitable for use in differentials that require API GL-5 or higher. For these applications please use either **Penrite Pro Gear 75W-90** or **Trans Gear 75W-90**.

**Please Note:** A 58mm cap with pouring tap is available to fit 20 litre packs. <https://penriteoil.com.au/products/58mm-plastic-tap>

### PRODUCT BENEFITS

- Smooth shift feel for the life of the oil drain
- Reduces harmful deposit formation
- Will not harm brass or bronze
- Compatible with synchromesh materials
- Excellent wear protection
- Contains synthetic base oils for long service life

### PRODUCT PERFORMANCE LEVELS

- API GL-4
- API GL-4 Plus
- Ford M2C200-C
- GM 12346190
- GM HN 2013
- MAN 341SL (level)
- ZFN 13010 (level)

### SUITABLE FOR USE WHERE SPECIFICATIONS BELOW ARE REQUIRED (FOR OUT OF WARRANTY SERVICE)

- MB 235.72



# PENRITE



**85% REDUCTION  
IN LANDFILL  
WASTE**

## TYPICAL DATA

Colour	Amber
Density at 15°C, kg/L	0.887
Viscosity, Kinematic, cSt at 40°C	105
Viscosity, Kinematic, cSt at 100°C	17.4
Viscosity Index	180
Viscosity, Brookfield, cSt @ -40°	100,800
KRL Before/After Shear Viscosity	17.2/14.7 (14.5%)
Zinc, Mass %	0.141
Phosphorus, Mass %	0.127
Magnesium, Mass %	0.096