



PENRITE



85% REDUCTION
IN LANDFILL
WASTE

PRO SERIES PETROL COMPLETE CLEAN +

Last updated: 10/01/2024 11:24 am

PRODUCT CODE	PACK SIZE	CARTON QTY
PSPCC0005	500ml	6

PRODUCT BENEFITS

Petrol Complete Clean+ is a professional strength, petrol fuel additive that effectively cleans the entire fuel system from fuel tank to engine. It uses a powerful and proven additive technology that cleans stubborn deposits and inhibits new contaminant build ups forming.

APPLICATION

Petrol Complete Clean+ is suitable for use in all petrol engines. It is safe for use with catalytic converters and oxygen sensors. It can be used in multi-point, direct and throttle body injected systems as well as carburettor fed induction systems. It can be used in either naturally aspirated or forced induction engines.

Petrol Complete Clean+ cleans carbon deposits from inlet valves that can affect engine efficiency and performance. It unblocks fuel injectors improving fuel economy and efficiency. It improves cold starting and provides for smoother idling as well as increased power and acceleration. It also increases the service life of the fuel system components.

Petrol Complete Clean+ dislodges and removes fuel system contaminants especially those found in commercial pump fuel that can affect the engine's performance. Its powerful formulation is designed to clean in one tank of fuel.

Dosage

1 x 500ml bottle treats 100 Litres of Petrol.

Please Note: If your vehicle is fitted with a "Capless" Fuel Filler system, we recommend using the vehicles emergency fuel filling funnel when adding this product to the fuel tank.

Petrol Complete Clean+ should be used every 10,000km to clean, maintain and prevent fuel system deposits being formed. This is particularly important for intake valve deposits that can build up after only 2000km if poor quality fuel is used. Penrite recommend the use of **Penrite Petrol Injector Cleaner** every 2500 KM to maintain maximum benefits of the **Petrol Complete Clean+**.

INDUSTRY SPECIFICATIONS

ASTM D-5500-98(2014) Standard Test Method for Vehicle Evaluation of Unleaded Automotive Spark-Ignition Engine Fuel for Intake Valve Deposit formation

ASTM D-6201 Standard Test Method for Dynamometer Evaluation of Unleaded Spark-Ignition Engine Fuel for Intake Valve Deposit formation

ASTM D-5598-01(2012) Standard Test Method for Evaluating Unleaded Automotive Spark-Ignition Engine Fuel for Electronic Port Fuel Injector fouling

Not Suitable for use with E85 Ethanol Fuel

PRODUCT BENEFITS

- Cleans fuel tank, lines, injectors, carburettors and inlet valves
- Prevents fuel system deposits and contaminants
- Improves power and performance
- Improves fuel economy and reduces emissions
- Improves idling and engine starting
- Reduces fuel consumption
- Safe for emissions systems and oxygen systems

PRODUCT PERFORMANCE LEVELS

- ASTM D-5500-98(2014)
- ASTM D-5598-01(2012)
- ASTM D-6201





PENRITE



**85% REDUCTION
IN LANDFILL
WASTE**

TYPICAL DATA

Colour	Amber
Density at 15°C, kg/L	0.878
Viscosity, Kinematic, cSt at 40°C	6.5
Viscosity, Kinematic, cSt at 100°C	2.3
Flash Point, °C	65