RADIATOR FLUSH

Last updated: 21/08/2023 6:22 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
ADRF375	375mL	6

PRODUCT BENEFITS

Radiator Flush is a fast acting (7 Minute), alkaline cooling system cleaner designed to remove rust, scale and other deposits from automotive cooling systems that could block or foul circulation of coolant though the radiator or engine.

APPLICATION

Radiator Flush is recommended to clean out the cooling system of all types of passenger cars, 4WD's, light & heavy duty commercial vehicles, motorcycles, agriculture, mining, construction and stationary engines.

Radiator Flush is designed to be used prior to new coolant being added to the vehicles cooling system as this will ensure the cooling system is free from rust, scale or any other residue which could block or foul the cooling system and prevent the new coolant from functioning as intended. It will also neutralise any leftover coolant remaining in the engine eliminating compatibility issues if changing coolant types.



Radiator Flush can also be used where any type of coolant has been present in the cooling system and is harmless to all metals, rubber, plastic and seals. We recommend refilling with a quality OEM approved Penrite antifreeze anti-boil coolant such as -

Red OEM Coolant (OEM Approved) Premix

Red OEM Coolant (OEM Approved) Concentrate

Green OEM Coolant (OEM Approved) Premix

Green OEM Coolant (OEM Approved) Concentrate

Blue OEM Coolant (OEM Approved) Premix

Blue OEM Coolant (OEM Approved) Concentrate

350,000KM Green Coolant Premix

350,000KM Green Coolant Concentrate

Universal Top Up Premix

RCI100,000 KM Concentrate

INSTRUCTIONS FOR USE

Use 1 bottle for up to 15 Litres capacity

- · Drain Cooling System
- · Refill radiator with clean water
- Add Radiator Flush to cooling system
- Start Engine and turn on heater
- Run engine for 10 15 minutes, this includes 7 minutes cleaning time
- · Turn off engine, allow to cool
- · Drain cooling system
- Refill with appropriate Penrite Coolant

NOTE - Please read Product Information sheet for more detailed Instructions

PRODUCT BENEFITS

- 1 bottle treats up to 15 Litres capacity
- Fast acting, cleans in 7 minutes
- Removes internal rust & corrosion
- Improves cooling system circulation
- · Harmless to all metals, rubber & water pump seals
- Compatible with all types of coolants
- · Improves cooling system performance
- Non-acidic formulation

PRODUCT PERFORMANCE LEVELS

Website: www.penriteoil.com.au Email: penrite@penriteoil.com.au



TYPICAL DATA

 Colour
 Blue

 Density at 15°C, kg/L
 1.08

 pH
 9.0 - 10.0