



PENRITE



85% REDUCTION
IN LANDFILL
WASTE

RADIATOR OIL REMOVER

Last updated: 22/03/2022 5:06 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
ADROR375	375ml	6

PRODUCT BENEFITS

Radiator Oil Remover is a highly alkaline cooling system flush additive specifically designed to remove oil from an engine's cooling system. It emulsifies oil that has entered the engines cooling system allowing it to be flushed clean.

APPLICATION

Radiator Oil Remover can be used in all types of liquid-cooled engines that are contaminated with engine oil, transmission oil or Hydraulic oil.

Radiator Oil Remover can be poured directly into the radiator, overflow or expansion bottle. It is safe to use and won't harm plastics, hoses, gaskets, seals, header tanks, water pumps, radiator or engine.

DIRECTIONS FOR USE:

- Drain coolant from the system
- Refill with water and add in Radiator Oil Remover directly into the cooling system via radiator or expansion tank.
- Refit radiator cap
- Run vehicle until thermostat opens and leave running for 15 minutes at normal operating temperature to allow Radiator Oil Remover to emulsify oil.
- Drain water and Radiator Oil Remover from the cooling system and refill with new Penrite Coolant

NOTE: Radiator Oil Remover should not be left in the cooling system for longer than needed to flush the system

DOSAGE

375ml treats contaminated cooling systems up to 15 litres in capacity

PRODUCT BENEFITS

- Dissolves oil in cooling system
- Prevents expensive replacement of cooling system parts that have been contaminated
- Safe for cooling system and engine
- Cleans scale, corrosion and rust from the cooling system improving efficiency
- Prepares cooling system for new coolant

PRODUCT PERFORMANCE LEVELS

TYPICAL DATA

Colour	Green
Density at 20°C, kg/L	1.00-1.10
Flash Point, °C	95
pH	14

