



PENRITE



85% REDUCTION IN LANDFILL WASTE

RED OEM COOLANT PREMIX

Last updated: 27/05/2024 9:48 am

PRODUCT CODE	PACK SIZE	CARTON QTY
COOLREDPMX001	1L	6
COOLREDPMX005	5L	3
COOLREDPMX205	205L	

PRODUCT BENEFITS

Red OEM Coolant Premix is a **GENUINE GLYSANTIN® G40® Original Equipment Manufacturer (OEM)**, fully licensed and warranty approved, type "A" ethylene glycol, anti-freeze anti-boil coolant as used in initial manufacturer factory fills. It uses a technically advanced Si-OAT (Organic Acid Technology) based inhibitor system that is Phosphate, Amine, Borate and Nitrite free. The extended long life inhibitor formulation prevents rust, corrosion, cavitation and degradation of the cooling system for 8 years or 500,000km. It is available in both concentrate and premix formulations.

PLEASE NOTE: Red OEM Coolant Premix replaces 8 Year 500,000 KM Red Coolant Premix and 6 Year Extended Drain Anti Freeze Anti Boil Coolant



APPLICATION

Red OEM Coolant Premix is suitable for the cooling systems of petrol, LPG, light and heavy duty diesel engines that require full Si-OAT Type A anti-freeze / anti-boil / anti-corrosion properties.

Red OEM Coolant Premix is suitable for cars, 4WD's, motorcycles, light & heavy duty commercial vehicles, construction and agricultural equipment. It is especially suited to vehicles of European origin such as Audi, Bentley, Bugatti, Lamborghini, VW, Seat and Skoda (all 2008 on), MAN trucks (Dec 2011 on), Mercedes-Benz trucks (Oct 2011 on) and Porsche (911, Boxster, Cayman, Cayenne, Panamera) 1997 onwards.

Red OEM Coolant Premix provides extended long-term protection against rust and corrosion for all materials used in the engine and in the cooling system. It protects cast iron, aluminium, copper and solder alloys as well as the hoses, seals and plastics. It is especially effective in all aluminium engines that are under load or used in extreme hot and cold climates. It may be used in all types of vehicles that use red, magenta or orange coloured initial fill coolants and it is also suitable for use in out of warranty service to maintain OEM performance. It is also ideal for motorcycles.

Red OEM Coolant Premix is a 50% concentration formulation and is ready to use directly from the container. It is pre-mixed with **Penrite De-Mineralised Water** and can be poured directly into the cooling system. No further dilution is required. It can be used as a complete service refill, top up or is safe to mix with compatible type A coolant. Penrite recommend that a 50% concentration level should be maintained for maximum, performance and longevity of the coolant and protection of the cooling system.

COOLANT FLUSHING

Penrite recommend flushing the cooling system prior to a complete service refill. **Penrite Radiator Flush** effectively cleans the system in 7 minutes and prepares the cooling system for new coolant.

DOSE RATE - FREEZING POINT BOILING POINT

Mix Ratio	50%
Freezing Point	-38°C
Boiling Point	+109°C

Please Note: A 58mm cap with pouring tap is available to fit 20 litre packs. <https://penriteoil.com.au/products/58mm-plastic-tap>

PRODUCT BENEFITS

- **8 Year or 500,000 km** (whichever comes first) drain intervals if used and maintained at 50%
- **OEM Approved** to maintain manufacturer's warranty
- Compatible with all plastics, rubbers and seals
- Protects all internal surfaces from corrosion, including aluminium
- **Phosphate free** formulation allows use with hard water
- **Borate, Nitrite and Amine free**



PENRITE



**85% REDUCTION
IN LANDFILL
WASTE**

MANUFACTURER'S (OEM) APPROVALS & INDUSTRY LICENSES

- Audi TL 774-G
- Bentley TL 774-G
- Bugatti TL 774-G
- Cummins CES 14603
- Deutz DQC CC-14
- Deutz Fahr Harvesters (from 04/2017)
- Ducati (Approved)
- Irizar (from 09/2016)
- Lamborghini TL 774-G
- Liebherr Minimum LH-01-COL3A
- MAN 324 Type Si-OAT
- MB-Approval 326.5
- MB-Approval 326.6
- MTU MTL 5048
- Porsche (From 2010)
- Seat TL 774-G
- Skoda TL 774-G
- VW TL 774-G

PRODUCT PERFORMANCE LEVELS

- | | |
|--|--|
| <ul style="list-style-type: none"> • AS 2108-2004 Type A • ASTM D-3306 • Audi TL 774-G • Bentley TL 774-G • BS 6580 • Bugatti TL 774-G • Cummins CES 14603 • CUNA NC 956-16 • Deutz AG 0199-99-1115/2091 • Fiat 9.55523 • Ford M97-B44-D • G12++ • German Army TL6850-0038/1 • Glysantin® G40® • GM 1825M • GM 1899M • GM 6277M • GM Holden 6277M • Jaguar M97-B44-D • JASO M325 (Japan) | <ul style="list-style-type: none"> • Jenbacher TA 1000-0201 • JI Case JIC 501 • JIS K2234 (Japan) • KSM 2142 (Korea) • Lamborghini TL 774-G • MAN 324 Type Si-OAT • MB 326.5 • MB 326.6 • Nissan NES M5059 • Opel B 040 1065 • Renault 41-01-001Q Type D • SAAB GM6277M • SAE J1034 • Scania T1.02-98 0813 • Skoda TL 774-G • Toyota Long Life TSK2601G • UNE 26.361.88 • Vauxhall B 040 1065 • VW TL 774-G |
|--|--|

TYPICAL DATA

Colour	Red
Density at 20°C, kg/L (50% Concentration / Premix)	1.071
Glycol Content, g/L (50% Concentration / Premix)	518