



# PENRITE



85% REDUCTION  
IN LANDFILL  
WASTE

## SMALL ENGINE 4 STROKE SAE 30 (Mineral)

Last updated: 10/10/2023 9:49 am

PRODUCT CODE	PACK SIZE	CARTON QTY
SEFS30001	1L	6
SEFS300025	2.5L	4
SEFS30004	4L	4
SEFS30005	5L	4
SEFS30020	20L	

### PRODUCT BENEFITS

**Small Engine Four Stroke Mono 30** is a premium mineral, non-friction modified engine oil formulated with modern additives for use in small four stroke engines. It provides complete protection against wear & corrosion and is designed to meet the lubrication needs of small four stroke engines. Meets MIL-L-2104B requirements.

### APPLICATION

**Small Engine Four Stroke Mono 30** is suitable for use in small engines in lawnmowers, generator sets and pumps, four stroke outboards / inboards, brushcutters and in other gardening equipment. It is also suitable for use in some 4 stroke motorcycles.

**Small Engine Four Stroke Mono 30** may also be used where in manual gearboxes where the manufacturer specifies a SAE 30 engine oil.

**Small Engine Four Stroke Mono 30** is suitable for use in -

Ariens	Briggs and Stratton	BSA	Clinton
John Deere	Honda	Kohler	Kawasaki
Onan	Robin	Simpson	Tecumseh
Villiers	Toro	Wisconsin	Pope
and many more			



Always check the [Penrite Lube Guide](#) for the correct lubricant application.

**Please Note:** A 58mm cap with pouring tap is available to fit 20 litre packs.  
<https://penriteoil.com.au/products/58mm-plastic-tap>

### PRODUCT BENEFITS

- Excellent engine cleanliness
- Ultimate wear protection.
- Protect against rust and corrosion.

### PRODUCT PERFORMANCE LEVELS

- API SG/CD
- MIL-L-2104B
- SAE 30

### SUITABLE FOR USE WHERE SPECIFICATIONS BELOW ARE REQUIRED (FOR OUT OF WARRANTY SERVICE)

- API SF



# PENRITE



**85% REDUCTION  
IN LANDFILL  
WASTE**

## **TYPICAL DATA**

Colour	Red
Density at 20°C, kg/L	0.894
Viscosity, Kinematic, cSt at 40°C	90
Viscosity, Kinematic, cSt at 100°C	11
Viscosity Index	113
Zinc, Mass %	0.117
Sulphated Ash, Mass %	0.67
Total Base Number (TBN)	6.5