



PENRITE



85% REDUCTION IN LANDFILL WASTE

SMALL ENGINE 4 STROKE 10W-30 (Semi Syn)

Last updated: 05/09/2022 5:00 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
SEFS1030001	1L	6
SEFS10300025	2.5L	4
SEFS1030005	5L	4
SEFS1030020	20L	

PRODUCT BENEFITS

Small Engine Four Stroke Multigrade 10W-30 is non-friction modified, semi synthetic SAE 10W-30 engine oil, formulated with modern additives for use in small four stroke engines. It provides complete protection against wear & corrosion and is designed to meet the lubrication needs of small four stroke engines.

APPLICATION

Small Engine Four Stroke Multigrade 10W-30 is suitable for use in lawnmowers, generator sets and pumps, four stroke outboards / inboards, four stroke brushcutters and in other gardening equipment that specify this viscosity grade.

Small Engine Four Stroke Multigrade 10W-30 is suitable for many 4 stroke motorcycles including those with wet clutches. It can also be used in motor cycles with a separate gear box and clutch assembly as a gear oil where the manufacturer recommends a 10W-30 engine oil for this application.

Small Engine Four Stroke Multigrade 10W-30 is suitable for use in the following engines -

Briggs & Stratton (Selected Models)	Cummins	Graden
Greenfield	Honda	Husqvarna
John Deere	Kawasaki	Kubota
Kohler (Aegis, Command, Triad Series)	Robin	Simplicity
Subaru	Toro	Yamaha
and many more		

4 STROKE OUTBOARDS/MARINE STERN DRIVES*

Evinrude	Johnson	Honda	Tohatsu
Yamaha	Yanmar	and many more	

**May also use Marine Outboard Four Stroke Engine Oil 10W-40*

Please **Note:** A 58mm cap with pouring tap is available to fit 20 litre packs. <https://penriteoil.com.au/products/58mm-plastic-tap>

PRODUCT BENEFITS

- Excellent engine cleanliness
- Ultimate wear protection.
- Protects against rust and corrosion.

PRODUCT PERFORMANCE LEVELS

- ACEA A3/B3
- API SL/CF
- China National GB 11121-2006

SUITABLE FOR USE WHERE SPECIFICATIONS BELOW ARE REQUIRED (FOR OUT OF WARRANTY SERVICE)

- API SF
- API SG
- API SJ/CF





PENRITE



**85% REDUCTION
IN LANDFILL
WASTE**

TYPICAL DATA

Colour	Amber
Density at 15°C, kg/L	0.865
Viscosity, Kinematic, cSt at 40°C	74
Viscosity, Kinematic, cSt at 100°C	11.3
Viscosity Index	145
Cold Cranking Viscosity, cP at -25°C	5805
Zinc, Mass %	0.129
Phosphorus, Mass %	0.118
Sulphated Ash, Mass %	1.31
Total Base Number (TBN)	11.2