



PENRITE



85% REDUCTION
IN LANDFILL
WASTE

SMALL ENGINE 4 STROKE SAE 30 (Mineral)

Last updated: 12/07/2024 1:05 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
SEFS30001	1L	6
SEFS300025	2.5L	4
SEFS30004	4L	4
SEFS30005	5L	4
SEFS30020	20L	

PRODUCT BENEFITS

Small Engine Four Stroke SAE 30 is a premium mineral, non-friction modified, mono grade engine oil. It is formulated with high grade base oils and modern additives for complete protection against wear & corrosion and is designed to meet the lubrication needs of smaller capacity four stroke engines.

APPLICATION

Small Engine Four Stroke Mono 30 is suitable for use in small engines in lawnmowers, generator sets and pumps, four stroke outboards / inboards, brushcutters and in other gardening equipment. It is also suitable for use in some 4 stroke motorcycles.

Small Engine Four Stroke Mono 30 may also be used where in manual gearboxes where the manufacturer specifies a SAE 30 engine oil.

Small Engine Four Stroke Mono 30 is suitable for use in -

Ariens	Briggs and Stratton	BSA	Clinton
John Deere	Honda	Kohler	Kawasaki
Onan	Robin	Simpson	Tecumseh
Villiers	Toro	Wisconsin	Pope

and many more

Always check the [Penrite Lube Guide](#) for the correct lubricant application.

Please Note: A 58mm cap with pouring tap is available to fit 20 litre packs.
<https://penriteoil.com.au/products/58mm-plastic-tap>

PRODUCT BENEFITS

- Excellent engine cleanliness
- Ultimate wear protection.
- Protect against rust and corrosion.

PRODUCT PERFORMANCE LEVELS

- API SG/CD
- MIL-L-2104B
- SAE 30

SUITABLE FOR USE WHERE SPECIFICATIONS BELOW ARE REQUIRED (FOR OUT OF WARRANTY SERVICE)

- API SF





PENRITE



85% REDUCTION
IN LANDFILL
WASTE

TYPICAL DATA

Colour	Red
Density at 20°C, kg/L	0.894
Viscosity, Kinematic, cSt at 40°C	90
Viscosity, Kinematic, cSt at 100°C	11
Viscosity Index	113
Zinc, Mass %	0.117
Sulphated Ash, Mass %	0.67
Total Base Number (TBN)	6.5