TRANSOIL SAE 250

	Correction (4)

PRODUCT CODE	PACK SIZE	CARTON QTY
T250001	1L	6

PRODUCT BENEFITS

Transoil 250 is premium non EP, API GL-1 rated SAE 250 gear oil designed specifically for use in veteran, vintage and Edwardian gearbox, transaxles and selected spur and bevel type rear axles. It does not contain any aggressive load carrying additives that may cause corrosion damage to ferrous and non ferrous metal types used in these types of vehicles.

APPLICATION

Transoil 250 suitable for use in manual transmissions and transaxles in veteran, vintage & Edwardian vehicles.

Transoil 250 is suitable for use in rear axles of veteran cars of one, two and four cylinders. It contains a special additive to help the load carrying ability of the oil. Contact with any water or moisture should be avoided or seal degradation may occur. This oil is compatible with leather and synthetic rubber seals.

Transoil 250 can be used in older style of hypoid gear sets.

Please Note: While this oil has the characteristics of the old 600W or steam cylinder oils, it MUST NOT be used as a steam cylinder oil.

PRODUCT BENEFITS

- Does not corrode ferrous and non-ferrous materials.
- Compatible with leather and synthetic rubber seals.

PRODUCT PERFORMANCE LEVELS

• API GL-1

TYPICAL DATA

Colour	Amber
SAE Grade	250
Density at 15°C, kg/L	0.901
Viscosity, Kinematic, cSt at 40°C	1203
Viscosity, Kinematic, cSt at 100°C	66
Viscosity Index	114



Last updated: 17/09/2021 10:49 am

Email: penrite@penriteoil.com.au