



**100** Celebrating  
**YEARS**

**AUSTRALIAN OWNED AND TRUSTED SINCE 1926** 

## ULTRA HV 100 ZINC FREE (Mineral)

Last updated: 17/10/2025 3:44 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
INDUSHV100020	20L	
INDUSHV100205	205L	

### PRODUCT BENEFITS

**Ultra HV 100 Zinc Free** is a premium quality, ISO 100 HV (**High Viscosity Index**), **Zinc free** (ZF), hydraulic oil made from premium base oils and a highly shear stable viscosity modifier and an organic advanced AW (anti-wear) additive. It is formulated to maintain stable thickness across a wide range of temperatures (hot and cold) for superior viscosity control.

**Zinc Free** (ZF) formulation allows safe use in all environments including marine and agriculture applications. It is also safe for silver and yellow metal parts.

In addition, it is dyed green for easy identification

### APPLICATION

**Ultra HV 100 Zinc Free** is recommended for use in hydraulic systems such as in outdoor mobile equipment (excavators, loaders, cranes, bulldozers, tractors etc), marine, mining, manufacturing, construction, civil, agriculture/harvesting, transport & forestry.

It is recommended for all types of hydraulic systems using vane, piston or gear pumps, air line lubricators, vacuum pumps, lightly loaded gear sets and bearing (such as headstocks, windmill gears) and hydraulic hoists and jacks.

It may be used in machinery manufactured by -

Caterpillar, Doosan (Develon), Hitachi CM, Hyundai CE, JCB, Kobelco, Kobota, Komatsu, Liebherr, Sany, Volvo CE, XCMG and others as well as in components manufactured by Bosch Rexroth, Hågglunds, Danfoss, Eaton, Kawasaki & Parker Hannifin.

**Please Note:** A 58mm cap with pouring tap is available to fit 20 litre packs.  
<https://penriteoil.com.au/products/58mm-plastic-tap>

### PRODUCT BENEFITS

- Combats against rust, foaming & oxidation (oil degradation)
- Reduces sludge and deposits
- Demulsibility properties to provide water separation
- Zinc Free formulation allows no ash residue (ashless)
- Suitable for servo valve systems
- Organic anti-wear (AW) additive to reduce friction and protect metal components
- Can be used over a wide range of temperatures
- Shear stability maintains equipment performance
- Lower start up viscosity increases energy efficiency
- Compatible with silver components
- Coloured green for easy identification

### PRODUCT PERFORMANCE LEVELS

- |  |   |
|--|---|
| • AIST (USS) 126                       | • Eaton Vickers I286-S                  |
| • AIST (USS) 127                       | • Eaton Vickers M-2950-S                |
| • ASTM D6158 (HV)                      | • ISO 11158 (ISO -L-HV)                 |
| • Bosch Rexroth Fluid Rating RDE 90245 | • Kawasaki Heavy Industries JCMAS D-041 |
| • China GB 11118.1 L-HM                | • Komatsu KES 07.841.1                  |
| • China GB 11118.1 L-HV                | • Parker Denison HF-0                   |
| • DIN 51524 Part 3 (HLP/HVLP)          | • Parker Denison HF-1                   |
| • Eaton E-FDGN-TB002-E                 | • Parker Denison HF-2                   |





**100** Celebrating  
**YEARS**

**AUSTRALIAN OWNED AND  
TRUSTED SINCE 1926** 

**TYPICAL DATA**

Colour	Green
ISO Grade	100
Density at 15°C, kg/L	0.871
Viscosity, Kinematic, cSt at 40°C	101
Viscosity, Kinematic, cSt at 100°C	14.5
Viscosity Index	147
FZG Pass Stage	NA
DIN 51382, 30 Cycles After Shear, cSt at 100°C	14.3